Post-Earthquake Data Collection Workshop

Executive Summary

Anchorage, Alaska July 20-22, 2014

Overview and Purpose

A workshop to discuss recent experiences and future needs related to post-earthquake data collection was held in Anchorage, Alaska from July 20 – 22, 2014 with participants from several different countries including New Zealand, Italy, Chile, Japan, Canada, and United States. Due to recent earthquakes in many of the represented countries, the workshop provided a unique opportunity to review data collected internationally, critically evaluate current data collection approaches, initiate collaborative international research efforts to maximize the knowledge gained from recent devastating events, and begin to develop international consensus on data collection protocols for future events.

To achieve a manageable scope, the workshop focused on building-related data. Lifelines such as roadways, power distribution systems, etc. are clearly essential for resilience but such data is generally collected in a systematic manner already since lifelines are typically managed by a single entity. Data collection for private buildings is considerably more challenging. Data of interest to this workshop include building performance, business interruptions, housing impacts and post-earthquake decisions.

Support and funding for this workshop was provided by the University of British Columbia, Ministry for Business Innovation and Employment (New Zealand), and the Earthquake Engineering Research Institute via its the National Science Foundation grant entitled "Seismic Observatory for Community Resilience - A Program to Learn from Earthquakes" (Award No: 1235573).



Participants of Post-Earthquake Data Collection Workshop, Anchorage, Alaska, July 2014

Workshop Procedure

On Day 1 workshop participants from Italy, Japan, New Zealand, and Chile shared their experiences with data collection and data use after recent earthquakes. A few other presentations also were given to share lessons from recent efforts to measure resilience, summarize the key features and challenges of data collection tools developed by a variety of organizations, and hear perspectives from the insurance and risk modeling communities. These presentations prompted discussion and prepared participants for the next day of breakout discussions. The workshop purpose and agenda can be found in Appendix I and the Day 1 presentations can be found in Appendix II.

On Day 2, workshop participants broke into three groups for half-day discussions on data collection protocols for the following three topics areas: Physical Damage Data (led by Santiago Pujol), Impact Data (led by Mary Comerio), and Reconstruction and Recovery Data (led by Stephanie Chang). The groups were asked to consider and reach consensus on (1) "Why do we collect data?",(2) "What do we collect?", and (3) "How do we collect this data?" Summary presentations of these Day 2 breakout discussions can be found in Appendix III.

The final event of the workshop was a two-hour conclusion-generating discussion based upon the outcomes of the Day 2 breakouts. The resolutions and action items from this discussion are summarized below, after brief summaries of the breakout sessions.

Damage Data Breakout

Building damage data is collected for several purposes following an event: guide immediate response and building management (e.g. placarding); identify knowledge gaps; collect damage statistics; assesses repair actions; insurance evaluation; and forensic studies. Data from the latter three purposes are not typically easily accessible due to privacy considerations. Different data will be collected depending on the purpose but common links between the data collected would serve to reduce duplication of effort. Discussants identified data fields to be collected under the following categories: Earthquake, Structure, and Consequences (Appendix AIII, pp. A431-A441). To avoid the restrictions of established checklists, damage descriptions can use narratives if standard terms and keywords are identified in advance.

The importance of having a representative sample, including both damaged and non-damaged buildings, was emphasized, particularly when using the data for damage statistics. This highlights the need for pre-earthquake data on buildings. In addition of helping with the selection of a representative sample, pre-earthquake data enables post-earthquake building management and improved assessment of building safety given better knowledge of structural system.

Research needs were identified for potential collaborative research proposals. In particular, it is critical to establish and validate methods for measuring the residual capacity of damaged building structures. Development of such a method will also inform the post-earthquake data collection needs.

Impact Data Breakout

Impact data represents a holistic view of the impact on the social, economic and natural environments as a consequence of damages to the physical environment. The critical sectors include but are not limited to: Housing, Health, Education, Economy (Jobs), Environment, Communication, Lifeline operability, and the Safety of Civil Society. For each sector, it is important to define critical metrics and

recognize the need for baseline data of what existed before as well as after the event. The discussants recognized that there could be barriers to access for such data. However, the value of such information cannot be overstated. Impact data connects the physical damage with operational effectiveness—to define building functions by structure type and link loss/damage with disruption of service.

Minimum parameters for a baseline and post event data include: Population of the impacted area (make up by census); the percent Urbanized vs non-urbanized; the number of Dwelling Units (+ types), the number of Hospitals/beds (+types); the number of Schools (+types); the number of Government buildings; the number of Industrial/commercial buildings; economic Productivity of the impact area; Ground Surface Changes and Lifeline Status; to be linked with Structural and Non-Structural Damage.

Discussants were clear that data protocols would be critical and suggested existing examples such as the GEM consequence protocols, the World Health Organization reports, Sphere Standards, UNDAC and other existing models as a starting point. In addition the discussants made the case that the engineering community needs to take ownership of functionality requirements to improve Performance Based Design. See notes in Appendix AIII, pp. A442 - A446.

Recovery Data Breakout

In addition to general research purposes, data collection during recovery is primarily intended to inform decision makers on "how recovery is proceeding". The specific question to be addressed with the collected data depends on the phase of response and recovery as shown in figure below. Identification of data to be collected for each phase will assist in decision making after future events.

| 4 | Social | Basic services | Wellbeing, risk perception | |
|--------------|----------|---------------------------------|--|-----------------|
| Type of Data | Physical | Can the building be used? | What do you do with the building? (demolition decision) | Code changes |
| Туре | Hard | | | |
| | | Emergency | Reconstruction | Recovery |
| | | | Time | , |

The following categories of data were identified by the discussants: Damage; Rebuilding; Functionality; Decisions; Economics; Behavior; Population; Perceptions. Types of data under each of these categories were identified and listed in Appendix AIII, pp. A447 - A453. Interviews with staff and general population will be an important data source for many of the categories identified.

Multiple sources and approaches to data collection are needed to achieve a complete picture of "how recovery is proceeding". In particular, linking different data sources and types (e.g., buildings with owners/tenants; business actions/time/impact) is key to understanding cause and effect during recovery. The importance of making data public and available to all was emphasized during the breakout session.

Resolutions

Empirical evidence from past earthquakes, documented through standardized collection of data, is essential to understanding and improving community resilience to earthquake disasters. The participants involved in this workshop are dedicated to reducing earthquake risk and increasing resilience of communities to future earthquakes by enhancing and improving the practice of pre- and post-earthquake data collection worldwide. To this end, the participants at this workshop resolve to:

- 1. Cooperate in future post-earthquake data collection and sharing efforts to the extent possible.
- 2. Promote a culture of open sharing of data in the field of earthquake engineering, similar to other scientific fields;
- 3. Work toward international agreements that will support standardization, interoperability, and sharing of data collected worldwide;
- 4. Collaborate in the development of a document identifying why post-earthquake data collection is critical to understanding and improving community resilience and use this document to promote the importance of standardized data collection with government agencies involved with post-earthquake recovery;
- Establish lines of communication and relationships with data collectors and agencies that will be involved in future earthquake response and recovery in an attempt to initiate pre-earthquake data collection and coordinate data collection and sharing after future earthquakes;
- 6. Explore the creation of a standardized taxonomy that describes damage, impacts, and recovery;
- 7. Explore means of validating and assigning quality ratings to post-earthquake data;
- 8. Promote the development of inventories of existing infrastructure to benchmark existing conditions, train users in data collection tools, and be available immediately post-earthquake to improve data collection and damage assessments;
- 9. Promote the development of standardized damage descriptions for building structures to enable comparison of performance across an inventory of buildings and estimate building residual capacity;
- 10. Compile a list of common models used to quantify recovery/risk/vulnerabilities that would inform the types and amounts of data to be collected to calibrate the models.

Planning details of the above resolutions will be carried out based on further mutual agreement and through close consultation and exchange of information between the workshop participants.

Action Items

Discussion led to the following action items to be implemented by the workshop participants.

- 1. Gather and translate data collection forms and protocols from each country in one place to allow others to review and study.
 - EERI staff will lead this effort and host forms on an EERI website.
- 2. Create working groups to consider how to attract funding to provide time and resources to act on the many ideas discussed in the meeting and included in the resolutions, considering but not limited to the following themes:
 - a. Standardization (for consistency and international interoperability of data)

- b. Defining value of data collection
- c. Consideration of categorizing data under time and purpose
- 3. Create a working group (perhaps the meeting conveners) to develop a short opinion paper based upon notes and outcomes of this workshop.
- 4. Conduct a case study exercise to share existing data from recent earthquakes amongst workshop participants. This case study exercise could explore opportunities and challenges to sharing protocols, test data sharing platforms and approaches, and help inform the development of an international taxonomy or data framework to standardize data.

Appendix

| I | Meeting Description, Proposed Agenda, and Participant List | A1 |
|-----|--|------|
| II | Sunday July 20 Presentations: | A7 |
| | Welcome/introduction Slides | A8 |
| | Italy | A20 |
| | Chile | A110 |
| | New Zealand | A248 |
| | Japan | A303 |
| | Resilience Observatory | A402 |
| | Data Collection Tools | A409 |
| | Insurance Industry Notes | A427 |
| III | Monday July 21 Discussion Summary Presentations & Notes: | A429 |
| | Tuesday Wrap-up Discussion Agenda | A430 |
| | Monday Session Summary: Physical Damage Data | A431 |
| | Monday Session Summary: Impact Data | A442 |
| | Monday Session Summary: Reconstruction and Recovery Data | A447 |
| | Notes from Tuesday Comments & Participant Observations | A454 |

Appendix I

Post-Earthquake Data Collection Workshop

Anchorage, Alaska July 20-21, 2014

Background:

The world has experienced unprecedented losses from earthquakes in recent years. For example, in Christchurch, New Zealand, the impacts of the February 2011 M6.3 earthquake include an estimated \$40 billion in losses (equivalent to 20% of New Zealand's GDP), demolition of ~70% of downtown buildings, including loss of more than 50% of heritage structures, expropriation of hundreds of homes in liquefied suburban regions, closure of the core business district for over 2 years, and outmigration of thousands of residents. Over the past five years, earthquakes have also impacted urban regions in Italy, Chile, and Japan, among many others. While devastating for the communities struck by the earthquakes, these events and their impacts present the international research and policy-development communities with unparalleled opportunities. This proposal aims to harness these opportunities through the development of an international workshop on post-earthquake data collection.

Empirical evidence from past earthquakes is essential to understanding and improving community resilience to earthquake disasters; however, we currently lack consensus on what data to collect, how to collect the data, and how to most effectively use it. Recent earthquakes around the world provide us with an opportunity to review data collected internationally, critically evaluate current data collection approaches, and initiate collaborative international research efforts to maximize the knowledge gained from recent devastating events and arrive at international consensus on data collection protocols for future events.

Workshop objectives:

The objectives of the workshop are:

- To report on data collection practices from recent earthquakes: What data were collected? How were the data collected? What worked? What did not work? What data were lost?
- Initial development of consensus-based data collection protocols.

To achieve a manageable scope, this workshop will focus on building-related data. Lifelines such as roadways, power distribution systems, etc. are clearly essential for resilience but such data is generally collected in a systematic manner already since lifelines are typically managed by a single entity. Data collection for private buildings is considerably more challenging. Data of interest to this workshop include building performance, business interruptions, housing impacts and post-earthquake decisions (repair vs demolish).

It is also anticipated that the workshop may lead to the development of international collaborative projects using empirical data from recent earthquakes to assess and improve community resilience in the event of major earthquakes.

Participants:

This unique multi-disciplinary workshop will include participants from six different countries: Canada, United States, New Zealand, Italy, Chile, and Japan. Notably, the latter four counties have all experienced devastating earthquakes in the past five years, thus the workshop will provide the

opportunity to share recent experiences and develop new partnership with international colleagues with common interests.

All international participants bring direct experience in data collection after recent earthquakes in their respective countries. Data have been collected by both government agencies and academic institutions, and hence both will be represented at the workshop. Notably, a representative from the insurance and reinsurance industry has been asked to contribute some remarks that will share the industry's perspective and assist in identifying potential sources of funding for collaborative research proposals from this important industry.

In order to keep the workshop effective, the number of participants will be limited to approximately 30, with the majority of participants bringing first-hand recent experience with data collection in Chile, Italy, Japan, and New Zealand.

Recent Earthquakes:

A critical portion of the workshop will be reports from Italy, Chile, New Zealand, and Japan on data collection experiences after recent earthquakes. Each country's participants will work together to develop a 75 min presentation (followed by 15 minutes of questions) to be given on Day 1 of the workshop. This presentation should be coordinated by one representative from each country but can be delivered by multiple participants if this format is preferred. To provide consistency in the reporting and valuable information for the Day 2 breakouts, we ask that the country reports address the following questions:

- 1. What forms of data were collected after the earthquake? Data of interest to this workshop include building performance (physical damage), business interruptions, housing impacts, and post-earthquake decisions (repair vs demolish). We are interested in data at both the detailed building level as well as at the broader community level. What data were used to assess building residual capacity and how were these data used in reconstruction decisions? What should be implemented in data collection protocols to make the assessment of residual capacity more reliable?
- 2. Have any relationships between the different forms of data been explored? For example, what is the relationship between the physical damage and business interruption? Are there other factors influencing the socio-economic impacts, suggesting other forms of data that should be collected?
- 3. What organizations were involved in collecting data and for what purpose? Such organizations may include city government, insurance companies, university researchers, etc. Although the goal of data collection may be different for each organization, the data may be similar and synergistic efforts should be identified.
- 4. What barriers are there to sharing data across different organizations? What experience do you have in finding ways to share data across government and non-government entities?
- 5. **How were the data collected?** Were any advanced technologies used to collect data or were all data collected manually? What training was provided for data surveyors?
- 6. **What data were lost?** Were there specific data that were not collected, or not collected in a coordinated manner, such that the data may not be available for future research studies?

- 7. **Lessons from the data collection process.** What aspects of the data collection process seemed to work well? What could be improved upon?
- 8. How are data stored after collection and what are access policies for this data?
- 9. Suggestions for the development of consensus-based data collection protocols? One of the primary goals of the workshop is the initial development of consensus-based data collection protocols for application after future earthquakes around the world. What experiences from the events in your country could inform the development of these data collection protocols?

Expected outcomes:

The workshop is expected to provide the impetus for the development of two types of joint international research proposals: (1) focused on the development of consensus-based data collection protocols; and (2) focused on using empirical data from recent earthquakes to assess and improve community resilience.

For proposal type #1, funding will be sought from public-private partnerships between government agencies responsible for collecting data for the recovery process and the insurance industry interested in rich data to refine natural hazard risk models. This effort is urgently needed to ensure improved and consistent data collection protocols are available prior to the next major earthquake such that valuable data are not lost in the future. Application of the proposed procedures in future earthquakes will provide an excellent opportunity to continue collaborative efforts initiated at the workshop.

For proposal type #2, joint funding will be sought from several national research agencies. Such proposals will build on a US National Science Foundation grant held by the Earthquake Engineering Research Institute to create a Seismic Observatory for Community Resilience with the goal of documenting and understanding the factors influencing the ability of communities to recover after devastating earthquakes. Linkages with new proposals to other national research agencies will be explored to enable international workshop participants to contribute to future joint research projects.

Timing and venue:

The workshop will be held over 1.5 days immediately prior to the 10th US National Conference in Earthquake Engineering in Anchorage, Alaska, in July 2014. This international conference draws participants from around the globe, and hence provides the perfect opportunity to host the proposed workshop. Travel costs will be covered by the participants as it is expected that they will be attending the conference regardless of the workshop. The workshop will be held in the NCEE conference hotel, the Anchorage Hilton.

Proposed Agenda:

The first day will focus on experiences from recent earthquakes, while the second day will provide an opportunity to discuss the development of post-earthquake data collection protocols and future collaborative activities.

Sunday, July 20, 2014

| 8:00 am – 8:30 am | Breakfast |
|---------------------|---|
| 8:30 am – 8:50 am | Welcome and objectives of the workshop |
| 8:50 am – 10:20 am | Italy experience (group organized presentation) |
| 10:20 am – 10:40 pm | Break |
| 10:40 am – 12:10 pm | Chile experience (group organized presentation) |
| 12:10 pm – 1:00 pm | Lunch |
| 1:00 pm – 2:30 pm | Japan experience (group organized presentation) |
| 2:30 pm – 2:45 pm | Break |
| 2:45 pm – 4:15 pm | New Zealand experience (group organized presentation) |
| 4:15 pm – 4:35 pm | Resilience Observatory (Scott Miles) |
| 4:35 pm – 4:50 pm | Break |
| 4:50 pm – 5:10 pm | Data collection tools (EERI) |
| 5:10 pm – 5:30 pm | Data collection and collaboration with (re)insurance industry (tentative) |
| 5:30 pm – 6:00 pm | Discussion and plans for Day 2 |
| 6:00 pm – 7:00 pm | Reception |

Monday, July 21, 2014

| 7:30 am – 8:00 am | Breakfast | | | | | | |
|---------------------|--|------------------|--------------------|--|--|--|--|
| 8:00 am – 9:30 am | Data Collection Protocols Discussion: (moderators) | | | | | | |
| | Breakout 1: | Breakout 2: | Breakout 3: | | | | |
| | Physical Damage Data | Impact Data | Reconstruction and | | | | |
| | (Santiago Pujol) | (Mary Comerio) | Recovery Data | | | | |
| | | | (Stephanie Chang) | | | | |
| 9:30 am – 9:50 pm | Break | | | | | | |
| 9:50 am - 11:30 am | Breakout 1 cont. | Breakout 2 cont. | Breakout 3 cont. | | | | |
| 11:30 am – 12:00 pm | Box lunch and planning for evening meeting | | | | | | |

Tuesday, July 22, Evening meeting:

| 5:00 pm – 7:00 pm | Workshop resolutions and action items for collaborative proposals |
|-------------------|---|
| | (with hors d'oeuvres) |

Participant List:

| | Name | email | Country | Organization |
|----------|--------------------------------|---|-------------------|----------------------|
| 1 | Andrew King | A.King@gns.cri.nz | NZ (coord) | GNS |
| 2 | Peter Wood | srlnprw@gmail.com | NZ | Min of Civil Defence |
| 3 | David Johnston | David.Johnston@gns.cri.nz | NZ | GNS |
| 4 | Mike Stannard | Mike.Stannard@mbie.govt.nz | NZ | MBIE |
| 5 | Quincy Ma | q.ma@auckland.ac.nz | NZ | Univ. of Auckland |
| 6 | Stefano Pampanin | stefano.pampanin@canterbury.ac.nz | NZ | Univ. of Canterbury |
| | | | | Holmes Consulting |
| 7 | John Hare | JohnH@holmesgroup.com | NZ | Group |
| 8 | Andrea Prota | andrea.prota@unina.it | Italy (coord) | UNINA |
| 9 | Maria Polese | mapolese@unina.it | Italy | UNINA |
| 10 | Marco Di Ludovico | diludovi@unina.it | Italy | UNINA |
| 11 | Gian Paolo Cimellaro | gianpaolo.cimellaro@polito.it | Italy | Torino |
| 12 | Paolo Bazzurro | pbazzurro@gmail.com | Italy | IUSS |
| 13 | Juan Carlos de la Llera | jcllera@ing.puc.cl | Chile (coord) | PUC |
| | | | | |
| 14 | Rene Lagos | rlagos@renelagos.com | Chile | Rene Lagos Engineers |
| 15 | Matias Hube | mhube@ing.puc.cl | Chile | PUC |
| | | | US (collaboration | |
| 16 | Judy Mitrani-Reiser | jmitrani@jhu.edu | with Chile) | John Hopkins |
| 17 | Toshimi Kabeyasawa | kabe@eri.u-tokyo.ac.jp | Japan (coord) | Univ. of Tokyo |
| 18 | Tomohisa Mukai | t_mukai@kenken.go.jp | Japan | BRI |
| 19 | Masaki Maeda | maeda@archi.tohoku.ac.jp | Japan | Tohoku Univ. |
| 20 | Satoshi Tanaka | tanaka_s@fuji-tokoha-u.ac.jp | Japan | Tokoha Univ. |
| 21 | Sam Kono | kono@serc.titech.ac.jp | Japan | Tokyo Tech |
| 22 | Koichi Kusunoki | kusunoki@eri.u-tokyo.ac.jp | Japan | Univ. of Tokyo |
| 23 | Toshikazu Kabeyasawa | kabeyasawa-t92ta@nilim.go.jp | Japan | MLIT |
| | 0 | | | Western Washington |
| 24 | Scott Miles | scott.miles@wwu.edu | US | Univ. |
| 25 | Mary Comerio | mcomerio@berkeley.edu | US | UC Berkeley |
| 26 | Steve Mahin | mahin@bekeley.edu | US | PEER |
| 27 | Vesna Terzic | vesna@berkeley.edu | US | PEER |
| 28 | Santiago Pujol | spujol@purdue.edu | US | Purdue |
| 29 | Ken Elwood | elwood@civil.ubc.ca | Canada | UBC |
| 30 31 | Stephanie Chang Sean Wilkinson | stephanie.chang@ubc.ca Sean.wilkinson@ncl.ac.uk | Canada UK | UBC Newcastle Univ. |
| 21 | Students | Scan.wiikiiison@nci.dc.uk | UK | ivewcastie Ulliv. |
| 32 | Frederic Marquis | frederic.marquis@usherbrooke.ca | Canada | UBC |
| 33 | Jenna Kim | jenna.jh.kim@gmail.com | Canada | UBC |
| 34 | Panos Galanis | pgalan@berkeley.edu | US | UC Berkeley |
| 54 | Staff | pgaiane beineley.edu | 03 | OC DELKEIEY |
| 35 | Marjorie Greene | mgreene@eeri.org | US | EERI |
| 36 | Heidi Tremayne | heidi@eeri.org | US | EERI |
| 37 | Maggie Ortiz | maggie@eeri.org | US | EERI |
| 38 | Alex Julius | alex@eeri.org | US | EERI |
| 39 | Eddie Vega | ejvega@eeri.org | US | EERI |
| 40 | Erik McAdams | emcadams@eeri.org | US | EERI |
| 40 | LIIK IVICAUAIIIS | emcadams@eem.org | US | LENI |

Appendix II: Sunday July 20 Presentations

International Post-Earthquake Data Collection Workshop

Sponsored by

EERI

UBC

MBIE - NZ

Thank you

- Co-Organizer, Stephanie Chang
- Marjorie Greene, Heidi Tremayne, Maggie Ortiz @ EERI
- Student and intern support
 - Panagiotis Galanis
 - Jenna Kim
 - Frederic Marquis

• All of you!

Workshop motivation

- Empirical evidence from past earthquakes is essential to understanding and improving community resilience to earthquake disasters.
 - However, we currently lack consensus on what data to collect, how to collect the data, and how to most effectively use it.
- 10NCEE provides opportunity to consider lessons from recent earthquakes regarding postearthquake data collection.
 - Italy, Chile, New Zealand, Japan

Workshop objectives

- To report on data collection practices from recent earthquakes:
 - What data were collected?
 - How were the data collected?
 - What worked?
 - What did not work?
 - What data were lost?
- Initial development of consensus-based data collection protocols and strategizing about what data matters.
- Initiate discussions on joint international research proposals on related topics.

Workshop scope

- Buildings
 - Lessons may come from lifeline data collection
- Data types:
 - building performance,
 - business interruptions,
 - housing impacts,
 - post-earthquake decisions (eg repair vs demolish)

Workshop questions

- What forms of data were collected after the earthquake?
- Have any relationships between the different forms of data been explored?
- What organizations were involved in collecting data and for what purpose?
- What barriers are there to sharing data across different organizations?
- How were the data collected?
- What data were lost?
- Lessons from the data collection process.
- How are data stored after collection and what are access policies for this data?
- Suggestions for the development of consensus-based data collection protocols?

Additional points to frame discussions

- What are the decisions that need to be made (on buildings) post-EQ and how will data help this decision making?
 - e.g. data for deciding fate of building (demolition), data for zoning?
- What data is needed for evaluating and adapting technical decisions?
- Need to identify two forms of links:
 - "links" that allow interoperability between data collected by different entities
 - "links" between physical damage, impact, and recovery data → to inform reconstruction policy.
- Bear in mind time frames
 - What is the minimum data to collect in the first weeks following, vs comprehensive collection later, vs data to assess residual capacity for decisions on demolitions.
- Recommendations coming out of this workshop could:
 - benefit decision-makers in earthquake-struck communities in the future, and
 - advance knowledge about earthquake disasters/recovery

Sunday Agenda

| 8:00 am – 8:30 am | Breakfast | | |
|---------------------|--|----------|--------|
| 8:30 am – 8:50 am | Welcome and objectives of the workshop | | |
| 8:50 am – 10:20 am | Italy experience (group organized presentation) | | |
| 10:20 am – 10:40 pm | Break | | |
| 10:40 am – 12:10 pm | Chile experience (group organized presentation) | | |
| 12:10 pm – 1:00 pm | Lunch (Bristol Bay BallroomKatmai room) | | |
| 1:00 pm – 2:30 pm | New Zealand experience (group organized presentation | ion) | |
| 2:30 pm – 2:50 pm | Resilience Observatory (Scott Miles) | | |
| 2:50 pm – 3:10 pm | Break | Shuffled | |
| 3:10 pm – 3:30 pm | Data collection tools (EERI) | presenta | tionsl |
| 3:30 pm – 5:00 pm | Japan experience (group organized presentation) | presenta | |
| 5:00 pm – 5:15 pm | Break | | |
| 5:15 pm – 5:35 pm | Data collection and collaboration with (re)insurance | industry | |
| | (Paolo Bazzurro) | | |
| 5:35 pm – 6:00 pm | Discussion and plans for Day 2 | | |
| 6:00 pm – 7:00 pm | Reception (Bristol Bay BallroomKatmai room) | | |

- Time will be made for discussion
- Keep notes for further discussion in breakouts tomorrow.

Monday Agenda

Breakouts: Alaska Ballroom - Aleutian, 2fl; Lupine, 1fl; Chartroom, 15fl

| 7:30 am – 8:00 am | Breakfast | | | | | | | |
|---------------------|-----------------------|--------------------------|--------------------|--|--|--|--|--|
| 8:00 am – 9:30 am | Data Collection Proto | cols Discussion: (modera | ators) | | | | | |
| | Breakout 1: | Breakout 2: | Breakout 3: | | | | | |
| | Physical Damage Data | Impact Data | Reconstruction and | | | | | |
| | (Santiago Pujol) | (Mary Comerio) | Recovery Data | | | | | |
| | | | (Stephanie Chang) | | | | | |
| 9:30 am – 9:50 pm | Break | | | | | | | |
| 9:50 am - 11:30 am | Breakout 1 cont. | Breakout 2 cont. | Breakout 3 cont. | | | | | |
| 11:30 am – 12:00 pm | Box lunch and plannir | ng for evening meeting | | | | | | |

- Please assist in an even distribution in the breakouts
- EQ Country participants: at least one person to each breakout please

Tuesday evening

Boardroom, 2fl; Dena'ina Convention Center

| 5:00 pm – 7:00 pm | Workshop resolutions and action items for collaborative |
|-------------------|---|
| | proposals |
| | (with hors d'oeuvres) |

Thank you!

Sunday Agenda

| 8:00 am – 8:30 am | Breakfast | | |
|---------------------|--|-----------|--------|
| 8:30 am – 8:50 am | Welcome and objectives of the workshop | | |
| 8:50 am – 10:20 am | Italy experience (group organized presentation) | | |
| 10:20 am – 10:40 pm | Break | | |
| 10:40 am – 12:10 pm | Chile experience (group organized presentation) | | |
| 12:10 pm – 1:00 pm | Lunch (Bristol Bay BallroomKatmai room) | | |
| 1:00 pm – 2:30 pm | New Zealand experience (group organized presenta | ion) | |
| 2:30 pm – 2:50 pm | Resilience Observatory (Scott Miles) | | |
| 2:50 pm – 3:10 pm | Break | Shuffled | |
| 3:10 pm – 3:30 pm | Data collection tools (EERI) | presentat | ions |
| 3:30 pm – 5:00 pm | Japan experience (group organized presentation) | presentat | ,10113 |
| 5:00 pm – 5:15 pm | Break | | |
| 5:15 pm – 5:35 pm | Data collection and collaboration with (re)insurance | industry | |
| | (Paolo Bazzurro) | | |
| 5:35 pm – 6:00 pm | Discussion and plans for Day 2 | | |
| 6:00 pm – 7:00 pm | Reception (Bristol Bay BallroomKatmai room) | | |

- Time will be made for discussion
- Keep notes for further discussion in breakouts tomorrow.

Additional questions to frame discussions

- What are the decisions that need to be made (on buildings) post-EQ and how will data help this decision making?
 - e.g. data for deciding fate of building (demolition), data for zoning?
- What data is needed for evaluating and adapting technical decisions?
- Towns vs Cities different data needed?
- Need to identify two forms of links:
 - "links" that allow interoperability between data collected by different entities
 - "links" between physical damage, impact, and recovery data → to inform reconstruction policy.
- Bear in mind time frames
 - What data is available (needed) at what times after event?
 - What is the minimum data to collect in the first weeks following, vs comprehensive collection later, vs data to assess residual capacity for decisions on demolitions.



Network of University Laboratories in Earthquake Engineering REte dei Laboratori Universitari di Ingegneria Sismica









EARTHQUAKE ENGINEERING RESEARCH INSTITUTE

Post Earthquake Data Collection Workshop



Italy Experience







Mauro Dolce

Presidency of Council of Ministers - Civil Protection Department Email: Mauro.Dolce@protezionecivile.it



Claudio Moroni

Civil Protection Department Email: Claudio.Moroni@protezionecivile.it



Gaetano Manfredi

University of Naples Federico II

Department of Structures for Engineering and Architecture

Email: aprota@unina.it



Andrea Prota

University of Naples Federico II

Department of Structures for Engineering and Architecture

Email: aprota@unina.it



Marco Di Ludovico

University of Naples Federico II

Department of Structures for Engineering and Architecture

Email: diludovi@unina.it



Maria Polese

University of Naples Federico II Department of Structures for Engineering and Architecture Email: mapolesei@unina.it



ReLUIS - Competence Centre of Civil Protection Dept.

• What is ReLUIS?

Network of University Laboratories in Earthquake Engineering



PARTE PRIMA Roma - Giovedi, il maggio 2003 (Illine del Parte Parima del Parte Parima del Parima del

N. 72

ORDINANZA DEL PRESIDENTE DEL CONSIGLIO DEI MINISTRI 20 marzo 2003.

Primi elementi in materia di criteri generali per la classificazione sismica del territorio nazionale e di normative tecniche per le costruzioni zona sismica. (Ordinanza n. 3274).

ORDINANCE OF THE PRIME MINISTER 3274/2003

ART.4

Al fine di assicurare la più agevole ed uniforme applicazione delle disposizioni
di cui alla presente ordinanza, il Dipartimento della protezione civile è
autorizzato a promuovere la costituzione di un centro di formazione e ricerca
nel campo dell'ingegneria sismica e di presente dei laboratori universitari
operanti nel medesimo settore.

Competence Centres

REte dei Laboratori Universitari di Ingegneria Sismica Charter members: Univ. Basilicata, Napoli, Pavia and Univ. di Trento) Collaboration with ENEA









ReLUIS - Competence Centre of Civil Protection Dept.


What is ReLUIS?

•The consortium ReLUIS has many similarities with other earthquake engineering networks (i.e. Network for Earthquake Engineering Simulation – NEES and Asian Pacfic Network for Center of Engineering Reaserch - ANCER).





•ReLUIS, is a <u>interuniversity consortium</u> with the purpose to coordinate the University Laboratories activity of seismic engineering, giving scientific, organizational, technical and financial supports to associated University



- Southern Italy Earthquake 23 November 1980 (Ms=6,9)
- **★** Umbria-Marche Earthquake 26 September 1997 (Ms=5,5)
- ★ Molise Earthquake 31 October 2002 (Mw=6,3)
- ★ L'Aquila Earthquake 6 April 2009 (Mw=6,3)
- Emilia-Romagna Earthquake in 20-29 may 2012 (Mw=5,9;5,8)

➤ Southern Italy Earthquake – 23 November 1980 (Ms=6,9)

The earthquake hit a vast area in Campania, Basilicata and, to a lesser extent, Puglia.

- 687 municipalities were seriously damaged;
- 2,914 deaths and more than 8,800 injured




- <u>February 1981</u> Regulations for implementing the law of 1970: instruction for the <u>organization of a civil protection system;</u>
- June 1981 new Minister for Civil Protection (Zamberletti).



"HURRY to save those who are still alive, to help who no longer has anything"

➤ Umbria-Marche Earthquake 26 September 1997 (Ms=5,5)



An initial earthquake tremor of magnitude 5.5 (Ms) hit a vast area of central Italy. Then a seismic sequence continued for several months in Umbria

and Marche, with thousands of tremors in a wide area, causing 11 deaths







Basilica of San Francesco d'Assisi

- For the first time the damage survey has been performed together with the usability survey (Aedes form)
- criteria for reconstruction phases: "light" and "heavy" reconstruction;
- Public funds (repair+ strengthening works) based on <u>parametric costs</u> assessed according to damages and vulnerability significant <u>parameters</u>;
- ➤ Molise Earthquake 31 October 2002 (Ml=5,4)
- new seismic code (OPCM n. 3274/2003)
- Code provisions: seismic assessment of strategic buildings ond infrastructures



➤ L'Aquila Earthquake – 6 April 2009 (Mw=6.3)

The main shock occurred at 03:32 on 6 April 2009, causing 309 deaths and over 1500 injured. Its epicenter was near L'Aquila, which together with surrounding villages suffered most damage.



- damage and seismic <u>usability assessment of each building</u> through in situ inspections;
- The <u>AeDES form</u> was adopted as a rapid tool to evaluate the safety conditions of the buildings;
- The financial support to the reconstruction process was calibrated also depending on the building usability rate;
- Reconstruction process based on light and heavy reconstruction;
- For each building <u>not only repair works</u> but also <u>local or global strengthening</u> <u>interventions</u> (or demolition and reconstruction) <u>were allowed</u>; the retrofit design as well as their costs were designed and computed by practitioners.

➤ Emilia-Romagna Earthquake – 20-29 May 2012 (Mw=5,9; 5,8)


In May 2012, two major earthquakes occurred in Northen Italy, causing 26 deaths and widespread damage.











- Damages mainly on <u>industrial buildings</u> <u>Business interruption</u>;
- additional damages provided by the earthquake of 29 may.
- Need to refine <u>Usability form for precast buildings</u>







Post Earthquake Safety Evaluation of Buildings

Damage and Safety assessment



> ATC-20

Following the San Fernando Earthquake in 1971 (South California), the Applied Technology Council (ATC) began developing Procedures for Postearthquake Safety Evaluations of Buildings (ATC-20) and a Field Manual: Postearthquake Safety Evaluations of Buildings (ATC-20-1).

> The Aedes form

The form and its manual derive from the experience gained in several earthquakes since earthquake in Umbria and Marche in 1997.

Updates were made after the earthquakes of Pollino 1998 and Molise in 2002.



Post Earthquake Safety Evaluation of Buildings

Data collected by Aedes Form

The usability evaluation is not a safety assessment, nor it substitutes it.

Buildings are intended as structural units - form takes into account only residential structure.

≻Section 1 - Building identification


- localization;
- n° of the survey;
- date of the survey.

➤ Section 2 - Building description:

- metrical data;
- age (period of construction);
- eventually renovation;
- type of use and exposure.

➤ Section 3 - Building typology

- <u>structural typology;</u>
- main elements of vulnerability.




| | Metr | ical dista | | Agr | | | ter . | _ | _ | | |
|----------------------------|--------------------------------------|---------------------------|----------------------|---|---|------------------------|--|----------------------------|-----------|---------|--|
| Total number of etunion | Antrage storey Aright | diverage a | ency surface n°() | Construction and assessment (Sun 2) | 4 O Rendered | No. of emits de ana | Etitiative | 100 | 10 | 0 1 | |
| O2 O10 O1 O11 | 2 O 234-330 2 O 334-50 4 O >50 | c O 50+100 n O 100+130 | м О 430 ,960 | 10 44 61 10 44 61 10 62 - 71 | B C Production C C Shapman D C Cofficer E C Public services | 33333 | A O HATS B O Months C O - 20% D O New uniformit | 0 1 2 3 4 5 | 2 3 4 5 6 | 2 3 4 5 | |
| 06 | 100c0: | 6 O 230 + 300 | | O 82 + 91 | c) O Strangic convices at O Townste | | # O Unumplaned | 9 | 9 | 9 | |

| • | \ | | | | Amony | buildings | | | - 1 | Other structures | | | |
|---|--|---|--|-----------------------------|---|-----------|---------|------------|-----------|------------------|-----------------------------|-------|---|
| | | | Phone | r new Treper new | | | - | | H.C. tame | | NG. | | |
| | Vertod | 1 | or furtiguity (substitution) partners, 1 | | det protocetty (Street, beste, squarer store,) | | Columns | | 3 | | No sheet | citie | 0 |
| | man. | î | | | | | 8 | Mare | d) | Ded fores | | | |
| | Porgonal Structures | - | MICHAE MICHAEL | to high one And an Annual 4 | | 2 | Den | SWEED ARTY | | Higar | ingra | | |
| | | _ | State | bure. | Dages. | Service | _ | _ | - | Ь | | Α. | 0 |
| | | A | -4 | C | - 0 | | F | G | н | 1. | PSMI AND Menistron | 0 | 0 |
| ч | Not interthed | 0 | | | | | 84 | | | H | Artin | 1000 | _ |
| 2 | Years when he ricks | | 0 | 0 | | 0 | 0 | 01 | Ht | 2 | distribution | 0 | 0 |
| 3 | Vaults with fin rods | | | 0 | | 0 | | 0 | | | Roo | d | |
| | Bioderic with files@86 sold procedur belows with a single layer of receiver plants, belong and shallow- and reads) | 0 | 0 | 0 | 0 | 0 | NO | 92 | 9 | | O Thrustog to O Nor Head | | - |
| t | Bearry with searchigid sittle process bears with a dealer layer of making plants, bears and tellure the photos | 0 | | 0 | 0 | 0 | 0 | 0 | | 3 (|) her thus | gri | |
| | Dearer with right side (in hors leaves and corrector to c. sides) | | 0 | 0 | | 0 | | 94 | 10 | 2 | 2 22 0000 | 9-50 | _ |

Post Earthquake Safety Evaluation of Buildings

Data collected by Aedes Form

- Section 4 Damage to structural elements and existing short term countermeasures:
- Section 5 Damage to no structural elements and existing short term countermeasures:
- Section 6 External risk induced by other construction and and existing short term countermeasures
- > Section 7 Soil and Foundation
- **≻**Section 8 Usability assessment
- >Section 9 Note



| 5 | Damage to non-su | ucturar elei | nemes an | iu existin | g short te | in coun | et measu | ics |
|---------------------|-------------------------------|--------------|----------|------------|------------|-----------|----------|-------------------------------------|
| _ | | | | EXISTING | SHORT TER | M-COUNTER | MEASURES | |
| Damage | | PRESENT | None | Removal | Propping | Repair | No entry | Barrier or passage protection |
| | | - A | | | D | E | F | |
| 1 Falling of plasts | r, ocurrings, false-collings | 0 | 0 | | | | | |
| 2 Feling of tiles. | chamneys | 0 | 0 | 0 | | 0 | | |
| 3 Falling of eaves | , parapets. | 0 | 0 | | | _ | | |
| | internal or external objects. | 0 | 0 | 0 | | | | 0 |
| 5 Damage to high | raciti or arwage systems | -0 | 0 | | | | | |
| 6 Damage to elec | the or gas systems. | 0 | 0 | | | | | |
| | | | | | | | | |

| KOK CY | atteanies | | | | | | | | 7 | намуна | no. | |
|----------------|--------------------------------------|--|--|---|---|--------------------------|--|-------|---------------|--|--|---|
| | 4 | News Co | 14841 | 9. | , B |] | | A | USABLE | building | 0 | |
| RISK | | STRUCTUAL | | (Sect 5) | (NOCE 6) | GEOTECHNICAL (Nett.7) | 1 | 2 | В | UNUSAI | ILE building (totally or partially), but USABLE ort term countermeasures | 0 |
| | | ** | 1 | 2 | - | 8 | 1// | 1, | c | PARTIA | LY UNUSABLE building (1) | 0 |
| | LOW | - 0 | | 0 | 3- | 0 | / | - 1 | | TEMPOR | CARRY UNUSABLE building requiring a more | _ |
| | OW WITH | | 9 | 0 | 0 | 0 | 11 / | - | D | fetailed | investigation | 0 |
| COUNT | HIGH | SURES | - | 0 | 0 | 0 | | | 6 | UNUSAL | LE building | 0 |
| | | | - | MAIL I | 1.0 | 100 | | | _ | | | _ |
| | | 2 0 | Only I | from ok | utsida | | O Not surve | red . | lasific Os | | | ľ |
| Survey | riction on accuracy | 2 C | Conty (| from ox | unside 2/3) | 4 | O Not surve | red . | lasific Os | d as B or | C: causes of external risk when hadding is classified as | |
| Survey | rictions on accuracy ted short | 2 C | Comp Comp | from or l fate (> | atelde 2/8) limited | 4 (*) er e) | O Not surve because of | red . | lasific Os | d as B or | C: causes of external risk when hadding is classified as | |
| Survey | ted short | 1 C 2 C 3 C | Only Partial Comp | from or l late (> sures, | 200) Distincted Transcence | 4 (*) er e) | O Not surve because of | red . | OS OA | d as B or uncy tel beat on | Common of external risk when building is classified as mod b O Ruins c O Demolished are c O Other | _ |
| Survey Suggest | ted short | t C 2 C 3 C | Only Partie Comp research torm | from or I fate (> surres, counter | 2/3) Emited recasure | 4 (*) er e) | O Not save because of stended (**) | red . | OS OA | dado do de | C causes of external risk when building is classified as used b O Ruins & O Demolished are a O Other | |
| Survey Suggest | ted short | I C 2 C 3 C | Only Partie Comp research torm | from or I fate (> surres, counter | 2/3) Emited recasure | 4 (*) er e) | O Not save because of stended (**) | red . | OS OA | uncy tef | C causes of casemal risk when hubbling is classified as used b Rains e Demolished age e Claber Suggested short terms countermeasures Research of convex, pasagines, asserbangs. | |
| Survey Suggest | ted short | I C 2 C 3 C Secretario de la Company de la C | Comp Farma Comp renew torms applica- | from or I fate (> surres, counter | 2/3) Emited recasure | 4 (*) er e) | O Not save because of stended (**) | ved. | OS OA | es e | C causes of external risk when building is classified as used b Ruins e Demolished nor e Ofther Demolished Suggested short term; countermeasures Researed of once; pasagens, averhangs. Removal of other internal or external objects | _ |
| Survey Suggest | ted short | t C 2 C 3 C Server countries of high | Only : Partial Composition torm : applica- | from ox I fate (> sures, counter ation o or to in | anide 2/8) Emited measure d strands fill panel | (*) or e) | O Not save because of stended (**) | ved. | 7 C | es e | C causes of external risk when building is classified as used b O Ruins c O Demolished near c O Other Suggested short term countermeasures Removal of other internal or external objects Barriers and passage protection | _ |

Post Earthquake Safety Evaluation of Buildings


Data collected by Aedes Form

Damage Level and extension

D1 slight damage:


components.

The damage not affect significantly the capacity of the structure; the damage is slight when the falling of objects can immediately be avoided.



D4-D5 very heavy damage:

The damage significantly modifies the capacity of the structure, bringing it close to the limit of partial or total collapse of the main structural components – including collapse









Post Earthquake Safety Evaluation of Buildings

Damage and Safety assessment

> ATC-20

Posting systems:

- Inspected Appears safe for lawful occupancy
- •Limited Entry / Restricted Use Some restriction on use, controlled by building owner/manager
- •Unsafe Entry controlled by jurisdiction



Usability Classification



> Aedes Form

Six usability rates:

- Usable
- Unusable but usable after short countermeasures
- Partially unusable
- Temporarily unusable
- Unusable
- Unusable due to external risk

Technical management of seismic emergency – damage survey and safety evaluation

Training


The training activities are carried out for:

- practitioners
- university professors and researchers



Objectives

- share a unique approach at the national level in the technical management of seismic emergency
- promote common standards, procedures, languages and operating methods







 Homogeneous safety evaluations by experts from different fields and from different boards.

L'Aquila Earthquake

- > Data collected Aedes Form
- > Housing impacts

Data collected - Aedes Form


about 72,000 buildings inspected (more than 80,000 inspection)

7 April






Data collected - Aedes Form



| | А | В | С | D | Е | F |
|---------|-------|-------|------|------|-------|------|
| Masonry | 48.7% | 10.7% | 2.6% | 1.2% | 30.5% | 6.3% |
| Mixed | 62.9% | 11.3% | 3.0% | 0.6% | 17.1% | 5.1% |
| RC | 61.6% | 19.4% | 2.3% | 1.1% | 13.5% | 2.1% |
| Total | 52.0% | 12.5% | 2.6% | 1.0% | 26.5% | 5.4% |

Data collected - GIS

GIS mapping of all damaged buildings



Housing impacts



Persons assisted: 65.579


Last Update - 18.04.2009



| ACCOMMODATION IN TENTS | | | | | | |
|------------------------|-------------------|----------------|---------------------|----------------|---------------------------|--|
| | Camps | Tents | Persons assisted | Field kitchens | Advanced Medical Posts | |
| COM1 | 36 | 1.512 | 13.876 | 13 | 15 | |
| COM2 | 24 | 869 | 5.475 | 16 | 14 | |
| COM3 | 40 | 946 | 6.562 | 10 | 3 | |
| COM4 | 19 | 906 | 4.518 | 17 | 3 | |
| COM5 | 10 | 868 | 4.206 | 9 | 6 | |
| COM6 | 14 | 247 | 1.850 | 4 | 0 | |
| COM7 | 18 | 609 | 3.123 | 0 | 0 | |
| COM8 | not yet avail. | not yet avail. | not yet avail. | not yet avail. | not yet avail. | |
| TOT | 161 | 5.957 | 39.610 | 69 | 41 | |

| ACCOMMODATION IN HOTELS AND PRIVATE HOUSES | | | | |
|---|--|--|--|--|
| Province | Persons | | | |
| Teramo | 18.468 persons: 13.458 in 194 hotels and 5.010 in 1.087 private houses | | | |
| Pescara | 3.875 persons: 3.872 in 65 hotels and 3 in 1 private house | | | |
| Chieti 2.876 persons: 2.828 in 105 hotels and 48 in 6 private house | | | | |
| Ascoli Piceno 750 persons in 9 hotels | | | | |
| Total | 25.969 persons | | | |

Housing impacts



Earthquake Umbria-Marche 1997 – Picture today

www.protezionecivile.gov.it






The C.A.S.E. Project



Complessi (Complexes)
Antisismici (Antiseismic)
Sostenibili (Sustainable)
Eco-compatibili (Eco-compatible)







Seismic Isolators



8,000 houses for **23,500** homeless available in few months – **4449** apartments C.A.S.E. project


Typical solutions post-earthquake

Lodging with different levels of cost and, above all, of comfort

| | Serviceable Useful life [year] | Surface/person about [mq] | Surface media [mq] | Cost /person [€/person] | Cost/Yr / person [€/person] |
|------------------------|--------------------------------------|---------------------------------|--------------------------|----------------------------|-----------------------------------|
| Tents | 3 | 6,2 - 9,4 | 7,8 | 5243 | 1748 |
| Roulotte | 5 | 2,3-3,5 | 2,9 | 3125 | 1005 |
| Container | 8 | 5 - 7,5 | 6,2 | 10875 | 1359 |
| Wooden houses (MAP) | 15 | 17,8 – 25,4 | 21,6 | 33249 | 2217 |
| Project C.A.S.E | 30 | 22,1 – 31,6 | 26,9 | 40856 | 1362 |
| | | | | | |
| Hotel | 1 | 7-12 | 9,5 | 5323 | 5323 |
| CAS | 1 | 10-20 | 15 | 2000 | 2000 |

Typical solutions post-earthquake

Lodging with different levels of cost and, above all, of comfort



L'Aquila Earthquake

- > Data collected Reconstruction process
- > Organizations involved in collecting data
- > Repair and strengthening works costs
- > Demolition and reconstruction

The Ordinances

Reconstruction policies

June 6, 2009 - OPCM 3778




June 6 2009 – OPCM 3779



July 9, 2009 - OPCM 3790



November 12 2009 – OPCM 3820



(*) With Annexes

The Reconstruction Process of private buildings

Financial Support

"LIGTH" RECONSTRUCTION

Rate A: Usable buildings

✓ Repair intervention with a maximum refund of 10.000 € + 2.500 €/dwelling;



The Reconstruction Process of private buildings

Financial Support

"LIGTH" RECONSTRUCTION

Rate A: Usable buildings

✓ Repair intervention with a maximum refund of 10.000 € + 2.500 €/dwelling;



Rate B: Building usable only after short term countermeasures

Rate C: Partially usable building.

✓ Total refund of repair intervention costs + local strengthening of structural or nonstructural members up to 150 €/mq.;

Local strengthening interventions:

- related to single structural members;
- no significant mass and stiffness change;
- only the local member capacity increase should be computed;
- the global analysis of the structure is not required.



- The "Filiera" activity
- √The process consists of a series of checks by:
 - 1. FINTECNA: Finanziaria per i Settori Industriale e dei Servizi S.p.A.



FINTECNA - Ministry of Economy and Finance, evaluates <u>administrative check</u> of application and documentation.

2. ReLUIS: Laboratories University Network of seismic engineering



Compliance between: i) repair intervention and damages; ii) local strengthening interventions and <u>italian seismic code provisions</u> (NTC 08 and Circ. 617/2009 as well as <u>specific provisions for the Abruzzo Emergency</u> (O.P.C.M. 3779, 3790 and Annexes by DPC). <u>Technical check</u>

3. CINEAS: Interuniversity Consortium of Insurance Engineering



Finacial check

• The "Filiera" activity



WHITE BOOK ON THE RECONSTRUCTION
OF PRIVATE BUILDINGS DAMAGED BY
THE L'AQUILA EARTHQUAKE

The "Filiera" activity

19936 FUNDING REQUESTS



19936 Funding requests related to L'Aquila city (outside the historical centre) and other municipalities have been analysed in the approval process

U.I.I = Housing unit



P.C. = Communal areas U.I.C. = Dwellings



P.C. = 3033

2761



U.I.C. = 13562

13087

L'Aquila

Other municipalities

698

2094


U.I.I = 2742

272

475

• Data Collection

19936 FUNDING REQUESTS



Application Digital documentatio



Data Collection

QUERY \longrightarrow Data

- Building address Usability rate (B,C, or E);
- structural typology (RC, masonry, steel, etc.);
- number of stories;
- global surface;
- age of construction;
- number of dwellings;
- Approval process timing;
- repair and strenghtening interventions;
- risk indicator [α];
- dwellings repair costs;
- Structural repair costs, local strengthening interventions costs (B or C buildings);
- seismic capacity increase interventions costs (E buildings)
- Demolition and reconstruction

Form to collect data


| | | DATI GE | NERALI | | |
|------------------------|-----------------------|-----------------|------------------------|----------------|-------------|
| Comune: | | | | | |
| Indirizzo: | | | | | |
| Foglio: | Particell | ic | Anno di | Costruzione: | |
| Agibilità: | i | DATI PE | RATICA | | |
| PROTOCOLLO | AQ-E-8CE-17142 | -C175-2 C-X-X-X | | | |
| U.I.C. correlate | | | | | |
| | | DATI GEO | METRICI | | |
| Altezza Totale [m]: | | | Superficie | Coperta [mig]: | |
| n° Piani Sopraelevati: | | | Alterza media | Plant (eschose | |
| nº Piani Interrati: | | | plano sottota | tto [m] | |
| | | DATI AZION | IE SISMICA | | |
| (C | Categoria Sott | asualo: | Categoria | Topografica: | |
| Regolarită în pianta: | | 8 | legolarità in elevazio | ne: | |
| Dati dinami | ci | eg (SLV): | | Tc (SLV): | |
| Ti: | | T2: | | T3: | |
| MP1: | | MPZ: | | MP3: | |
| 4 | CARATTERISTIC | HE MATERI | ALI E DETTAGLI | COSTRUTTIV | /1 |
| alcestruzzo | Acciaio | | | Sta | iffe |
| cm [MPa]: | fym [MPa]: | | | Travi | Pilastri |
| | | | | 6. | 4: |
| | Tipologia be | irre: | Pas | 50 | Passo |
| | | | [cn | 112 | [cm]: |
| | | DATI INTER | RVENTO | | |
| Riparazione | | ☐ Interventp | Locale | □ mig | glioramento |
| NTERVENTO 1: | | AL | TRO INTERVENTO: | | |
| ITERVENTO 2: | | | | | |
| NTERVENTO 3; | | | | | |
| Indic | catori di rischio: re | apporto tra cap | pacità e domanda i | n termini di P | GA |
| alfa_uv ANTE OPERAM: | | | alfa_u | FONDAZIONE: | |
| alfa uv POST OPERAM: | | | | | |

The damaged building stock

The "Filiera" activity


19.336 funding request B or C E 10.430 funding 8.906 fundi request request 2211 3.564 Buildin Buildings 5775 Buildings

5775 BUILDINGS



The damaged building stock


Usability rate vs. structural type age of constr.



- ✓ RC structures: E rate buildings decrease with recent age of construction (from about 60% to about 15%)
- ✓ Masonry structures: E rate buildings is almost constantly about 35%)

The damaged building stock

Usability rate vs. structural type n° of stories




- ✓ RC structures: E rate buildings increase with number of stories
 (from about 10% to about 50%)
- ✓ Masonry structures: E rate buildings increase with number of stories (from about 25% to about 45%)

Light Reconstruction

June 6 2009 - OPCM 3779







Rate A: Usable buildings

Rate B: Building usable only after short term countermeasures

Rate C: Partially usable building.

Light reconstruction - Buildings Usability rate

THE "LIGTH" RECONSTRUCTION

Strong support to practioners




GUIDELINES AND CALCULATION EXAMPLES

REPAIR AND STRENGTHENING OF STRUCTURAL ELEMENTS, INFILLS, AND PARTITIONS

Freely downloadable at website www.reluis.it

Light reconstruction - Approval process

Funding requests grant (B or C buildings)



| Date | n° rec | • | Grant |
|----------------|--------|-----|----------------|
| [-] | [-] | [%] | [€] |
| December 2009 | 34 | 0% | 940.492,17 |
| March 2010 | 5.957 | 63% | 246.860.149,31 |
| September 2010 | 8.467 | 90% | 452.717.28,51 |
| September 2011 | 9.048 | 96% | 509.215.730,00 |
| March 2013 | 9.247 | 98% | 532.259.802,10 |
| September 2013 | 9.281 | 98% | 534.359.872,31 |


After 1 year 90% (8467 of 10439) financially approved by the municipality

✓ Municipalities grant released: A grant of about 452 million of euro at September 2010, total "ligth" reconstruction costs of about € 534.000.000, 00

Light reconstruction - Buildings Usability rate


• 3564 Private buildings





3564 Usability rate B or C

2211 Usability rate E



1738 R.C. Buildings

1580 Masonry Buildings

246 Other tipologies

3318

• <u>Costs on 2501 Private buildings – L'Aquila</u> Buildings B or C :

The grant includes the costs for <u>repair intervention</u> + <u>local</u> <u>strengthening</u> of structural or no-structural members.



• 1.599 R.C. buildings - mean grant: 246 €/m²




• 902 masonry buildings mean grant : 318 €/m²

Costs include: practitioners technical fees and V.A.T.

R.C. Private buildings

| | z or sere <u>mente</u> |
|---------------------|------------------------|
| | |
| n° of Buildings [-] | 1599 |
| Mean [€/m²] | 246,78 |
| Median [€/m²] | 216,47 |
| Minimum [€/m²] | 41,03 |
| Maximum [€/m²] | 1.090,78 |
| Range[€/mq] | 1.049,75 |
| 16° Percentile | 101,47 |
| 84° Percentile | 390,74 |
| Standard Dev.[€/m²] | 154,57 |
| CoV [%] | 63 |
| Asymmetry [-] | 1 |
| Kurtosis [-] | 2 |
| Total grant [€] | 375.866.841,96 |
| Mean grant [€] | 235.063,69 |
| Mean Surface [m²] | 898,28 |





✓ Buildings grant: Mean value of 246 €/mq., corresponding to a mean grant of about € 235.000, 00 for each building, mean surface of about 900 mq.

Masonry Private buildings


| | - 902 m | | - 902 masonry buildings mean grant : 218 c/m² |
|--------------------------------|-------------------------------------|----------|--|
| The great to | peluedes the constant of strengths. | ā.zi | costs for repair intervention + <u>local</u> report the total for repair intervention + <u>local</u> relocate the costs for repair intervention + <u>local</u> |
| | | | |
| n° of Buildings [-] | 902 | 600 | |
| Mean [€/m²] | 318,22 | | |
| Median [€/m²] | 292,26 | 500 | |
| Minimum [€/m²] | 32,20 | <u>.</u> | |
| Maximum [€/m²] | 962,36 930,16 | 400 | |
| Range[€/mq] | 930,16 | 300 | |
| 16° Percentile | 147,45 | 5 | |
| 84° Percentile | عْ 488,10 ° | 200 | |
| Standard Dev.[€/m²] | 172,16 | | |
| CoV [%] | 54 | 100 | |
| Asymmetry [-] | 1 | 0 | |
| Kurtosis [-] | 1 | _ | 0,00,00,00,00,00,00,00 |
| Total grant [€] | 103.418.291,36 | 9 | 2, 10, 20, 30, 10, 20, 20, 20, 10, 80, 20, 10, 80, 20, 10, 80, 20, 10, 80, 20, 10, 80, 20, 10, 80, 20, 10, 80, 20, 10, 80, 20, 20, 10, 80, 20, 20, 10, 80, 20, 10, 80, 20, 10, 80, 20, 10, 80, 20, 10, 80, 20, 20, 10, 80, 20, 10, 80, 20, 10, 80, 20, 10, 80, 20, 10, 80, 20, 10, 80, 20, 10, 80, 20, 10, 80, 20, 10, 80, 20, 10, 80, 20, 10, 80, 20, 10, 80, 10, 10, 10, 10, 10, 10, 10, 10, 10, 1 |
| Mean grant [€] | 114.6543,0 | | Grant [€/m²] |
| Mean Surface [m ²] | 377, 35 | | |

✓ Buildings grant: Mean value of 318 €/mq., corresponding to a mean grant of about € 115.000, 00 for each building, mean surface of about 377 mq.

Cost rates



Masonry Buildings: 902



Private buildings

Repair cost rate due to dwellings: 115 €/m²

Note: Computed as the repair costs of dwellings (the ones for which the application was submitted) divided by the cover building total surface


- On each building the repair cost rate due to dwellings is: 93 €/m²
- ✓ U.I.C. grant: Mean value of <u>218 €/</u> <u>mq.</u>, corresponding to a mean grant of about <u>€ 30.000 for each</u> U.I.C.,

Note: Computed as the repair costs of dwellings (the ones for which the application was submitted) divided by the cover building total surface



Light reconstruction - Repair & Strength. Costs

- R.C. Private buildings
 - Repair mean costs: 208 €/m²
 - Local Strengthening mean costs: 38 €/m²








A65

Light reconstruction - Repair & Strength. Costs

Masonry Private buildings

- Repair mean costs: 242 €/m²
- Local Strengthening mean costs: 76 €/m²



Strenghtening interventions

STEEL TIES




Local strengthening costs: doubed with respect to RC buildings (in any case lower than maximum allowable 150 €/mq)

ReLUIS - Project on School Buildings

SEISMIC SAFETY ASSESSMENT OF SCHOOL BUILDINGS IN L'AQUILA

SAFETY INDEX INCREASE PROVIDED BY LOCL STRENGTHENING SOLUTIONS



Removing brittle failure mechanisms

References

Frascadore R., Di Ludovico M., Prota A., Verderame G.M, Dolce M., and Cosenza E., "Local strengthening of RC structures as a strategy for seismic risk mitigation at regional scale" **Earthquake Spectra**, in press., online available.

Di Ludovico M., Balsamo A., Prota A., Verderame G.M., Dolce M., and Manfredi G., "Experimental Behavior of non-conforming full scale RC Beam-Column Joints Retrofitted with FRP" International Workshop Role of Research Infrastructures in Seismic Rehabilitation - **SERIES, Istanbul**, TUrkey, February 8-9, 2012, paper ID SS2-5, pp. 21-22. (http://web.itu.edu.tr/series).



" THE HEAVY" RECONSTRUCTION

July 9, 2009 - OPCM 3790







1951 Of Laquila

Rate E: Unusable building.

The Reconstruction Process of private buildings

Financial Support

"HEAVY" RECONSTRUCTION

Rate E: Unusable building



- ✓ Total refund of repair intervention costs + seismic strengthening up to 400-600 €/mq. (minimum safety level 60% of current code request, up to 80%)
- ✓ In case of "E" buildings with a low level of structural dameges, total refund of repair interventions and it is also possible to perform only the <u>local strengthening</u> of structural or non-structural members up to 250 €/mq. (global analysis is not obligatory)


The so called "E-B buildings" in the approval process





Heavy reconstruction - Approval process

Funding requests submission (E buildings)



| Date | n° approval funding request | | Grant |
|----------------|-----------------------------------|-----|------------------|
| [-] | [-] | [%] | [€] |
| March 2010 | 10 | 0% | 2.520.526,28 |
| September 2010 | 172 | 2% | 16.189.933,57 |
| September 2011 | 1.325 | 16% | 231.255.611,15 |
| September 2012 | 4.595 | 54% | 901.860.304,41 |
| September 2013 | 6.257 | 74% | 1.604.415.532,45 |


After 3 years, 50% of requests (4585 out of 8906) financially approved by the municipalities

✓ Municipalities grant released: A grant of about 900 million of euro at September 2012, total "heavy" reconstruction costs of about € 1.600.000,000,000


Heavy reconstruction - Buildings Usability rate

2211 (1902 E+ 309 E-B) private buildings





Usability Rate E - 1902 edifici



3564 Usability rate B or C

309 Usability rate E-B

1902 Usability rate E

836 R.C. Buildings

1020 Masonry Buildings

46 Other tipologies

Heavy reconstruction - Buildings Usability rate

Costs on 762 Private building - L'Aquila

Buildings E:

The grant includes the costs for repair intervention + <u>seismic</u> <u>strengthening</u>. + energy efficiency upgrade + structural and geothecnical tests.



• 448 R.C. buildings - mean grant: 1030 €/m²

(about 4 times higher than in case o B or C buildings – 246 €/mq)



• 314 masonry buildings mean grant: 935 €/m² (about 3 times higher than in case o B or C buildings – 318 €/mq)

Costs include: practitioners technical fees and V.A.T.

Heavy reonstruction – Costs


• R.C. Private buildings

| Buildings E: - 448 R.C. buildings - mean grant: 103 | 0 €/m² | - 448 R.C. buildings - mean grant: 1030 €/m² |
|--|---|---|
| - 314 masonry buildings mean grant : | 935 €/m² | - 314 masonry buildings mean grant : 935 6/m² |
| The groot includes the costs for repair intervention rehabilitation. * adjustment or energy * structure geothernical tests | * <u>seismic</u> cural limite grant inc <u>rehabilitation</u> . geothecrical t | oludes the costs for repair intervention + <u>seismic</u> . + adjustment of energy + structural and tests |
| | - | 100 |
| n° of Buildings [-] | 448 | 90 |
| Mean [€/m²] | 1.030,4 | |
| Median [€/m²] | 1.057,4 | |
| Minimum [€/m²] | 168,0 | |
| Maximum [€/m²] | 1.826,96 | is 60 - 50 - 40 - 40 - |
| Range[€/mq] | 1.658,65 | |
| 16° Percentile | 806,41 | |
| 84° Percentile | 1.258,2 | 5 30 |
| Standard Dev.[€/m²] | 240,68 | |
| CoV [%] | 23 | |
| Asymmetry [-] | 0 | |
| Kurtosis [-] | 0 | 0, 30, 40, 40, 40, 40, 40, 40, 40, 40, 40, 4 |
| Total grant [€] | 805.129.213,53 | 3, 8, 1, 80, 10, 130, 120, 180, |
| Mean grant [€] | 1.797.163,0 | Grant [€/m²] |
| Mean Surface [m ²] | 1.733,8 | |

✓ Buildings grant: Mean value of 1.030 €/mq., corresponding to a mean grant of about € 1.800.000, 00 for each building, mean surface of about 1.700 mq.

Heavy reonstruction – Costs

• Masonry Private buildings




✓ Buildings grant: Mean value of 935 €/mq., corresponding to a mean grant of about € 575.000, 00 for each building, mean surface of about 610 mq.

Heavy reconstruction - Costs

Cost rates

R.C. Buildings: 448

Masonry Buildings: 314



Heavy reconstruction - Costs


Private buildings

Repair cost rate due to dwellings: 170 €/m²

Note: Computed as the repair costs of dwellings (the ones for which the application was submitted) divided by the cover building total surface

 On each building the repair cost rate due to dwellings is: 116 €/m²


✓ U.I.C. grant: Mean value of <u>287 €/</u> <u>mq.</u>, corresponding to a mean grant of about <u>€ 40.000 for each U.I.C.</u>,



Heavy reconstruction – Costs

R.C. Private buildings


- Energy efficiency upgrade costs (394 build.): 96 €/mq.
- structural and geothecnical tests costs: 10 €/mq.



Concrete average cylindrical compressive strength

Heavy reconstruction - Repair & Strength. Costs

- R.C. Private buildings
 - Repair mean costs: 592 €/m²
 - Seismic strengthening mean costs: 344 €/m²



Strenghtening intervention

Isolators Stee

Steel dampers






- ✓ Strong impetus for innovation
- ✓ Almost in every case two or more techniques have been used in combintion

Heavy reconstruction - Repair & Strength. Costs

Masonry Private buildings

- Repair mean costs: 499 €/m²
- Seismic rehabilitation mean costs: 357 €/m²



Reinforced plaster



Stenghtening interventions

• Energy upgrade costs (394 buildings): 96 €/mq.

The Reconstruction Process of private buildings

Financial Support

"HEAVY" RECONSTRUCTION

Rate E: Unusable building

✓ <u>Demolition and Reconstruction or replacement</u> in case of:



- Totally collapsed buildings
- Masonry structures partially collapsed (more than 25% in volume)
- Reinforced Concrete Structures, average compressive cylindrical strength lower than 8 MPa
- Reinforced Concrete Structures, more than 50% of storey's columns with a drift higher than 1.5%_
- <u>Demostrating the economic convenience: demolitionn and reconstruction</u> <u>costs lower than repair and strengthening</u> (to be demonstreted)
 - ✓ Specific Reccomendation for masonry aggregates

The Reconstruction Process of private buildings

Financial Support

"HEAVY" RECONSTRUCTION

Rate E: Unusable building

demolition and reconstruction

Specific form to compute demolition and reconstruction costs

Cost range:


1,200 - 1,700 €/mq.,
depending on several building characteristics

Determinazione del limite di contributo ai sensi dell'art. 5, Co. 4 OPCM 3881/2010 e del DCD n. 27 del 02-12-2010

Inserire i dati nelle caselle grigie. Il presente documento, fornito a solo titolo esemplificativo, permette il calcolo del limite di contributo ammesso per la ricostruzione ai ensi dell'art. 5, comma 4 dell'OPCM 3881/2010 e del DCD n. 27/2010. La Struttura Tecnica di Missione non è responsabile per eventua modifiche apportate al documento stesso. dentificazione dell'edificio Denominazione Comune Indirizzo Civico nº aggregato nº edificio Dati catastali: Sezione Foglio particelle Sub determinazione del limite di costo unitario La) costo base di realizzazione tecnica (C.B.N.) Costo base di realizzazione tecnica (C.B.N.) € 808,00 a) Oneri aggiuntivi sicurezza lavori D.Lgs 81/2008 e.s.n € 40,40 b) Applicazione D.Lgs 192/2005, D.lgs 311/2006 € 161,60 rendimento energetico - INCREMENTO ART. 5, COMMA 4, ULTIMO CAPOVERSO € 56,56 c) rispetto nuova normativa sismica (DM 14-01-2008 e circolare 617 02-02-2009) C.B.N. Risultante € 1.066,56 1b) maggiorazioni sul differenziale di costo per particolari condizioni SELEZIONE tecniche a) dotazione dell'intervento di polizze assicurative postume decennali a € 0,00 garanzia dei rischi di danni alla costruzione b) adozione di un piano di qualità relativo all'intervento e/o al programma di c) miglioramento del comfort ambientale con riferimento agli aspetti acustici € 40.40 ed igrotermici - Incremento ART, 5, CO 4, ultimo capoverso OPCM 3881 d) utilizzo di dispositivi antisismici € 0.00 e) particolari condizioni di localizzazione € 24.24 f) tipologie edilizie con numero di piani uguale o inferiore a quattro € 0,00 g) numero prevalente di alloggi con superficie utile non superiore a 65 mq € 0,00 h) produzione del fascicolo del fabbricato D.Lgs n. 81/2008 TOTALE MAGGIORAZIONI TECNICHE APPLICATE € 64,64 C.R.N. - Costo unitario a base d'appalto -€ 1.131,20 LIMITE UNITARIO DI CONTRIBUTO SUL COSTO DI COSTRUZIONE (€/mq Sc)

Heavy reconstruction - Demolition

<u>Demolition and reconstruction:</u> <u>531 buildings (out of 1951) - 27% of the E building stock</u>



 421 buildings: repair and retrofit costs higher than demolition and reconstruction

31 Buldings forfait grant of 750 €/m²

44 masonry buildings partially collapsed (more than 25% in volume)

1 R.C. building: more than 50% of storey's columns with a drift higher than 1.5%;

34 R.C. buildings: average compressive cylindrical strength lower than 8 MPa

-Demolition and reconstruction mean cost: 1261,04 €/m²

Robustness and resilience

• L'Aquila: Collapsed R.C. Buildings

15 collapsed R.C. buildings

135 victims

(43% of 309 victims of L'Aquila earthquake)

0.6% of R.C. damaged building stock




Hotel Duca degli Abruzzi collapse, L'Aquila 2009.



Student's Home collapse, L'Aquila 2009.

Robustness and resilience - ReLUIS - DPC projects

- ✓ Within the 2014-2016 RELUIS-DPC research project, an activity is ongoing aimed at deriving a methodological approach to deal with structural robustness within the Italian national code:
- ✓ DPC-RELUIS Project Task 3.2 «Development of methodologies to quantify structural robustness»; Prota, D. Asprone, G. Manfredi (University of Naples), D. Chiaia, A. Fantilli (Polytechnic of Turin)



Robustness and resilience - ReLUIS - DPC projects

Initiative to improve community resilience

Public information on risk

TERREMOTO PARLIAMONE INSIEME Earthquake: let's talk together

Immediately after Emilia Earthquake

Series of events, started on 11 June 2012, sponsored by the Civil Protection Department, Emilia-Romagna Region and the National Institute of Geophysics and Vulcanology in collaboration with the Network of University Laboratories for Earthquake Engineering, the Regional Health Service of Emilia Romagna and voluntary organizations of civil protection

> 32 meetings on the Italian territory

ww.protezionecivile.gov.it













Robustness and resilience - ReLUIS - DPC projects

Initiative for seismic risk reduction

Public information on risk

TERREMOTO IO NON RISCHIO "Earthquake I don't risk"

102 squares in 100 Municipalities in 2012

215 squares in 200 Municipalities in 2013

223 squares in 203 Municipalities in 2014 (June 15th-16th)





Campagna nazionale sulla riduzione del rischio sismico 13-14 ottobre 2012







Earthquake I don't risk" www.iononrischio.it

- What data were used to assess building RESIDUAL CAPACITY and how were these data used in reconstruction decisions?
- WHAT SHOULD BE IMPLEMENTED in data collection protocols to make assessment of residual capacity more reliable?

Policies after L'Aquila earthquake

Policies for BUILDING DEMOLITION

demonstrating the ECONOMIC CONVENIENCE

to demolish and rebuild instead of repair and retrofit

(art. 5 comma 1 OPCM 3881)

WITHOUT
demonstrating the
ECONOMIC
CONVENIENCE

(lump sum refund)

(art. 5 comma 2 e 3 OPCM 3881)

WITHOUT demonstrating the ECONOMIC CONVENIENCE

(SEVERE DAMAGES)

(art. 5 comma 5 OPCM 3881)

For Masonry buildings



partial failure of bearing walls for at least 25% of the building volume For R.C. buildings



(≥1.5% on more than 50% columns of a



storev)

weak concrete (fc <8 Mpa)</p>

Residual drifts



Examples after L'Aquila 2009







Residual drifts: measurements after L'Aquila 2009

Reluis has measured permanent drifts for two damaged buildings in L'Aquila confronting the efficacy of traditional and innovative techniques

plumb line



The simplest and more economic technique, may be applied only for accessible elements and is sensible to external interferences (e.g. wind)

total station



Traditional topographic technique, very precise (tolerance ± 2mm). Allows measuring discrete points, that have to established a priori, on the element

laser-scanner 3D



Innovative technique, very precise (tolerance ± 2mm). Allows reconstructing the spatial coordinates of the surveyed object with a dense DEM. Specific points to be measured can be decided also a posteriori.

Residual drifts: measurements after L'Aquila 2009

4 storey building in Pettino (AQ)





Building damage: a **soft storey** mechanism at the first level is activated.










Example of damage on some of the columns at the first storey


Residual drifts: measurements after L'Aquila 2009

For security reasons, only accessible or visible columns on the perimeter, circled in the bottom figure, were measured



The measured columns

Sign convention



| Pilastro | $\theta_{\rm B}(\%)$ | $\theta_{\rm A}(\%)$ |
|----------|----------------------|----------------------|
| 01 | +0.74 | / |
| 02 | +0.13 | / |
| 04 | +0.96 | / |
| 06 | +0.51 | / |
| 07 | +2.52 | +0.40 |
| 32 | -0.93 | +0.19 |


1st level permanent drifts (evaluation from D-DEM data)

Residual drifts: measurements after L'Aquila 2009

4 storey building in Pianola (AQ)







Building damage: a soft storey mechanism at the first level is activated.











Example of damage on some of the columns at the first storey

Residual drifts: measurements after L'Aquila 2009

For security reasons, only accessible or visible columns on the perimeter, circled in the bottom figure, were measured



Permanent
deformation of
building in
elevation
(magnified
displacements for
representation purposes)



 θ_{B}^{+}

| Pilastro | $\theta_{\rm B}(\%)$ | $\theta_{\rm A}(\%)$ | |
|----------------------------|----------------------|----------------------|--|
| 01 | +1.04 | -0.56 | |
| 05 | +0.25 | +0.64 | |
| 13 | -1.79 | +0.60 | |
| 19 | +0.77 | +0.35 | |
| 17 | +1.89 | -0.54 | |
| 14 | +0.29 | 0.00 | |
| 1st level permanent drifts | | | |

(evaluation from D-DEM data)

The measured columns

What data were used to assess building residual capacity and how were these data used in reconstruction decisions?

- No direct evaluation of Residual Capacity
- ➤ Indirect evaluation through:
 - ✓ residual drifts (difficult to measure; very few cases)
 - → usability of this criterion depends on the construction type
 - √ global damage level (for very severe damage)

Direct _decision on demolition


√ building tagging (linked to damage) → influence
on the applicable funding scheme

What should be implemented in data collection protocols to make assessment of residual capacity more reliable?

Residual Capacity as
representative parameter for assessment of
building reparability in a
Performance Based Policy framework

Reparability issues


Repair/Retrofit criteria: Policies after L'Aquila earthquake



Evaluation of Residual capacity (Bazzurro et al. 2004)

Residual Capacity as:

the minimum spectral acceleration (at elastic period T1 and with 5% damping) such as to determine local or global collapse during an aftershock



Evaluation of Residual capacity (Bunno et al., 1999; Bunno and Maeda, 2001; Nakano et al. 2004)

$$R = \frac{I_{s,D}}{I_s} \cdot 100 \,(\%)$$

Residual Capacity Index (%)

Is seismic index;

Is $\propto CxF$ with $C \propto base sh$

Reduction Factor





Table 3: Seismic Capacity Reduction Factor η (JBDPA [1])

| Damage Class | Brittle Column* | Ductile Column* | Wall w/o Boundary Columns* | Column w/ Wing Wall(s)* | Wall w/ Boundary Columns* |
|-----------------|-----------------|-----------------|----------------------------------|----------------------------|---------------------------------|
| | 0.95 | 0.95 | 0.95 | 0.95 | 0.95 |
| 11 | 0.60 | 0.75 | 0.60 | 0.60 | 0.60 |
| 411 | 0.30 | 0.50 | 0.30 | 0.30 | 0.30 |
| IV | 0 | 0.10 | 0 | 0 | 0 |
| ٧ | 0 | 0 | 0 | 0 | 0 |

ASSESSMENT OF RESIDUAL CAPACITY with SPECTRAL APPROACH

Residual Capacity REC_{Sa} spectral acceleration corresponding to collapse

REC_{Sa} found applying <u>IN2</u> method <u>for intact or</u> damaged building (Polese et al., 2013)



$$REC_{Sa} = C_b \cdot \mu_{cap}$$


for
$$T_{eq} \ge T_c$$



Note similarity with definition of Is (and damaged Isd) by (Nakano et al. 2004)

Is seismic index; Is,D seismic index reduced due to damage; Is ∝ CxF with C ∝ base shear coeff. and F ductility factor

Assessment OF RESIDUAL CAPACITY for Damaged buildings



Pushover based procedure to assess behavior of damaged buildings


(Polese et al. 2013, adapted after FEMA 306)

need for suitable calibration of plastic hinges modification factors for existing buildings (typically with non-conforming elements)

PLASTIC HINGES MODIFICATION FACTORS


for NONCONFORMING columns

Definition of plastic hinges modification factors (after FEMA 306, 1998)




| | stiffness | strength | Plastic rotation |
|---------|---------------------|-------------------|------------------|
| intact | K | My | a |
| damaged | K'=λ _K K | $My'=\lambda_QMy$ | a'=a-ad |

Modification factors as a function of local ductility demand (Di Ludovico et al., 2013)



Modification factors shall be derived via experimental calibration



Evaluation of REsidual Capacity (REC)

A key aspect is the assessment of suitable REDUCTION FACTORS to determine residual capacity:

Based on damage level (post-earthquake assessment)

Based on ductility demand (modeling)

Needconsistent values for:



Deifficitient efetaena greetsictilitayrinatecoalumns, walls,)

➤ forethist viron type em (pontspansall be thist viron FELY) Des 307 & Japanise approach to be extended)and more test-based calibration of REDUCTION FACTORS

Damage Data (speed survey form)

The DAMAGE DATA collected in the Aedes survey form (speed form, for tagging purposes)

Definition of the damage levels for RC structural elements - beams and columns (in Aedes)

| | Damage level | | DAMAGE (1) | | | | | | | | |
|----|--|-------|------------|-------|-------|-----------|-------|-------|-----------|-------|------|
| | - extension | | D4-D5 | | | D2-D3 | | | D1 | | |
| | | Ve | ry Hea | vy | Medi | ium-Se | vere | | Light | | _ |
| co | ructural mponent e-existing damage | > 2/3 | 1/3 - 2/3 | < 1/3 | > 2/3 | 1/3 - 2/3 | < 1/3 | > 2/3 | 1/3 - 2/3 | < 1/3 | Null |
| | | Α | В | С | D | E | F | G | Н | _ | L |
| 1 | Vertical structures | | | | | | | | | | 0 |
| 2 | Floors | | | | | | | | | | 0 |
| 3 | Stairs | | | | | | | | | | 0 |
| 4 | Roof | | | | | | | | | | 0 |
| 5 | Infills and partitions | | | | | | | | | | 0 |
| 6 | Pre-existing damage | | | | | | | | | | 0 |

^{(1) -} The damage extension must be filled only if the corresponding damage level is present in the

| Damage | Description |
|--------|--|
| D1 | Cracks up to 1 mm in beams and up to 0.5 mm in columns or walls, if not related to concrete crushing. Diagonal cracks in external walls up to 1 mm (up to 2 mm if at the frame interface) |
| D2-D3 | Cracks up to 4-5 mm in beams and up to 2-3 mm in columns. Imperceptible leaning. Incipient buckling of reinforcing bars and concrete cover spalling. Diagonal cracks in external walls up to few mm. |
| D4-D5 | Collapse or inclination more than 1%. Crack width is more than 5 mm in beams and 3 mm in columns. Buckling of reinforcing bars. |

Examples from Manual










Δ104

Damage data vs residual capacity

How can we connect those damage definitions to local ductility demand and to the relative residual capacity variation?

Experimental assessment through residual cracks



Maeda et al., 2004

Di Ludovico et al., 2013

Damage data vs residual capacity

AFTER SPEED ASSESSMENT FOR ALL DAMAGED BUILDINGS

What DAMAGE DATA is collected in the Aedes survey form (speed form, for tagging purposes)

| | Damage level - - extension | | DAMAGE (1) | | | | | | | | |
|----|--|------------|------------|---------------|-------|-----------|-------|-------|-----------|-------|------|
| | | | D4-D5 | | 1 | D2-D3 | | | D1 | | |
| 1 | | Very Heavy | | Medium-Severe | | Light | | | = | | |
| co | ructural mponent e-existing damage | > 2/3 | 1/3 - 2/3 | < 1/3 | > 2/3 | 1/3 - 2/3 | < 1/3 | > 2/3 | 1/3 - 2/3 | < 1/3 | Null |
| | | | В | С | D | Е | F | G | Н | | L |
| 1 | Vertical structures | | | | | | | | | | 0 |
| 2 | Floors | | | | | | | | | | 0 |
| 3 | Stairs | | | | | | | | | | 0 |
| 4 | Roof | | | | | | | | | | 0 |
| 5 | Infills and partitions | | | | | | | | | | 0 |
| 6 | Pre-existing damage | | | | | | | | | | 0 |

(1) - The damage extension must be filled only if the corresponding damage level is present in the

DATA available as percentage at the building level: difficult to use for lumped plasticity models, unless a mechanism type is assigned

Damage data vs residual capacity

AFTER DETAILED ASSESSMENT AT SINGLE BUILDING LEVEL (lengthy, but necessary for decision)


What is available at the SINGLE BUILDING LEVEL (after detailed analysis by

designer in orde

✓ DETAILED DAMAGE ASSESSMENT

✓ PHOTOS

✓ MATERIAL PROPERTIES CHARACTERIZATION



What should be implemented in data collection protocols to make assessment of residual capacity more reliable?

FOR SPEED SURVEY FORMS:

The need for speed is an imperative; data collection cannot be slowed by requests for detailed data evaluation

FOR DETAILED ASSESSMENT AT THE BUILDING LEVEL:

Request to categorize damage according to:

Element types;

behavior modes;

Damage levels

Damage dis mechanism

Position

Form to collect data

| | DATIO | SENERALI |
|----------------------|---------------------------------|-------------------------------------|
| Limine | | |
| Married . | 1 | |
| Notice 1 | Pictoria | Ame of Corrowed: |
| opinion) | DAII | PRAIKA |
| PROTOCOLID | 0.04408-07512-0175-2 GW- | LAT |
| MAL certains | | |
| | DATI GE | OMETRICI |
| Andrea Tomas (m) | | Supervisioners (mg) |
| of York Sepreciousid | | Alternativity techni |
| of fair home. | | pay remain fed |
| | DATI AZIG | ONE SISMICA |
| 12 | Congress Million | Categoria Fapagraficia. |
| Registric or points. | | Tagonina in pleasure: |
| Dati dinami | e epuit | 0-(0.0) |
| 28: | 82 | tr. |
| MPE | WHE | Aleg: |
| - | CARATTERISTICHE MATE | RIALLE DETTAGLI COSTRUTTIVI |
| alcastrumo | Accinio | Staffe |
| th partie | him plants | Their Figure |
| | Spalge have | Takes Parcel |
| | 200.00 | Det. Net |
| | DATI INT | ERVENTO |
| Depositor | D tetativat | to Local Dialglaryments |
| ATEMPRITA L | | ACTRO ATTENUENTO: |
| ITERNENTO A | | |
| engygen a | | |
| T-BOOKETTO-BO | | |
| | catani di riodhia: rapporta tra | repecte e domende in termini di PCA |
| | catari di riodhia: rapporta tre | repeché e domanda in termini di PCA |





Mauro Dolce

Presidency of Council of Ministers - Civil Protection Department Email: Mauro.Dolce@protezionecivile.it



Claudio Moroni

Civil Protection Department Email: Claudio.Moroni@protezionecivile.it



Gaetano Manfredi

University of Naples Federico II

Department of Structures for Engineering and Architecture

Email: aprota@unina.it



Andrea Prota thank you!

University of Naples Federico II

Department of Structures for Engineering and Architecture

Email: aprota@unina.it



Marco Di Ludovico

University of Naples Federico II

Department of Structures for Engineering and Architecture

Email: diludovi@unina.it



Maria Polese

University of Naples Federico II Department of Structures for Engineering and Architecture Email: mapolesei@unina.it







2010 CHILE EARTHQUAKE AND DATA COLLECTION METHODOLOGIES

- Characteristics of the ground motion
- Emergency response system
- Information sources



BUILDING DATA

- Immediate damage inspections
- Detailed visual inspection of damaged buildings
- Structural recovery or rehabilitation projects



GEOPHISICAL, EARTHQUAKE AND TSUNAMI INFORMATION

- Instrumental data
- Geotechnical data
- Tsunami data



SOCIAL AND HUMAN IMPACT

- Mental health
- Economic losses



LIVELINES AND CRITICAL INFRASTRUCTURE

- Hospitals, schools, ports, road network
- Potable water, communications and electric power systems



LESSONS LEARNED

Conclusions





POST-EARTHQUAKE DATA COLLECTION: THE 2010 MAULE EARTHQUAKE IN CHILE


De la Llera, J. C.¹, Rivera F.¹, Jünemann R.¹, Mitrani-Reiser, J.², Fortuño C.¹, Hube M.¹, Santa María H.¹, Ríos M.¹, Lagos R.³, Guendelman T.⁴, Candia G.¹, Ledezma C.¹, Cienfuegos R.¹, Lindenberg, J⁴.

ABSTRACT

This article presents an overview of the different processes of data recollection and the analysis done by different stakeholders during and after the emergency caused by the 2010 Maule earthquake in central-south Chile. The article is not an exhaustive recollection of all of the processes and methodologies used; it rather points out some of the critical processes that took place with special emphasis in the earthquake characterization and building data. Although there is strong similarities in all of the different processes for collecting data after the earthquake, the evidence shows that a rather disaggregate or atomized approach was used by the different stakeholders. Moreover, no common standards were implemented or used, and the resulting granularity and accuracy of the data was not comparable even for similar cases, which sometimes led to inadequate decisions. More centralized efforts were observed in resolving the emergency situations and getting the country back to normal in its operation, but the reconstruction process took different independent routes depending on several external factors and actions of individuals and communities. Several conclusions are presented that are lessons derived from this experience in dealing with a large amount of earthquake data. The most important being the true and immediate necessity of making all critical earthquake information available to anyone who seeks to study such data for a better understanding of the earthquake and its consequences. By looking at the information provided by all these data, we aim to finally improve seismic codes and engineering




National center for integrated disaster management, CIGIDEN




Data collection Problem


Surveying Capacity



Analysis & evaluation of data











2010 CHILE EARTHQUAKE AND DATA COLLECTION METHODOLOGIES

Seismic Setting




















Deaths

~ 580 in 2010

~1600 in 1960

~ 800 in 1922










Feb-27 Earthquake






Instrumental Data

| Data type | Source | Website |
|---------------|--|---|
| Acceleration | Servicio sismológico Nacional (SSN) of Chile | http://www.sismologia.cl/ |
| records | Renadic | http://terremotos.ing.uchile.cl/ |
| Waveform data | IRIS | http://www.iris.edu/wilber3/find_event |
| | UNAVCO Data Archive | http://facility.unavco.org/data/dai2/app/dai2.html# |
| | International GNSS Service | http://igscb.jpl.nasa.gov/ |
| GPS | Argentinian cGPS network operated by Instituto Geografico Nacional (IGN) of Argentina | http://www.ign.gob.ar |
| GI S | Brasilian cGPS network operated by Instituto Brasileiro de Geografia e estatistica | http://www.ibge.gov.br/ |
| | Chilo-German observatory of Concepcion operated by BKG-Frankfurt/U-Concepcion/IGM | http://www.tigo.cl |
| InSAR | Tong et al (2010) | http://supersites.earthobservations.org/chile.php#surface |
| SAR images | JAXA, ALOS/PALSAR data | http://www.eorc.jaxa.jp/ALOS/en/ |




Curico records


REGISTRO RENADIC: ESTACION: HOSP CURICO / P. SOTO R. BOROSCHEK UNIVERSIDAD DE CHILE RED NACIONAL DE ACELEROGRAFOS




Earthquake 27/F 2010













- The change in viewing geometry and surface changes is dectected as a change in phase
- The range-change is related to various geometric sources




$$\Delta \phi_m = -\frac{4\pi}{\lambda} \left(\Delta R_{\text{datum}} - \frac{B_{\perp}}{R \sin \theta} z - \delta \right) + \phi_{\text{noise}} + n \cdot 2\pi$$

Deformation







Interferograms 2010





Figure 3: (a) Ascending unwrapped interferograms for Maule 2010 earthquake, (b) Aftershocks $M_w \ge 5$ of Maule 2010 earthquake between Feb 27 and May 29 2010








GeothecnicalData








| Dam | Construction | Туре | Height | Crest Length | Distance to Epicenter | |
|-----------------------------|--------------|------------------|--------|--------------|--------------------------|--|
| | year | | (m) | (m) | (Km) | |
| Lliu Lliu | | Rockfill | 20 | 530 | 340 | |
| Rapel | 1968 | Concrete arch | 90 | 330 | 230 | |
| Colbun | 1985 | Earthfill | 110 | 670 | 130 | |
| Pehuenche | 1991 | Earthfill | 80 | 370 | 150 | |
| Cipreces | 1955 | Gravity pipes | | | 175 | |
| Cioihueco | | Earthfill | 20 | 500 | 180 | |
| El Toro | 1973 | Gravity pipes | 540 | | 120 | |
| Abanico | 1952 | Gravity pipes | 150 | | 195 | |
| Hueleheico | | | | | 210 | |
| Pangue | 1996 | Concrete gravity | 103 | 360 | 240 | |
| Ralco 2004 Concrete gravity | | 155 | 360 | 260 | | |
| Ralco 2004 Concrete gravity | | 155 | 360 | 260 | | |

Source: GEER Report



















International Teams



US Teams: EERI (LFE); ASCE (TCLEE); USGS (GEER)

EERI focus on: reinforced concrete, masonry, and steel buildings; bridges; healthcare facilities; non-structural building components; instrumentation; social sciences/planning/policy/recovery; and tsunami effects





Talca Regional Public Hospital, Talca, Chile, March 19, 2010

Rick Bissell

Professor of Emergency Health Services, University of Maryland Baltimore County

Francisco de la Masa

Chile Ministerio de Salud Santiago, Chile

Judith Mitrani-Reiser

Assistant Prof of Civil Engineering, Johns Hopkins University

Bill Holmes

Structural Engineer, Rutherford & Chekene, San Francisco, CA

Thomas Kirsch

Associate Prof and Co-Director of the Center for refugee and Disaster Response, Johns Hopkins University

Mike Mahoney

Senior Geophysicist at FEMA, Washington, DC

Nicolas Santa Cruz Marin

Graduate Student of Civil Engineering, Pontificia Universidad Catolica, Chile



Goals of Hospital Team

- Assess physical damage:
 - structural
 - non-structural
 - utilities
 - equipment
- Identify vulnerabilities that can:
 - threaten patients
 - reduce the hospital's functional capacity (ability to provide medical care)
- Develop a protocol to collect detailed data measuring effectiveness and vulnerabilities of a single region medical system
- ► Assess the physical and medical similarity of Chilean Hospitals to the USA system



Hospital Damage Overview

- No hospital suffered a complete structural failure
- ▶ Total number of hospitals in shaken region: 130
- Of the 79 damaged hospitals:
 - 4 uninhabitable
 - 12 had greater than 75% loss of function
 - 8 partially operating after main shock
 - 62% needed repairs or replacement
- Many had extensive loss of equipment
- ► All lost power, external water supply, and communications






Hospitals studied in the Bio-Bio Province:

- Los Angeles Regional Hospital
- Hospital de Hupiel
- Hospital Laja
- Hospital Santa Barbara
- Hospital Nacimiento
- Hospital Yumbel
- Hospital Mulchen





Hospitals





Functional Damage

- ▶ Damage causing disruption and affecting patient safety:
 - Loss of communication
 - Loss of power
 - Loss of water
 - Elevator outage
 - Water damage
 - Damage to bulk oxygen tanks
 - Ceiling failures
 - Nonstructural masonry damage
 - Disruption to special services such as paper medical records, pharmacies, and laboratories
 - Damage to medical equipment
 - Damage to MEP equipment
 - Damage to MEP distribution systems



- ▶ The need to evacuate patients is a significant failure because it:
 - is extremely dangerous for patients
 - takes staff away from serving externally injured
 - creates demand for patient space, possibly off site

Mutual aid

- no patients were emergently transferred to other facilities (probably due to poor communications)
- patients were temporarily housed on site
- many were discharged to their homes
- in a few cases, patients were transferred later



- ► Significant failures; most due to derailed counterweights
- ▶ In every building evacuated, elevators were inoperable, requiring patients to be carried down stairs or ramps
- ► Elevator machine rooms and shafts are typically accessible only by elevator maintenance service or one person on site







Communication Systems

- No plan for emergency communication in facility or between facilities, particularly to the centralized headquarters of the health system
 - lead to isolated hospital 'islands'
- Over-reliance on cell phones
 - widespread power outages
 - towers were down for days

Most consistent issue identified by hospital administrators





- ► All facilities lost outside power for various time periods (up to 3 days)
- ► All facilities have emergency generators and at least 3 days fuel supply. However:
 - Some generators did not automatically turn on and needed a manual start
 - The generators were not always sufficient to power important medical equipment (e.g. radiology) or the entire facility



Water Damage

- ▶ Most hospitals had on-site storage for 3 or more days of essential water (or wells)
 - Unlike most hospitals in the USA
- Water pressure from backup systems was often not sufficient for toilets and some medical equipment and the HVAC
- Some received priority water deliveries from municipal authorities
- ► Other water-related damage: damage to distilled water tanks, pipe failures and flooding





Water storage tanks



Water storage tank at Concepcion.



New tank under construction at Talcahuano—not quite in time



- ► Damage/disruption from water
 - not frequent
 - caused at least three buildings to be evacuated
 - shut down 3 of 6 ors in relatively new building



Water Damage

► 2005 building in Los Angeles
Hospital: brick in-fill wall collapsed
onto a water tank holding roughly
150 gallons of distilled water;
water traveled through joints
damaging hallway in front of
surgical ward and shutting down
50% of the ward.





- Some hospitals lost internal systems
- Bulk oxygen storage tanks
 - Standard of practice is to anchor: no overturning reported.
 - Tensile yield failure of threaded fasteners.
 - Punching shear failure of tank leg.










- Suspended lay-in ceilings Generally without any seismic detailing.
 - Most consistent failure.
 - Often causes little real damage but great fear and disruption
 - Fallen light fixtures and air registers can be life safety issue
 - Older ceilings drop dust and other debris (in the US, often asbestos)




► Los Angeles Hospital: fallen light fixtures and mechanical registers, in addition to ceiling panels





► Retrofit: clips used to stabilize ceiling tiles at Talca Hospital (new building)





► Retrofit: packing tape used to keep dust out of ICU showed excellent seismic performance!





- ► Infill masonry/heavy partition damage
 - Considered "nonstructural" but, like ceilings, causes fear, creates dust and occasionally risk of injury.





- ► Apparently vulnerable areas like paper medical records, pharmacies, and laboratories
 - Usually damaged only when building had other nonstructural damage

► Medical Equipment

- Usually damaged only when building had other nonstructural damage
- Damage to radiological equipment recorded



► Essentially unstable medical record storage—undamaged. Nacimiento.





▶ Still working on straightening out Talcahuano medical records after 3 weeks









- Loss of power, water, and communication
- Severe damage to suspended ceilings
- ► Mechanical equipment damage resulted in loss of hot water affecting kitchen, laundry, and sterilization services
- Medical equipment damage forced hospitals to sterilize off site, and disrupted diagnostic services
- ► Water damage forced hospitals to shut down buildings, dialysis treatment, and had severe sterilization implications (e.g., surgical ward)
- ► Stand-alone shelving damage, resulting in disorganization of medical records for few days to several weeks



Hospital Physical Damage Impact

- ▶ Damage from even very small details can shut down a hospital.
 - Water damage from a small pipe break shut down operating rooms.
- Securing both mechanical and medical equipment can be critical to maintaining hospital operations.



Hospital Preparedness


- All hospitals had backup systems for water and electricity, although they were not always sufficient to provide services
 - But none had backup for sewer
- ► Communications systems need redundancy.
 - Lead to complete isolation
 - One used ambulance radios for local communications.



- Hospitals do not have to collapse to be rendered inoperable
- ► Functional losses are usually due to non-structural damage
- Communications systems are critical!
- Redundancy is necessary for water, power, and sewage systems
- ► Like Katrina- Hospitals must be prepared to be on their own for 2-3 days in a major event



► San Fernando Earthquake 1971 (M_W 6.6; 6:01am PST) Olive View Medical Center





► San Fernando Earthquake 1971 (M_W 6.6; 6:01am PST) Olive View Medical Center



Seismic Performance of US Healthcare Facilities

▶ Northridge Earthquake 1994 (M_W 6.7; 4:31am PST) Kaiser Permanente Building



Acknowledgements


- ► This study was supported by the Earthquake Engineering Research Institute's Learning from Earthquakes (LFE) Program, the Johns Hopkins University's Office of Critical Event Preparedness and Response (CEPAR), and the Federal Emergency Management Agency (FEMA).
- We would also like to acknowledge the valuable input and support from Professors Juan Carlos de la Llera and Catterina Ferreccio at Pontificia Universidad Católica, Ministro de Salud Jaime Mañalich, Subsecretaria de Redes Asistenciales Giovanna Gutierrez, Rossana Fuentes, Jaime Vidal, and all the wonderful MINSAL employees who hosted us and patiently answered all of our questions.



Seismic response of Ports



Port Location







Liquefaction


- Saturated and loose sands $(\sigma_n = \sigma_n^{'} + u_w)$
- Consequences:
 - Temporary loss of support and stiffness






























Drag of foundation systems






Slanted piles are laterally very stiff






Torsion



Torsion












K-12 Public Schools

State of public schools after the earthquake



- 51 schools
- Structural assessment and retrofit projects

▶ Schools in RESCATE Project






► Rapid inspection and damage assessment


PROYECTO RESCATE Cód. Establecime FICHA GENERAL POR ESTABLECIMIENTO DICT **ESTABLECIMIENTO** FECHA INICIO FICHA N° LICEO FEDERICO HEISE MARTI - CUERPO 1 - EDIFICIO ACCESO DIRECCIÓN REGIÓN ÁREA GEO. URRUTIA S/N PARRAL URBANA NOMBRE CONTACTO CARGO TELÉFONO Marcela Guzmán Arquitecta SECPLAN 73-637710 mguzmanarquitecto@gmail.com INFORMACIÓN GENERAL DE ANTECEDENTES INFORMACIÓN GENERAL DE LA ESTRUCTURA Área en planta [m²] veles sobre terreno Materialidad Sistema de tabiquería Hormigón Armado (H.A.) Losas de H.A. Placas de yeso cartón Albañilería Armada (A.A.) Losas aligeradas Albañilería Confinada (A.C.) Vigas de madera Placas de OSB Albañilería Simple (A.S.) Vigas de acero Observaciones adicionales: Daños importantes en albañilería confinada y columnas de hormigón armado de segundo y tercer piso. RESUMEN GENERAL VISITA A TERRENO Nº días de inspección Fotografías 8769, 8771 a 8775 8540 Carl Lüders Nº personas inspección ESTADO GENERAL DE LA ESTRUCTURA terminados puntos de la estructura. Sin embargo, existe la factibilidad de Daño leve cuperación. De acuerdo a esto, se recomienda desarrollar un proyecto MAPA Y/O FOTOGRAFÍA DEL ESTABLECIMIENTO

▶ Damage Level in RESCATE Schools




Schools Detailed inspection

Structural damage by element




Schools Detailed inspection

Structural damage by element





Structural damage by element



Schools Detailed inspection

► Structural elements


| Nestor Aguirre | INSPECCIONÓ | ingeniero P | esponsab | in | Fecha | Fioha Nº | Total | Fotografias |
|--|--|-------------------|--------------|----|-------|------------|------------|----------------|
| ELEMENTO ESTRUCTURAL NIVEL DE 1 2 3 4 Información Adicional MATERIALIDAD - TIPO DE DARO Lave Medio Severo Colapso (Existe Figuracion? A Muro HA. falla corte B Muro HA. falla corte C Viga HA. falla fiexcocompresión ma poyos X C Colama HA. falla corte C C Viga HA. falla fiexcocompresión C Colama HA. falla corte C C Colama S C Colama S C C C C C C C C C C C C C C C C C C | | | | | | | _ | |
| A Muror H.A. falla cortie A Muror H.A. falla cortie B Muror H.A. falla finaccompression C Viga H.A. falla finaccompression E Viga H.A. falla finaccompression C Viga H.A. falla finaccompression C Viga H.A. falla finaccompression E Viga H.A. falla finaccompression C Columna H.A. falla cortie C Columna H.A. falla finaccompression H. Nudo H.A. falla finaccion C Columna H.A. falla finaccion Lose H.A. falla finaccion J Muro albatiliteria controlada falla cortie K Muro albatiliteria controlada falla cortie M Biscontrol H.A. falla controlada falla cortie M Elemento H.A. falla controlada falla cortie M Elemento H.A. falla controlada D Otro (especificar) Francisci ricia in el alorgi. D Otro (especificar) Francisci ricia in el alorgi. Sección L[cm)el(cnt (*Area losas al[cm)bt(cmt)) Elemento H.A. falla controlada Muros Columnas Sección L[cm)el(cnt (*Area losas al[cm)bt(cmt)) Elemento H.A. falla controlada Nuros Columnas Vigas Columnas Vigas Columnas Vigas Columnas Vigas Columnas Vigas Columnas Franciscimiento (cmt) Recubrimiento (cmt) | | | | | | | informa: | ión Adicional |
| A Mure H.A. fails covrie B Mure H.A. fails accorde C Viga H.A. fails flexocompression F Columna H.A. fails corrie C Columna H.A. fails flexocompression F Columna H.A. fails corrie C Columna H.A. fails corrie C Columna H.A. fails flexocompression F Columna H.A. fails flexocompression C Columna H.A. fails flexoco | | | | | | | | |
| B Murc H.A. falls forecompresión C Viga H.A. falls forecompresión E Viga H.A. falls forecompresión C Observaciones Adicionale E Viga H.A. falls forecompresión C Columna H.A. falls come C C C C | | | - | | | - | | |
| © Viga H.A. falia financompresión E Viga H.A. falia financompresión I Columna H.A. falia conte Columna H.A. falia conte I Columna H.A. falia conte I Columna H.A. falia conte I Maria financión diagonal I Lidia H.A. falia financión J Muro altarifieria continuala talia conte K Muro altarifieria continuala talia conte E Muro altarifieria continuala conte E Muro altarifieria continuala conte E Muro altarifieria continuala talia conte E Muro altarifieria continuala conte E Muro altarifieri | | | | | | | Ancho Pr | |
| E Viga H.A. fatila filescoonspresión en apoyos X | | | | | | | | |
| E columna H.A. falla corrie Columna H.A. falla corrie Columna H.A. falla strucción diagonal I. Losa H.A. falla tracción diagonal I. Losa H.A. falla fallación J. Wuro alfastifieria confinida talla corte K. Muro alfastifieria cominada talla corte L. Muro alfastifieria cominada talla corte L. Muro alfastifieria simple talla corte V. Falla de sentamiento D. Oto (sespecificar): Transción talla si existe V. Sección L[om]e(cni / Ácta lossas sijom)ot(cni) Espesor(oni) Espesor(oni) Piso - Ejes N-S. 6 Ejes S-O. E RRMADURAS DE REFUERZOS (solo ci con vicibles): Muros Columnas Vigas Corfinamento Borde L.orgitudinal Columnas Vigas Confinencio (cni) Recubrimiento (cni) | | | | | | | Observacio | nes Adicionale |
| Columna K.A. falla decided diagonal H. Nudo K.A. falla tracided diagonal Lose K.A. falla fusicide diagonal J. Muro albuffiella confinada talla corte K. Muro albuffiella confinada talla corte L. Muro albuffiella confinada talla corte M. Elemento R.A. falla corroadin N. Elemento R.A. falla corroadin N. Eatla de assentamienzo D. Otto (sepocificar): formatio risks et al dore. DIMENSIONES Y UBICACIÓN DEL ELEMENTO LELEMENTO SENDIONES Y UBICACIÓN DEL ELEMENTO LELEMENTO Muros Columnas Columnas Vigas Vigas Confinantero Borde Longitudinal Confinantero Borde Longitudinal Confinantero Borde Nutros Columnas Confinantero Borde Longitudinal Columnas Confinantero Borde Longitudinal Confinantero Columnas Vigas Confinantero Columnas Vigas Confinantero Columnas Vigas Confinento Columnas Vigas Confinento Columnas Confinento Columnas Columnas Confinento | | n apoyos | X | | | | | |
| R. Riside H.A. fails specified diagonal J. Less H.A. fails favoid in the corte W. Muro attainifiests continued table corte W. Muro attainifiests ammade table corte L. Muro attainifiests ammade table corte W. Extension H.A. fails correctors M. Extension H.A. fails correctors N. Fails de seentherinemitio D. Otro (expectificar): **Transcort make an el seque.** UBICACIÓN DEL **ELEMENTO LELEMENTO ARMADURAS DE REFUERZOS (solio el con visibiles): **Muros Columnas Wigas ARMADURAS DE REFUERZOS (solio el con visibiles): **Muros Columnas Orifinamiento Borde Longitudinal Longitudinal Longitudinal Entitibos Recubilimiento (cm) | | | | | | | | |
| I Lose H.A. falls fexión J Nuro albutifierta continuata talla conte E Muro absutifierta minda talla conte L Nuro absutifierta minda talla conte E Muro absutifierta minda talla conte E Muro absutifierta minda talla conte D Otro (especificar): Torrector triba sel acopte DIMENSIONES Y Sección L(om)n(cm) / Area lossas a(cm)b(cm) E Sepeso(cm) Piso - Ejes N-S 6 Ejes E-O E RRMADURAS DE REFUERZOS (colo si son visibles): Muros Columnas Vigas Confinamento Borde Longitudinal Conte Malla Estribos Estribos Estribos Estribos Procubimiento (cm) Recubimiento (cm) | | | | | | | | |
| J Muro attentitenta confinada taña conte k Muro attentitenta amada taña conte L Muro attentitenta amada taña conte M Elemento H.A. faña conroadón Fatta de aestenamento D Otro (especificar): / Immobil misia el alongo DIMENSIONE S Y USICACIÓN DEL ELEMENTO LEMENTO ARMADURAS DE REFUERZOS (colo el con visibles): Muros Columnas Vigas Conglitadinal Longitadinal Longitadinal Estribos Estribos Estribos Estribos Finada (con y Maria de Conglitadinal Estribos Estribos Estribos Estribos Estribos Estribos Entrevuero Vertical (en A.A.) Maila inferior Maila Esperior Recubrimiento (con) | | | | | | | | |
| K Muro attaititeria ermade falla corte L Muro attaititeria ermade falla corte L Muro attaititeria principie talia corte M Elemento H.A. falle corrosofor N Fatta de exentamiento D Otro (expecificar): | | orte | | | | | | |
| L duy attentitienta simple tatla corte M Elemento HA. Falla controlor N Estra de acentralizanto O Oto (sepocificar): **Transition triba in al alopo.** DIMENSIONE Y UBICACIÓN DEL ELEMENTO X **TRANSITIONE Y UBICACIÓN DEL ELEMENTO **X **TRANSITIONE STATE **TRANSITIONE ST | | | | | | | | |
| N Falls de esentamientilo D Oto (especificar): X | L. Muro attarilleria simple talla cort | | 717-1 | | | | | |
| D Oto (sepectficar): // furnishin finite in a storp. DIMEN\$ (ONE) \$ Y UBICACION DEL ELEMENTO X | M Elemento H.A. fafia corrosión | | 11 1 1 | | 1 | | | |
| | | - 13 | J L | | 0 | | | |
| | | | x | | | | | |
| VBICACNON DEL | Portugues (Osse at at apopo- | | | | | | | |
| E Imiliary E I | Dimensiones : | h[cm] / Area loss | as ajomjebje | m] | Esper | nor[cm] | | |
| Ejes 5-0 E | | | - | | | | | |
| Muros Columnas Vigas Confinamiento Borde Longitudinas Longitudinas Dobte Malia Estitos Estitos Recubrimiento [cm] Recubrimiento [cm] Recubrimiento [cm] Fabba Losas Referezo Vertical [en A.A.) Malia sinferior Mata Superior Escalarillas Recubrimiento [cm] Recubrimiento [cm] | ELEMENTO | - | - 9.7 | | | L.P. | Ejes E | 0 E |
| Sosierillas Recubrimiento [cm] Recubrimiento [cm] | rabes | | | 4 | Lo | sas | | |
| Escalerillas Recubrimiento [cm] Recubrimiento [cm] | | Malia inferi | ior | | | | rior | |
| FOTOGRAFIAS ELEMENTO ESTRUCTURAL DAÑADO | Escaleritas | Recubrimie | into [cm] | | | Recubrimie | nto [cm] | |
| STOCKE WE SEEMEN O 25 THUS UNAS DATABLE | EOTOGRAPIA EL CHENTO PATO | | | | | | | • |
| | | 1 | | | | | | |

Non Structural elements

| y | | L | 7 | C | HIERÍA TUC | ELEN | MENTOS | - 1 | 10432 | | | | | | | | | |
|------------------------------------|------------------|--------------|---------------------|---------|-------------------------------------|--|------------|------------------------|----------|-------------------|---------------|-------------|------------|--------|------|---|--|--|
| INSPECCIONÓ Pablo Femández | | | | | | | Ing | Feoha | 10. | Floha No | | | | | | | | |
| | | | | | | - 112 | | 28/01/2011 | | 2 | 1 | 36 | | | | | | |
| R | EC | NTO | 0 | | Piso 1 | 0 | res indice | ciones (si co | rrespon | ide): | | | | | | _ | | |
| Pa | bel | lón . | Α- | | E m N-S 1.3 - | 1.4 | | | | | | | | | | | | |
| | Sal | 23 | | 14 | Ejes E-O 1.A - | 1.B | | | | | | | | | | | | |
| | | | EL | | ENTOS HORIZON | | - | | | | | | | | | | | |
| Descripción Materialidad Patología | | | | | | | Nivel | de daño | 0 | tra materialidad | (especificar) | | Fo | logn | _ | è | | |
| ijel | _ | | | | P.V.C. | | | 4.000 | | | | - | 0302 | | | | | |
| 'av | men | to_ | | | CER | • | | | | | | _ | | 030 | _ | _ | | |
| | | | | | NTOS VERTICA | | | | | | | | | | | | | |
| 8E | MUI | EST | RA | UNA | A FOTOGRAFIA | A-12 C - 1-1 L | | | | The second second | | | | | _ | | | |
| 11 | | | | | Descripción | | malidad | Patolo | 10 | Nivel daño | Othe ma | derisdae | (wap | waitle | M) | | | |
| ĵ. | | | | | Elemento vertical | | H.A. | | | | | | | | | _ | | |
| Otto meteralished graphed four | | | | | Revestimiento | _ | PIN | - | | - In- | | | | | | _ | | |
| - | | | | | Altura revestimient Fotografias: | 0303 (| 1 | N° puertas N° vent. | 0 | | | | | | | _ | | |
| 8 | * | * | | | V V | 0303 | 0304 | M. ABULT | | Danc - | | 1.70 | > | 71 | m | т | | |
| 9 | | | à | Ţ | | (4) | | | | | | | | | | | | |
| Niveldaño | + | Lave | Dafe | Oafe | | | | | П | N. | 7 | 0305 a 0306 | ω | PIN | -HA | | | |
| pla | Ŧ | 0 | 0 % | Þ | | - | b | | | | Į. | 8 | 3 | | | 1 | | |
| Patologia | | DESC | seppord, N | N WILL | Fotog | noff a | 0004 | | | Fotografia | 0000 | vert | "puertas: | | х | | | |
| Materialidad | HA. | PIN | [m] | - | 18 | | - | • | | - Charles | 9 | ы | 6,3 | H | | + | | |
| Matter | - | Н | anto 3 | 0100 | | | • | M | | W | | Daño: - | Darto: DPU | ٠ | į. | | | |
| Descripción | Bernanto vertica | Savestmismis | Wans neveral manual | dogstan | Fotografia costo Fotografia coco | | | | | | | | | | | | | |
| See the table to the | | | | | Materialidad | terialidad Patologia Nivel daño Otra materialdad (especificar) | | | | | | | | 1 | × | | | |
| Elemento vertical Revestimiento | | | _ | 11 | HA - | | | | | | - | | | П | | | | |
| | | | | | PIN | 0.0 | | | | | | 4 | | П | | | | |
| | | vest | mie | nta: | 3 [m] | v" puertas: | 0 | Dario: - | | | | - | | ı | | | | |
| | grai | | | | 0307 a 0309 | V" vent.: | 0 | Dafe: - | | | | | Ш | ᆫ | L | 1 | | |
| INSTALACIONES ¿En funcionamiento? | | | | | ¿En funcionamien | to? | Desc | ripción del d | afio (en | caso que com | esponda) | | Fo | togri | dias | | | |
| Agua - | | | | | | 1 | | | - | | | | | | | | | |
| | | dad | | | 86 | | - | Encienden 4 | de 14 t | ubos fluorescer | yten. | | | - 7 | | | | |
| Gas - | | | | | | | , | | | | | | | | | | | |



Ministry of Public Work





Damage Levels

DL-1: No damage

DL-2: Low damage that required minimum or no repair

DL-3: Damage that required repair

DL-4: Collapse

Bridge Damage Level









Girder Damage Level











Failure and solution process Llacolén Bridge, Bíobío Region






► Failure and solution process Claro River bridge





Road Network Sif platform

















Communication system



















DataCollection process

| Type of Inspection | Immediate damage Inspection | Detailed visual inspection of damaged buildings | Structural recovery or rehabilitation project |
|--------------------|---|---|---|
| • | Community/owners/local | Owners/constructors/local government | Owners/central government |
| Objective | Define basic security conditions of housing units: habitable/non-habitable/ collapse risk | Analyze the current status of damaged buildings and decide repair or demolition | , , , |
| What? | Global building situation/general building dagta/photographs | Building damage information/detalled building data (drawings, soil mechanic reports, etc.) | Detailed damage information by element/ laboratory tests |
| Who? | NGO's/volunteers/students/ professionals | Professionals/academics | Professionals/academics |
| How? | Different damage inspection reports/non pre-established plan/ on site decisions | Inspection protocols for global damage survey/ internal strategies | Detailed survery of damged elements/ instrumental measaurements |



Damage inspection in Santiago Local engineering offices

Type of information collected by local offices





FORMULARIO NUMERO

FORMULARIO DE EVALUACION DE INTESIDAD DE DAÑOS

División Ingeniería Estructural y Geotécnica

Area Ingeniería Estructural Formularlo de Evaluación de Intensidad de Daños -Rev. D

▶ Damage Inspection form

| | FORMULARIO NUMERO |
|--|---|
| Dirección | |
| UBICACIÓN: | Inspessión de la Edificación |
| Conure | Exteriores e interiores |
| Cluded | CLASIFICACIÓN DE HABITABILIDAD |
| | Verde Amarillo Naranja Rojo |
| | 10000 |
| DENTIFICACION DE LA EDIFICACION | |
| NOMBRE EDIFICACION | DESCRIPCION DE LA ESTRUCTURA Sistema estruotural |
| Williams Coll Individual | Hormigón Armado Sistema de Marcos Prefebricados C |
| Uso predominante: | Sistemas Viktos |
| Residencial 2 Comercial 3 Educacional 4 Salud | Alberileria Armeda O Cerémico C |
| E. Hotelero 6. Institucional 7. Industrial 8. Oficinas | Confinede |
| 2. Bodeges 10. Estecionemientos 11. Otros | No ermede Fiscel C |
| De la edificación De la planta baja | Acero Pórticos Amostrados |
| | Porticos no Amiostredos |
| Numero de pisos: Niveles sobre el terreno Total Sutterreness | Soldedo Apernedo O Misto C |
| | Madere Pórticos y paneles en madere |
| Dimensiones Aproximadas St. Planta: Subbraceo Sucerestudura | Porticos en madere y paneles en otro material |
| p, Planta: Subinoscep Superestructure Frente (m) Frente (m) | Observaciones: |
| Fando (m) Fando (m) | |
| | Bistema de Piso |
| ANTIGUEDAD DE LA ESTRUCTURA | Hormigón Armedo Loze → Mecize ○ Algerede ○ |
| Año de recepción de la estructura (aprox.) | Ceuter Moduler Viges |
| Reparaciones 8I No C | Acero Pleces Colebonantes, (Steel Deck) |
| | Viges de Sección Jene |
| letale: | Viges Reticulates |
| | |
| | Viges Otro. |
| | |
| I rilvel de deño en comparación al terremoto de 1935 fue: | Sistema de Teoho |
| | |
| Neror O Iguel O Neyor O NA O | Loses de Hormigón Armedo Cerches de Acero S |
| | Cerches de Medere Plece Fibrocemento C |
| STADO DE LA EDIFICACION | Tejado (cemento o cerámico) Piaca Zinc Alum Piacas de OBS Entablado Artesanal |
| VI NEW OF THE POST (PARTICIA) | Place defétice Otro. |
| estado general de la Edificación | |
| evisar la écificación en forma global y defailar las adaraciones necesarias en la sección de comenfantes | ********* |
| Existe colecto | Sistema de Tabiqueria Places de Florocemento Places de Yeso Cartón C |
| 1. No. 2 Percial 3 Total | Hormipon celular Places de 088 |
| Desviación o inclinación de la edificación o de algún entrepiso | Pieces V/DF Spopus |
| 1. SI 2. No 3. No se pudo determinar | Harmigán con galjestiteso Otro |
| Falla o asentamiento de la cimentación | |
| 1. SI 2 No 3. No se pudo determiner | Marcos Soportante de Madere |
| Fella en soporte o conservación de estanques 1. No 2. Percial 3. Total | Nercos Soportente de Aluminio |
| Falles en cabezales de muros. | |
| 1. No 2 Percial 3 Total | |
| | Security Code Security Selections |

Felle en talud o movimiento en masa
 No 2 Puntual 3 General

5. Asertamiento circundente o licuefección

1. No 2 Puntual 3 General

Muro Cortina

Estuco (normal o arquitectónico)

Memposteria




Damage inspections Engineering offices experience


▶ Damage inspection form

| PROTE | GE | | | | | FIG | СНА ТЕ | CNICA DE | DA | ÑOS | 5 - F | ABITA | CI | ONAL | | | |
|-----------------|--------------|---------|------|------|----------|---|---------|-------------|-------|------|-------|---------|--|--------------|--------|--------|-----|
| 1 IDENTIFIC | ACION I | PROPIE | DAI | 0. | | | 2. | - TIPOLOG | IAS | | | - | | | | | |
| DIRECCIÓN: | | | | | | | VIENDA | ED | IFIC | 0 | _ | OTRO | \neg | _ | _ | | |
| | | | | | | | 10" | Nº PISOS | | | PISC | ı\$ | | Nº PISO | S | | |
| | | | | | | | TH | PO AGRUPAC | CION | i | | | | | | | |
| | | | | | | | Als | SLADO | | PA | REAL | 00 | _ | CONTIN | UO | | 7 |
| | | | | | | | TIE | PO VIVIENDA | | | | | | | | | |
| | | | | | | | | RVIU | | PR | IVAD | 0 | _ | OTRO | \neg | | |
| COMUNA | COMUNA FECHA | | | | | | | | ION | APRO | MIXE | ADO | 10000 | | | _ | |
| 3 SISTEMA C | ONICTO | HOTIN | _ | _ | | | - | | | | | | | | | | |
| ALBANILERIA AF | - | _ | | LER | A RI | FORZADA | HC | ORMIGON AR | JAMU | 00 | Г | ADOBE | | MADERA | 0 | TROS | |
| 4 DAÑOS AP | DECIAD | OS FS | TRIL | CTI | IDA | DDINCIDAL | V TED | MINACIONI | FC | | | | | | | | |
| ESTRUCTURA | | | - | _ | NO | | 120 | - Incidit | _ | i No | 1 | | | | | 51 | NO |
| CIMIENTO/SOBE | | σo | | ۴ | - | MURO MED | IANERO | | 1 | 1 | - | SAS HOE | PANIC | ON ARMADO | | + | 1 |
| RADIERES | | | | | \vdash | MURO EXT | | ES INDES | + | + | | | | HORIZONTALE | 5 | + | + |
| MURO ALBAÑILI | RIA APA | AADA | | + | \vdash | ANTEPECH | | - ALIMES | 1 | + | - | | - | TECHUMBRE | | + | + |
| MURO ALBANILE | | | | | - | CADENAS/ | | | + | + | - | | _ | ANTETECHOS | | + | + |
| MURO HORMIGO | | | | - | \vdash | PILARES | 11000 | | | + | | | _ | ESTACIONAM | EMTO | - | + |
| TERMINACION | | 00 | _ | SI | NO | T. SEC. STORES | | | | a No | - | DIENKA | YE U | ESTALIUMAN | ENIO | _ | NO |
| PAVIMENTOS IN | - | r | _ | - | 1100 | TERRAZA/ | RALCON! | (Babasiba | - | - | - | LOS | - | | | 1- | 140 |
| TABIQUERIAS IN | | | - | Н | | ESCALERAS | | | + | + | - | NALES | - | | | + | + |
| MARCOS Y PUER | _ | | * | Н | | | _ | | | | | | ENSORES | | | | |
| MARCOS Y PUER | | - | | Н | \vdash | ESCALERAS EXTERIORES ASCENSORES CUBIERTA COPA DE AGUA O ESTANQUE | | | | | | | - | + | | | |
| MARCOS Y VENT | | LINONE | _ | Н | \vdash | ALEROS | _ | | + | CUFA | | | and the same of th | | | | + |
| SI - PRESENTA D | | BLE; NO | -NO | PRE | SEN | | BLE | | - | _ | | | | | | _ | _ |
| 5 DAÑOS AP | RECIAD | OS INS | TAL | AC | ONI | ES. | | | | | | | | | | | |
| INST. REDES | SI | NO | T | | | SI | NO | ARTEFAC | ros | T | SI | NO | Т | | SI | T | NO |
| AGUA POTABLE | | | ELE | CTF | BICID | AD | | SANITARIO | 75 | | | | o | ALEFONT | | \top | |
| ALCANTARILL. | | | GA | s | | | | ELECTRICO | RICOS | | | | 141 | CHOS GAS | | + | |
| 6 HABITABIL | IDAD | | | | | | | - | | _ | | _ | | | | | |
| HABITABLE | JUAU. | | NO | MAI | HTA | BLE | | COLAPSO | DAD | CIAL | | | 100 | DLAPSO TOTAL | _ | | _ |
| HADITADLE | | - | NO | HAL | *** | BLE | | CODAFSO | FAR | LIAL | _ | | v | JUAP SU TUTA | | _ | _ |
| 7 OTRAS CO | NSIDER | ACION | ES L | J OF | BSE | RVACIONES | 5. | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| NOMBRE REVISO | R | | | | | | | NOMBRE P | ROF | IETA | OUN | | | | | | |
| FIRMA | | | | | | | | FIRMA | | | | | | | | | |

▶ Damage register symbol



Damaged building inventory



General Information

- 1. Location
- 2. Year of construction
- 3. Number of stories
- 4. Structural system
- 5. Main occupancy

Damage information

- 1. Level of damage
- 2. Damage report
- 3. Photos
- 4. Video

Documents and professionals

- 1. Documents
 - Soil mechanics
 - Structural drawings
 - Calculation report
 - Structural model


 - Architectural drawings
 - Construction documents
- 2. Project Managers
 - Real Estate
 - Construction company
 - Engineering company
 - Architect
 - Structural reviewer



Damaged RC walls Experimental and modeling



RC Wall Test




Force-Deformation relationship












W1 W2

W3


2010 EQ

A203






Concepcion buildings location 7724 77






- Orientation of buildings
- Plan and height irregularities
- Structural detailing and constructive errors
- Multi-story damage
- Sources of energy dissipation

Orientation of buildings






Main damage in the East-West direction and in the shortest axis of the structure



Severe damage in building TL

Severe damage in building AH






East elevation of TO




Light damage 🔲 Moderate damage 📒 Severe damage



TO: Axis 1A


Damage level representation





Irregularities

Irregularities in plan and height had an important role in the observed damage

• The most irregular buildings (AA and TO) are the most damaged ones.








Schematic plan TO

Irregularities "Flag-shaped" walls






AA Building




AH Building


Common Irregularities





Irregularities
Coupling beams in walls
















Detailing & brittleness

Thin walls with high axial load were unable to confine the concrete core

- Spalling of the concrete cover
- Buckling of longitudinal reinforcement
- Brittle collapse of the wall









AH

CM

PdR



Serious detailing and construction issues are observed in the inspected buildings (specially in Torre O'Higgins)

- Bad anchor between beam-wall joints
- Cut stirrups and outside the confined area
- Absence of confinement in the wall boundaries



Lack of stirrups




Reinforcement outside the confined Typical confinement detail area






There is damage propagation between floors



CM building: propagation of damage between stories




There is damage propagation between elements



CM: propagation of damage between elements



Damage propagation between stories and elements



PdR building: damage propagation

Energy dissipation elements

Since 1985 the buildings have changed continuously:

- Less wall thickness, less wall densities, bigger axial loads and elimination of lintels
- An important source of energy dissipation is eliminated → Modify R factors!





AH



PP

PP

Value of the second of the

RdT

V
Non-structural elements intact



A design review was made (using chilean code NCh433) for the 4 most damaged buildings:

Utilization factor =
$$FU = \frac{Demand}{Strength}$$

FU < 1



Satisfactory design

1 < *FU* < 1.25



Slightly deficient elements

1.25 < *FU* < 1.5



Moderately deficient elements

FU > 1.5



Severely deficient elements

Walls:

- Shear
- Axial-flexural

Beams:


- Shear
- Positive Moment
- Negative Moment

Drifts y displacements:

- Drifts in CM < 2‰
- Maximum drifts < 1‰ drift CM




Walls in shear (~ 1000 elements per building)






Design review v/s observed damage:



Plaza del Río building: FU in 1st story

Plaza del Río building: Damage in 1st story

Stabilization process EM Building







Stabilization process EM Building













Stabilization process TO Building











Stabilization process TO Building















Stabilization process

Repair, Stabilization and demolition of buildings



TO building: Temporary stabilization



EXAMPLE: PERFORMANCE OF SEISMICALLY PROTECTED BUILDINGS












Titanium tower Hysteretic damping









Social behaviors





Survey of socioeconomic characterization added a mental health module and conducted a survey shortly after 27F


Módulo Impacto Psicosocial Personas de 18 años y más, presentes al momento de la encuesta, y que sean capaces de responder por si solos la encuesta Indique la frecuencia y la intensidad (gravedad) según la tabla 1, Ha tenido alguna vez imágenes, recuerdos o pensamientos dolorosos del terremoto/tsunami. 10. Se ha sentido distante o alejado de la gente 2. Ha tenido alguna vez pesadillas sobre el terremoto/tsunami 11. Ha sido incapaz de tener sentimientos de tristeza o de afecto 12. Ha tenido dificultad para imaginar una vida larga y cumplir sus objetivos 3. Ha sentido que el terremoto/tsunami estaba ocurriendo de nuevo, como si lo estuviera 13. Ha tenido dificultad para iniciar o mantener el sueño 4. Hay cosas que se lo han hecho recordar 14. Ha estado irritable o ha tenido accesos de ira 15. Ha tenido dificultades para concentrarse 5. Ha tenido sensaciones físicas por recuerdos del terremoto/tsunami (como transpiración, temblores, palpitaciones, mareos, náuseas o diarrea) 16. Se ha sentido nervioso, fácilmente distraido, o como "en guardia" 6. Ha estado evitando pensamientos o sentimientos sobre el terremoto/tsunami 17. Ha estado nervioso o se ha asustado fácilmente 7. Ha estado evitando hacer cosas o estar en situaciones que le recordaran el terremoto/tsunami 8. Ha sido incapaz de recordar partes importantes del terremoto/tsunami Intensidad Frecuencia (Gravedad) 9. Ha tenido dificultad para disfrutar de las cosas 0 = nunca 0 = nada 1 = leve 1 = a veces 2 = 2-3 veces 2 = moderada 3 = 4-6 veces 3 = marcada 4 = a diario 4 = extrema 5g 6f 6g 7f 7g 8f 8g 9f 9g 10f 10g 11f 11g 12f 12g 13f 13g 14f 14g 15f 15g

PTSD in caregivers of preschool children


| Comuna | TEPT (%) |
|--------------|----------|
| Antofagasta | 2,6 |
| Tocopilla | 0,0 |
| Montepatria | 0,0 |
| La Serena | 3,7 |
| Coquimbo | 2,7 |
| Los Andes | 8,3 |
| Valparaíso | 7,4 |
| Lampa | 8,8 |
| Quilicura | 9,9 |
| La Florida | 3,1 |
| Puente Alto | 14,6 |
| San Bernardo | 16,5 |
| Rengo | 7,8 |
| Collipulli | 9,8 |
| Vilcún | 2,5 |
| Río Bueno | 5,1 |
| Osorno | 3,6 |
| Puerto Montt | 0,0 |
| Total | 7,3 |

Bedregal et al., 2013

Social Vulnerability index



Economic Losses as %GDP







▶ What forms of data were collected after the earthquake?

Different data at different depths, from ground deformations and motion, tsunami effects, structural and non structural damage in structures, such as buildings, ports, schools, lifelines, etc., and social response

► Have any relationships between the different forms of data been explored?

- Building damage vs. soft soil conditions
- Types of building damage vs. focal distance
- Directivity and orientation in building response
- Loss of functionality vs. non-structural components
- Tsunami effect vs. fault-slip distribution
- Socio-economic status vs. earthquake resilience



► What organizations were involved in collecting data and for what purpose?

Ministry's, regional and communal governments, insurance, real-estate, construction and design companies, researchers, communities, individuals

► What barriers are there to sharing data across different organizations?

- Have possible personal and company liabilities
- Take scientific and professional advantage of seismic records and ground motion data in general
- Risk company and professional reputation
- Lose competitiveness relative to competition (e.g., ports)



▶ How were the data collected?

- Physical observations done by different agents on the physical environment: accelerometers, seismometers, GPS, InSAR, LiDAR, SASW, and DCPT
- Physical observations of the built environment: site visits and technical inspections
- Psycho-social observations of agents and communities: surveys on people and communities
- Operational observations of the integrated system: changes in ONEMI and new seismic codes (and decrees)

▶ What data were lost?

Earthquake data is almost always collected by someone, so the problem is more that of sharing the data and making it available for research purposes



- ► Lack of a standard instrument for inspections led to different assessments for the same structure
- ▶ Lack of planning resulted in duplication of efforts
- ▶ Large disparity in knowledge and technical criteria of the evaluators in building inspections
- Private companies could not disclose data to the public
- ▶ No consolidated information system, making it very difficult to share information among professionals and researchers
- ➤ Very few institutions were prepared with protocols and equipment to go out to inspect a large number of structures



- Scope of the post-earthquake inspection should be first clearly defined (emergency, operation recovery, or reconstruction)
- Data should be
 - Available for decision makers, authorities, and relevant stakeholders
 - Obtained by standardized procedures
 - Correct and unbiased for use in later research purposes to improve design standards and construction practices
 - Obtained only once to avoid unnecessary duplications and trouble to people
 - Mounted on a central platform that enables classifying and sharing it



- ▶ Define an "NDA" for data recollection and research purposes
- Use communication technologies exhaustively in collecting data
- ▶ Universities and research centers should develop and implement these protocols



10NCEE Special Session, Anchorage, Alaska The Canterbury Earthquake Sequence: Lessons for Response and Recovery

July 23, 2014

Canterbury Earthquakes Sequence Building Damage, Data Collection, & Access

Andrew King – GNS Science

Peter Wood – NZSEE

Mike Stannard – MBIE

Stefano Pampanin – University of Canterbury

John Hare – Holmes Consulting Group

David Johnston - GNS Science

Introduction — Andrew King GNS Science Topic

Scene setting – Regulation & Overview

Seismology & ground motions

Ground deformations

Building Safety Evaluations

Building Condition Evaluations

> Insurance and Losses

Socio-Economic Implications

> Discussion

Mike Stannard

Andrew King

Peter Wood

Mike & Andrew

John Hare &

Stefano Pampinin


Andrew King

David Johnson

Everyone

Regulatory and Overview

Mike Stannard, Chief Engineer, MBIE



Canterbury Earthquake Sequence

4 Sept 2010, 22 Feb, 13 June, 23 Dec 2011

Fatalities – 185

Cost – Estimates up to \$NZ40 billion ≈ 20% GDP, (\$US35B)


Insurance – one of biggest insurance claim events in world, > 450k residential claims for 170k houses

Christchurch CBD – 1700 commercial buildings demolished

Government priority – rebuild Christchurch, implement Canterbury Earthquakes Royal Commission recommendations.

Events – > 14,000 shakes, including M7.2 Sep 2010, M6.3 Feb 2011







Issues

Existing regulatory framework – Building Act/Code not addressing disaster response or recovery

- -No legislative authorisation for building usability evaluation (safety)
- -Repair after earthquake unclear


Response

Legislation – Canterbury Earthquake Recovery Act

Short term changes to Building Act (dangerous buildings to include earthquake hazard)

- -Proposed changes to Act to include rapid building usability assessment (tagging)
- -Issue guidance


National Building Act and Building Code



| Issues | Response |
|--|---|
| Placards – damage evaluation, public perception buildings safe | Develop DEE process for residual capacity assessment |
| Seismic hazard changed as a result of earthquake | Engineers and seismologists working together to consider building performance and short and long term hazard – raise hazard factor 35% |
| Changed public perception of risk elsewhere | Proposed amendment to earthquake-prone building legislation: -Balance cost and risk; -Different perceptions and preparedness to pay across NZ; -Affordability for rural towns, demolition; -Market/insurer drivers for strengthening. |
| Clarity of objectives for building structural performance requirements | Proposals for review of Building Code to introduce tolerable impacts for various limit states |

Motion Records Andrew King GNS Science

- Purpose: Locate and quantify event signature (Mag, Depth, Rupture characteristics) for haz. evaluation & future seismicity projections; Evaluate within-event shaking characteristics
- Collected using
 - seismographs with backbone network (Sat-phone link)
 - supplemented by rapid-response instruments (aftershock) Cell-phone link + on-site storage)
- Collected by Geonet (GNS) also U of Canterbury; later by some overseas research teams
- ▶ Data Stored & accessible via Geonet Open Access
- Missing: detailed instrumental site conditions
- Improvements: greater network density; forward predictive capacity; liquefaction trigger conditions



Revised Forecast for Canterbury region (whole of Canterbury plains) starting July 1st, 2012

| 5 years | | | 20 years | | | |
|-----------------|-------------------|-------|-------------|-------------------|-------|-------------|
| EQ Magnitude | Average Number | Range | Probability | Average Number | Range | Probability |
| 5.0-5.4 | 4.6 | 1-9 | 99% | 11.1 | 5-8 | 100% |
| 5.5-5.9 | 1.4 | 0-4 | 75% | 3.3 | 0-7 | 97% |
| 6.0-6.4 | 0.4 | 0-2 | 34% | 1.0 | 0-3 | 64% |
| 6.5-6.9 | 0.1 | 0-1 | 11% | 0.3 | 0-2 | 27% |
| 7.0+ | 0.04 | 0-1 | 4% | 0.1 | 0-1 | 13% |

Source: GNS "50-year" Model revised following recent international expert peer review and using all data up to Jan 25th, 2012.

1 year hazard forecast for Canterbury region currently remains above Wellington region

| Magnitude | Canterbury starting May 28 th 2012 (high rates now declining rapidly) | Wellington starting Dec 15 th 2011 (fairly stable numbers as no significant activity at present) |
|-----------|--|---|
| 5.0-5.4 | 75% | 40% |
| 5.5-5.9 | 33% | 13% |
| 6.0-6.4 | 10% | 3.6% |
| 6.5-6.9 | 3% for city | 1.0% |
| 7.0+ | 1% | 0.3% |

Source: GNS "50-year" model revised following recent international expert peer review and using all data up to Jan 25th, 2012.

Rapid Impact Assessments Peter Wood NZSEE

- Intended use: Response & Recovery planning; Future use (liquefaction; landslide & boulder roll risk projections); Foundation and infrastructure design requirements
- Collected using: Low-level Oblique imagery (NZDF, CDEM, GNS, Media), Satellite dlnSAR, High Resolution vertical aerial imagery, LiDAR, Precise GPS and Precise levelling field survey of benchmarks
- > Collected by and for.
 - MCDEM Response and recovery planning
 - EQC Insurance claims settlement;
 - Consultants building and utility repair strategy;
 - Universities liquefaction mapping;
 - Researcher/Insurer cause of damage

Rapid Impact Assessments (2)

- Data storage, retrieval, and sharing policies variable still difficult! Private and confidential issues
- > Clearing Houses (NEHRP model)
 - shared rapid impact assessments: both physical and virtual;
 - The physical meetingscontinue, nearly four years after initiation.

> Missing:


- Unique Building Identification;
- Pre-event High-resolution digital elevation model (DEM);
- Full appreciation of the relationships between ground, foundation, and structure.

> Improvements:


- Common and standardised ways of describing buildings, building elements, foundations, ground, and then - damage.
- Data management and sharing policies
- Interoperability




Aerial photography - Liquefaction (NZAM)




Cosmo SKYMed coherence



Cosmo SKYMed (X-band SAR)




Airborne LiDAR differencing (2003-2011)




LiDAR data courtesy AAM (2003) and NZAM (2011)

Vertical displacement (mm)

modelled from GPS observations and 2003-2011 LiDAR






LiDAR change detection

Collapsed spire New construction and rubble Cathedral Partially Collapsed building

New Zealand Post Earthquake Damage Data Collection Experience

Canterbury Geotechnical database







Image correlation processing by Sebastien Leprince, Caltech

New Zealand Post Earthquake Damage Data Collection Experience



Building Safety Evaluation MS AK

- Purpose: Emergency phase screening of buildings that pose a unacceptable risk to occupants, the public or neighbouring properties
- Conducted using: Paper-based templates and 2009 guidance handbooks (Level 1 and Level 2) (based on ATC-20)
- ➤ Conducted for. Territorial Authority Building Control via the CDEM Controller using co-opted Structural Engineers and Building Officials from around NZ.
- > Missing:
 - Details of building history (prior to inspection) either asbuilt or since last inspection.
 - Adequate trained/qualified engineers to undertake evaluation (many problems with highly variable results)

Building Safety Evaluation (2)

- Data storage: manually transferred data from paper to electronic database
 - procedure difficult and inaccurate particularly with multiple events requiring multiple inspections; didn't translate to timely map production
- ➤ Data retrieval: Council consider open available on application as with building permit data; other departments are more restrictive (privacy issues!)
- > Future improvements:
 - New guidance notes and training in preparation for Building Usability, including replacing 'green' (implies safe) placard with 'white' (implies inspected);
- New Zealand Post Earthquake Damage Data Collection Experience




Building <u>Damage</u> Evaluation (JH SP)

- ➤ Purpose: To ensure that significant damage to buildings is identified and understood to inform building repair and to inform ongoing occupancy of building.
- Conducted using: As-built plans and detailed on-site inspection (including invasive investigation if required)
- Conducted for: Building owners under direction from Government (CERA) by Consulting engineers (structural, material and Geotech)
- > Missing: Detail as to:
 - cause or location of damage
 - basis upon which residual building capacity established
- Issues: Consistency of engineering evaluations, no uniformity of damage state and criticality


Standardised Report Form

- > Excel spreadsheet
 - Most common platform for engineers
- Used drop-down lists where thought possible and practical
- > Limited free-field descriptions
- Included simple IEP capacity calculator voluntary use
- > Next time:
 - Add simple damage states
 - Even more drop-downs
 - Different platform?



Building <u>Damage</u> Evaluation (2)

- Data storage: Electonic reports (pdf) and Detailed Engineering Evaluation (DEE) summary spreadsheets submitted to CERA; stored in CERA database until 'approved' by CERA then passed to Council Building Reports
- Data retrieval: Council considers their building records open to public as with building permit data; other departments are more restrictive (privacy issues!)
- > Future improvements:
 - Pre-event assessment being undertaken as part of Earthquake Prone Building register evaluation
 - Data retrieval to hand-held inspection tablet now possible
 - Use of common fields for both inspection and loss projection





BUILDING IDENTITY

Draft Report on Pre-1970s Reinforced Concrete Buildings in Christchurch CBD
Draft 22nd March 2011 -NOT FOR PUBLIC RELEASE-

| Building No | 70s-XX |
|-----------------------------------|---|
| Building Name | SBS Tower |
| Address | 128 Worcester St (180 Manchester St) |
| Zone | 8 |
| Storeys Above Ground Level | 9 |
| Approximate Gross Floor Area (m2) | ~900 |
| Year Built | 1964-65 |
| Type of Construction | RC Coupled-Walls (EW/NS), Steel Frame (EW – north end) |
| Occupancy Type | Commercial Office |



North-West View




Photos of SBS Building under construction in the 1960s.






Draft Report on Pre-1970s Reinforced Concrete Buildings in Christchurch CBD
Draft 22nd March 2011 -NOT FOR PUBLIC RELEASE-

Typical exterior damage photos (4 max)







Detail 3: Minimal damage at the facade precast panels (except for local crushing at the slab-window region).



Draft Report on Pre-1970s Reinforced Concrete Buildings in Christchurch CBD
Draft 22nd March 2011 -NOT FOR PUBLIC RELEASE-

In terior damage photos

Detail 4: Interior view of the damaged coupling beam at the West elevation walls. Diagonal and horizontal deformed reinforcements were observed. No confining vertical ties can be found in the spalled locations.







Detail 5: Interior view of the

Detail 5: 10-20mm cracking on the RC slab along the internal shear walls (E-W direction).



Detail 8: Concrete spalling at the pin support at the bottom landing of the staircases. Damage was more severe at the upper levels.



Detail 7: Damaged coupling beam at the internal coupled-walls (East-West direction).



Detail 9: Movement at the top landing of the staircases. Gaps of 10-50mm were observed





Draft Report on Pre-1970s Reinforced Concrete Buildings in Christchurch CBD
Draft 10th March 2011 -NOT FOR PUBLIC RELEASE-


| 70s-302 |
|---|
| Securities House |
| 221 Gloucester |
| 3a |
| 8 |
| ~330 |
| 1970-1979 |
| Concrete Frames with Concrete Core walls |
| Commercial Office |
| |








Building Plans







Foundation System

The foundation system is formed by isolated footings for columns and foundation (coarse) beams for walls, attached to the ground using piles (size and depth not specified in available drawings). Footings are attached to each other using slender foundation beams. Wider beams were used on axis 4, whereas thin beams were used to attach the outer ends of the C-shaped wall to the west side columns.




Figure 2: Foundation system. Left: foundation pan view; right: course beam details and piling information

Structural System

The structural earthquake resistant system is conformed by perimeter RC frames and RC structural core C-shaped and L-shaped walls. Gravity loads in the central area are resisted by columns with capitals jointed continuously to the cast in situ floor slab. The C-shaped wall is used as support for stairs together with the L-shaped thin wall, as shown in details. Note the interior RC L-shaped wall has got a single mesh inside, as shown in details. Stairs are jointed at each floor level to the structural walls using cast in situ floor slabs. Floor system consists in cast in situ RC slabs 5 in. thick (130mm).






Figure 3: Structural System. Left: typical plan view; right: Column, beam and slab details







Figure 4: Structural System. Left: C-shaped wall details; right: stairs connection details


7


Damaged buildings (22 Feb 2011)























Building Loss – Consequences (AK SP)

- Purpose: determination of a settlement claim consistent with the specific insurance policy.
- Collected using: Electronic tablet and data collection tools; paper forms.
- Collected By: Insurance loss adjusters and their technical advisors
- Data Storage: within each the respective private insurers, usually in electronic form
- Data access policy: Privacy prevents any (or nearly any) disclosure; Special arrangements are required and possible in some cases where trust and security can be assured.

Residential assessments - EQC

- ➢ Globaly unique EQC role in providing cover for land damage – EQC claims settlement not just about buildings but also the associated land;
- Understanding land changes and likely future ground performance critical input to recovery – transparency of this information essential for international confidence and community engagement;
- Importance of geotechnical information for the recovery drove new approaches to information management and private-public sharing

Residential assessments – EQC 2

The Canterbury Earthquake Sequence (CES) necessitated multiple recollection of all data (including aerial photography & LiDAR) after each significant event.

Some complexities:

- ➤ Overlapping interests in building safety and loss/damage evaluations, particularly for multi-unit dwellings;
- ➤ The nature of the CES and the legislation generated multiple claims for the same dwelling necessitated multiple assessments for a single building, over 750,000 assessments undertaken by EQC in association with the CES.

Loss information is currently being shared (under NDAs) with reinsurers, researchers, and loss modellers.

Building Loss – Consequences (2)

- > Missing:
 - Description of damage (and in many cases of the building since the focus is on the remedy)
 - Descriptions of the cause (shaking or deformation)
- Data retrieval: possible (with 'special arrangements' but complicated (particularly for large claims with multiple insurance layers
- > Future improvements:
 - Access to loss data by regulation if necessary.
 - More consistent (standardised) insurance policies that appropriately assign risk.

Social Impact and Injuries (DJ)

- Purpose: to gain an appreciation of the factors that influence social response and community resilience
- > Collected using: Surveys, direct discussion and census
- Collected for: Stats NZ, ACC; MSD; CERA; Councils, DHBs
- Missing: Community wellbeing, transient populations, linking meta-data
- > Data Storage: within many organizations
- > Data Retrieval: Stats NZ Portal, data sharing protocols
- Future Improvements: date sharing protocols between agencies

Nat Hazards DOI 10.1007/s11069-014-1094-7

ORIGINAL PAPER

The 2010/2011 Canterbury earthquakes: context and cause of injury

David Johnston · Sarah Standring · Kevin Ronan · Michael Lindell · Thomas Wilson · Jim Cousins · Emma Aldridge · Michael Warne Ardagh · Joanne Margaret Deely · Steven Jensen · Thomas Kirsch · Richard Bissell

Received: 10 September 2013/Accepted: 13 February 2014

Springer Science+Business Media Dordrecht 2014

Abstract The aim of this study was to investigate causes of injury during the 2010/2011 Canterbury earthquakes. Data on patients injured during the Darfield (4 September 2010) and Christchurch (22 February 2011) earthquakes were sourced from the New Zealand Accident Compensation Corporation. The total injury burden was analyzed for demography, context of injury, causes of injury, and injury type. Injury context was classified as direct (shaking of the primary earthquake or aftershocks causing unavoidable injuries), action (movement of person during the primary earthquake or aftershocks causing potentially avoidable injuries), and secondary (cause of injury after shaking ceased). Nine categories of injury cause were identified. Three times as many people were injured in the Christchurch earthquake as in the Darfield earthquake (7,171 vs. 2,256). The primary

D. Johnsto

Joint Centre for Disaster Research, T20 Wellington Campus, Massey University, 94 Tasman Street, Wellington, New Zealand

D. Johnston (E3) Joint Centre for Disaster Research, GNS Science/Massey University, P.O. Box 30 368, Lower Hutt 5010, New Zealand e-mail: david johnston@gns.cn.nz

S. Standring E. Aldridge University of Auckland, Auckland, New Zealand

K. Ronan Central Queensland University, Rockhampton, QLD, Australia

Texas A&M University, College Station, TX, USA

University of Canterbury, Christchurch, New Zealand

J. Cousins GNS Science, Wellington, New Zealand

Published online: 27 February 2014



Relative risk by gender and age

| | Christchurch | Darfield | | | | Christchurch | | |
|--------|--------------|--------------------------|---------------------------|------|-------------------------|--------------|---------------------------|------|
| | Population | Total Injuries (n) | Injuries per 10,000 | Risk | Total injurio (n) | | Injuries per 10,000 | Risk |
| Gender | | | | | | | | |
| Male | 168,423 | 803 | 47.7 | 1.0 | 252 | 5 | 149.9 | 1.0 |
| Female | 180,012 | 1453 | 80.7 | 1.7 | 464 | 6 | 258.1 | 1.7 |






Relative risk by gender and age


| | Christchurch | Darfield | | | Christchurch | | |
|---------|--------------|-------------------|------------------------|------------------|----------------|---------------------------|------------------|
| | Population | Total Injuries | Injuries per 10,000 | Relative risk | Total injuries | Injuries per 10,000 | Relative risk |
| Under 5 | 21,477 | 15 | 7 | 1 | 66 | 30.7 | 1 |
| 5-9 | 21,396 | 12 | 5.6 | 0.8 | 41 | 19.2 | 0.6 |
| 10-14 | 22,797 | 31 | 13.6 | 1.9 | 86 | 37.7 | 1.2 |
| 15-19 | 25,875 | 62 | 24 | 3.4 | 241 | 93.1 | 3 |
| 20-24 | 27,597 | 68 | 24.6 | 3.5 | 359 | 130.1 | 4.2 |
| 25-29 | 22,506 | 81 | 36 | 5.2 | 371 | 164.8 | 5.4 |
| 30-34 | 24,858 | 145 | 58.3 | 8.4 | 433 | 174.2 | 5.7 |
| 35-39 | 26,310 | 224 | 85.1 | 12.2 | 636 | 241.7 | 7.9 |
| 40-44 | 26,091 | 240 | 92 | 13.2 | 674 | 258.3 | 8.4 |
| 45-49 | 25,008 | 304 | 121.6 | 17.4 | 784 | 313.5 | 10.2 |
| 50-54 | 21,927 | 274 | 125 | 17.9 | 821 | 374.4 | 12.2 |
| 55-59 | 20,313 | 197 | 97 | 13.9 | 644 | 317 | 10.3 |
| 60-64 | 15,084 | 175 | 116 | 16.6 | 554 | 367.3 | 12 |
| 65+ | 47,196 | 428 | 90.7 | 13 | 1461 | 309.6 | 10.1 |


New Zealand Post Earthquake Damage Data Collection Experience

Context of injury

| | Darfield | Christchurch | | |
|--------------------------------|-------------|--------------|--|--|
| | n (%) | n (%) | | |
| Primary Immediate | 377 (16.7) | 3129 (43.6) | | |
| Primary Action | 1025 (45.4) | 1293 (18.0) | | |
| Primary Unknown | 50 (2.2) | 574 (8.0) | | |
| Secondary (including clean-up) | 499 (22.1) | 1881 (26.2) | | |
| Aftershock Immediate | 165 (7.3) | 172 (2.4) | | |
| Aftershock Action | 134 (5.9) | 103 (1.4) | | |
| Aftershock Unknown | 6 (0.3) | 19 (0.3) | | |







Christchurch quake- first 24 hours Accident location and external cause of injury

| | Total injuries | Male | Female | Ratio |
|------------------------------|----------------|------------|------------|-------|
| | n | n (%) | n (%) | F:M |
| Accident Scene | | | | |
| Home | 3392 | 1002 (30%) | 2390 (70%) | 2.39 |
| Commercial/Service | 1549 | 444 (29%) | 1105 (71%) | 2.49 |
| Location | | | | |
| Road/Street | 399 | 143 (36%) | 256 (64%) | 1.79 |
| Industrial Place | 228 | 112 (49%) | 116 (51%) | 1.03 |
| School | 140 | 34 (24%) | 106 (76%) | 3.12 |
| Place of Recreation or Sport | : 80 | 21 (26%) | 59 (74%) | 2.81 |
| Place of Medical Treatment | 45 | 8 (18%) | 37 (82%) | 4.63 |
| Other/Not Obtainable | 826 | 268 (32%) | 558 (68%) | 2.08 |

- ➤ Gender differences were significant and causes are varied. Further work is need to explain them.
- ➤ In general, improved building codes, strengthening buildings and securing fittings will reduce future earthquake deaths and injuries.
- ➤ However, the high rate of action injuries earthquake suggests that further education is needed to promote appropriate actions during and after earthquakes.



9. Suggest possible data collection protocols?

- Seek consensus and standards for describing earthquake damage to ground and to buildings, to aid interoperability;
- Clarify what data can be shared and what is restricted because of privacy and confidentiality reasons – support with relevant data structures;
- Seek arrangements that encourage Collaboration versus Competition

10NCEE Special Session, Anchorage, Alaska The Canterbury Earthquake Sequence: Lessons for Response and Recovery

July 23, 2014

Canterbury Earthquakes Sequence Building Damage, Data Collection, & Access

Andrew King – GNS Science

Peter Wood – NZSEE

Mike Stannard – MBIE

Stefano Pampanin – University of Canterbury

John Hare – Holmes Consulting Group

David Johnston – GNS Science



Toshimi Kabeyasawa, University of Tokyo Masaki Maeda, Tohoku University Koichi Kusunoki, University of Tokyo Toshikazu Kabeyasawa, National Institute for Land and Infrastructure Management Tomohisa Mukai, Building Research Institute Satoshi Tanaka, Tokoha University Susumu Kono, Tokyo Institute of Technology



Japan experience

Focused on damages to reinforced buildings

Presentations (70min)

Toshimi Kabeyasawa, AIJ disaster committee and damage survey Masaki Maeda, Damage level evaluation and 3.11 Tohoku experience Koichi Kusunoki, Non-structural damages, Survey organizations Toshikazu Kabeyasawa, Tsunami disaster Tomohisa Mukai, Functional use of buildings Satoshi Tanaka, Insurances and housing impacts Susumu Kono, Possible future improvement and discussions Discussions and questions (20min)

Post-Earthquake Data Collection Workshop Anchorage, July 20-21, 2014


AIJ Disaster Committee and Post-Earthquake Organized Survey

- 1. AIJ disaster committee and survey on damage to buildings
- 2. Collected and lost data on the damages to school buildings in Fukushima by the East-Japan Earthquake, Mar 11, 2011

Toshimi Kabeyasawa 壁谷澤 寿海 Earthquake Research Institute The University of Tokyo



Reconnaissance framework in Architectural Institute of Japan



780 school buildings were surveyed in detail: 400 RC, 200 S, 180 other educational facilities: e.g. 46 requests and 9 severely damaged from 890 high-school buildings in Fukushima prefecture

Collected and lost data

Collected data:

Damage evaluation: 780 damaged school buildings were inspected by AIJ, Damage levels were evaluated for above requested from local governments to AIJ through MEXT

Recovery: The damage levels are to be used for recovery procedure **Seismic evaluation:** The seismic indices(Is) had been evaluated for most of the old school buildings (before 1981)

Retrofit: Some of the old buildings had been retrofitted

Ground motions: Free field earthquake motions were recorded at 2000 K-net stations in 20km mesh and 2000 others

Lost data:

Damage statistics: Inventory data including minor/no damages and complete damage rate statistics are insufficient

Private Info Protection Law: Damage survey on private buildings became basically difficult after 2006

Input motions to buildings: Inputs and responses were recorded at some buildings, but very few in cases with severe damages


Post-earthquake response to damages of buildings

Major earthquake

Quick damage inspection

Damage rate evaluation

Rehabilitation




Rehabilitation procedure for RC school buildings

Damage Rate Evaluation


Rehabilitation Plan and Cost Estimation

Rehabilitation



Rehabilitation procedure for RC school buildings

Target performance for with moderate/minor damage



Seismic Index after rehabilitation shall be planned as:

$$I_{S(plan)}=DI_{S}+\Delta I_{S} \ge I_{SO}$$

I_{S(plan)}=: Seismic Index for the planned structure

DIs: Residual Seismic Index for damaged structure

 $\Delta I_{\rm S}$: Incremental Seismic Index with repair and strengthening

Iso: Seismic Index required for school (≥ 0.7 or 0.75)


3.11 2011 East Japan Earthquake

- Tsunami
- **✓** Nuclear Power Plant
- ✓ Wide affected area due to high magnitude




- **♦ Difficulty in reconnaissance**
- **♦ Delayed and long-term recovery**


Observed strong motions in 2011 East Japan EQ




Frequency components of far/near field motions (2011 East Japan/1995 Kobe)



Acceleration and Velocity Spectra (Fukushima, FKS003)







Reconstruction on 2012.6.23



In case of private schools, recovery is relatively fast, and demolish and reconstruction was completed until 15 months after.

No. 4 Building of Public F-High School (F-cities, RC3, 1961-1963)





Reconstruction and temporary school building (April 23, 2014)




The reconstruction is still under procedure after three years in case of this public high school, my old school in Fukushima.

Damage statistics for RC bldgs of public highschools in Fukushima





Relations between seismic performance indices Is and residual seismic capacity R



Report from Japan Damage level evaluation and 3.11 Tohoku experience

Masaki MAEDA Tohoku University




Miyagi prefecture and 3.11 EQ

2011/03/11 14:46(JST)







20

Q1: What forms of data were collected after the earthquake?

- Seismic capacity evaluation
- Damage level and residual capacity

Q5: How were the data collected?

- Manually with specific forms: damage
- Instruments: seismic motions



Post-EQ inspection and rehabilitation

Occurrence of EQ



Quick inspection

Conducted by local government

Inspector = structural engineers & architects



Damage evaluation and rehabilitation

Conducted by owner

Inspector = structural engineers, researchers

Quick inspection

- Conducted by local government
 - Lecture and training in all the prefectures after 1995 Kobe EQ.
 - Over 100,000 inspectors in Japan, 2000 in Miyagi pref.





Check sheet for quick inspection

- Summary of the building
- ✓ Name, Address, Usage
- Structural type/system
- ✓ No. of story
- Hazard on structure (Rank A, B, C)
- Most severe damage to columns
- Ground, base and surroundings
- Hazard on falling objects
- ✓ Window glass
- Exterior finishing board
- ✓ Signboard, etc.



#合料定(調査の1で危険と判定された場合は危険、それ以外は調査の2と3の大きい方の危険度でき まする。)
1. 調査済 (網) 2. 要注意 (質) ③ 危険 (帯)

コメント (構造躯体等が危険か、落下物等が危険かなどを記入する。)


こが育と37倍の 在に被暑 た、危険。

及の 厚受 はイエトげ 初のはく難、幾下の可能性 石川、危険。

コメントは相定ステッカーの注記と同じとする。

| | | | | | | 険度判定調査表 | | | |
|--|--------------------------|------------------------|-------------------|----------------|-----------------|-----------------------|------------|--|--|
| 16 号 00- | | | | | | , 满去同数 | 00-04 | | |
| · 者氏名(都通府) | %/No) | 00 | | \mathcal{H} | | | | | |
| 築物概要 | | ΔΔ. | | · A | <u>#</u> /_AA-9 | 8/6 | 建築物業 | | |
| 1 建蒸物名称 | | 集合1 | <u> </u> | | 建築物番号 | 444 | 444 | | |
| 2 建基物所在地 | JAPP! | DOOR A | 107/-2- | | 住宅地回整理書具 | | 在北京 | | |
| 3 建築物用途 1.戸建て専用住宅 2.長屋住宅 〇共同住宅 4.終用住宅 5.店舗 〇事務所 ススメ | | | | | | | | | |
| 7. 旅館・ホテル 8. 庁舎等公共被設 9. 病院・診療所 10. 保育所 11. 工場 3 12. 食庫 13. 学校 14. 体育館 15. 劇場、張敷場等 16. その他 () | | | | | | | | | |
| A MARINE DE LA DESCRIPTION DE LA CONTRACTION DEL CONTRACTION DE LA CONTRACTION DE LA CONTRACTION DE LA CONTRACTION DEL CONTRACTION DE LA C | | | | | | | | | |
| | | 鉄筋コンタ | | | ○混合構造 (」) | RC) & (RC) | 地上 /O | | |
| | | | 下 / 階 | | | | 7 40 | | |
| 6 建築物規模 | 1階寸 | 法 約7_ | 40 m×1 | _25 | m. | | 1 25 | | |
| 開査 調査方法: | | | | | | | 2076 | | |
| 1 一見して危険 | と判定さ | れる。(政 | 高する場合は | ○を付け | 危険と料定し調査 | を終了し総合判定へ) | 2 | | |
| 1.建築物全体又 | は一部の | 原域・高階 | | 2. 施器 | Bの著しい破壊、L | 記構造との著しいずれ |] | | |
| 3.建築物全体又 | u - 新の | 表しい傾斜 | | 4.50 | D## (|) | 1 - | | |
| | | | | | - 20 1 | | , — | | |
| 2 隣接建築物・ | 陶业场等 | E等及び構造 | | | 8ランタ . | C7>2 | 1 | | |
| E OMBUREUS | - MARKET | | Aラン 1.無し | 9 | Oan | - (1) | 809(1) | | |
| (1) の有無 | .v/m:+so | 10 | 1.50 | | U | | 0 2 | | |
| ②保証性事物・ る危険 | 周辺地盤 | の破壊によ | ●作験集し | | 2.不明確 | 3.危険あり | ⊕ / | | |
| 11 ③晩盤破壊に | ③螃蟹破壊による健務物全体の沈 | | | , | 2. 0.2≡~1.6∈ | 3. 1.0=#5 | @/ | | |
| ④不用沈下に | よる建築 | 物全体の幅 | O 1/60EET | | 2. 1/60~1/30 | 3. 1/30dg | ® / | | |
| \$5 | | | | | | | 柱の被害最大 | | |
| 定 性の被害(下る | | | | | | 壁の長さに読みかえる) | 2 | | |
| ②情傷度 V d | (性本数/ | 調査性本数 | | ## 7 / | ■素柱32本 () | | 0 3 | | |
| | | | 1. 1%KF | ww. / · | 2. 1%-10% | O. 10% AT | | | |
| (2) ⑥神師度例の | 2年本歌/ | 調査性不設 | © 10%ELT | 松款 / 4 | 2. 10%~30% | 3. 20% #4 | ® / | | |
| 7650(2) | | | 1. 興養済 | | 2. 数排电 | O R PA | M(Q(2) | | |
| 7830.47 | | | 全部ハラン | クの場合 | Bランクが1の場 | | | | |
| | | | | | | は8ランクが2以上 | | | |
| 危険度の判定 | | | 1.調査済み | | 2.委往草 | ① 他等 | 805 | | |
| 制定(1)と制定(2)。 度で制定する | かうち大き | な方の危険 | (契件観測 | 査) | | | _ 3 | | |
| | | | | | | | _ | | |
| 3 落下危險物 | 転倒燈器 | _ | | | | | , | | |
| | | | ランク | la- | Bランク | C9>9 | | | |
| ①窓枠・窓ガラス | | 1.ほとんと) | 1100 | | , orest | 3.落下の危険有り | 0 2 | | |
| ①外媒材(モルタ: ル・石貼り等) | ル・タイ | 1.ほとんど無観客 | | O89 | 的なのび割れ、聴用 | 3.顕著なひび割れ、別権 | @ 2 | | |
| ①外装材 (ALC 板・PC 板 1.目地の鬼・全量・ブロック等) | | 製程度 | Ø#: | 専用が見られる | 3.顕著な目地でれ、仮破壊 | ⊕ _ 2 | | | |
| ①重報・機器類 1.税約策し | | | Oto 4 | かな傾斜 | 3.基下の危険有り | @ 2 | | | |
| ①星外臨段 | | | | 2.6% | かな傾斜 | 3.明瞭な傾斜 | (B) - | | |
| あその他 (基タ)水 | その他 (及り)(建設 1.安全 | | | 2.要注 | œ. | Ø ® 除 | ® 3 | | |
| 角験度の制定 | | 1.調査済み 全部人ウンタの場合 | | 2.要社 | | Den | 押定 | | |
| | | | | 89 | ンタが1以上ある場 | ○ ランクが1以上ある場 | . 3 | | |
| SARS OF | | h s wide o | 1. C. H. A. I. C. | | 対が分類をのうと | 3 の大きい方の危険度で! | | | |
| 吸口料定 (時度) | | x < 11 x ≥ 1 | に構造は底 | m, en | ALTERNATION Z C | *ハングロルソハン(2000K) (c.) | 19 総会判定 | | |
| 労する。 | | | | | | | | | |

Damage survey at Tohoku Univ. campus



Post-EQ inspection and rehabilitation

Occurrence of EQ



Quick inspection

Conducted by local government

Inspector = structural engineers & architects



Damage evaluation and rehabilitation

Conducted by owner

Inspector = structural engineers, researchers

26

Post-EQ Damage Evaluation

- Japanese Guideline (JBDRA, 1990)
 - Residual seismic capacity, R, is evaluated by damage class (I, II, III, IV, V) of structural members



R - index (%) Limit state

[Slight] 95 - 100

80 - 95

[Moderate] 60 - 80

[Severe] - 60

[Collapse]

Serviceability

Reparability Safety



[Minor]

Basic concept of Damage level evaluation


Residual Seismic Capacity Ratio R

Is: seismic performance index in Seismic Evaluation Standard(1977)

$$I_s = E_0 \times S_D \times T$$


$$E_0 = C \times F$$
: Basic Structural Index

C: Strength Index, F: Ductility Index





Load Carrying Cap. vs. Damage Class





Damage class of structural member


Damage Level Classification Standard (1991)


| Damage Class | Observed Damage to Structural Members |
|--------------|---|
| I | Some cracks are found. Crack width is narrower than 0.2 mm. |
| II | Cracks of 0.2 - 1 mm wide are found. |
| III | Heavy cracks of 1 - 2 mm wide are found. Some spalling of concrete is observed. |
| IV | Many heavy cracks are found. Crack width is 2 mm or wider. Reinforcing bars are exposed due to spalling of covering concrete. |
| V | Buckling of reinforcement, crushing of concrete and vertical deformation of columns and/or shear walls are found. Sidesway, subsidence of upper floors, and/or fracture of reinforcing bars are observed in some cases. |

2014/7/20

Damage survey for school buildings

546 RC school bldgs. were investigated by AIJ reconnaissance team (over 20 professors)







Damage class I to V

Check sheet for damage level evaluation

23 上部構造の耐震性能残存率 R による判定

- ① 被害の最も激しい階と方向 __1_階 方向: □短辺方向 □長辺方向
- ② ゾーニングの要否: ①不要(建物全体で判定する)

□必要(ゾーニングした区画を平面図などで明示し、区画ごとに判定する)

③ 構造部材の損傷度調査結果 ※()内にそれぞれの柱本数や壁枚数を記入し合計を計算する。

| | | | Flexura | I III | | | Wall | | | | , |
|-------|---------------------|---|------------------|-------|------------------|----------|------------------|-----------------|----------------|--------------------|------------|
| | Shear col | . | col. | | | | — | _ | - | 合計 | |
| 総部材数 | (25) | + | () | + | () | + (| 4) | + (2) | = | (31) | |
| 調査部材数 | (25) ^① | + | () ² | + | () ³ | + (| 4) ⁴ | + (2) | ⁵ = | (31) | |
| | ①x 1 | + | ②x 1 | + | ③x 1 | + | ④x 2 | + 5x 6 | = | (45) | $=A_{org}$ |
| 損傷度 0 | (1) | + | () | + | () | + (|)× 2 | + (1)× 6 | <u> </u> | (7) | $=A_0$ |
| 損傷度 I | $(3) \times 0.95$ | + | ()× 0.95 | + | ()× 0.95 | + (|)× 1.9 | + ()× 5 | 5.7 = | (2.85) | $=A_1$ |
| 損傷度Ⅱ | $(11) \times 0.6$ | + | ()× 0.75 | + | ()× 0.6 | + (| 2)× 1.2 | + ()× 3 | .6 = | (9) | $=A_2$ |
| 損傷度Ⅲ | $(4) \times 0.3$ | + | ()× 0.5 | + | ()× 0.3 | + (| 1)× 0.6 | + (1)×1 | .8 = | (3.6) | $=A_3$ |
| 損傷度IV | $(2)\times 0$ | + | ()× 0.1 | + | ()× 0 | + (|)× 0 | + ()× (| = | (0) | $=A_4$ |
| 損傷度V | $(4) \times 0$ | + | $() \times 0$ | + | ()× 0 | + (| 1)× 0 | + ()× (| | 0 | $=A_5$ |
| | | | | | | $\sum A$ | $A_j = A_0 +$ | $A_1 + A_2 + A$ | $A_3 + A_4$ | $_{4} + A_{5} = ($ | 22.5) |

④ 耐震性能残存率 R

$$R = \frac{\sum A_j}{A_{org}} \times 100 = \frac{(22.5)}{(45)} \times 100 = (50)$$

上部構造の耐震性能残存率Rによる被災度区分

- □無被害(*R*=100)
- □軽微(95≦*R*<100)
- □小破(80≦*R*<95)

- □中破(60≦*R*<80)
- 大破 (R<60)

□倒壊(崩壊・落階等によりほぼ*R*≒0 とみなせる)

Pictures and comments

文料省学校調查 写真語

学校名: 魏谷東小学校 住所: 仙台市宮城野区鶴ヶ谷六丁目2

建物名 (金属等号): 西校舎 ((f)-2~7) RC 造 3 閣建 (3.708m2)

担当者:東北大学(前田匡樹、松川、青木、三浦、高橋、前田美里、松尾)

調査日時: 4月22日(金) AM9:00~12:00 応急危険度:危険 被災度:中破



校舎全景。写真右が西校舎、左が東校舎。 渡り廊下を通して連結され、ExpJが、渡り 厳下の西校舎側の位置に設けられている。東 校舎は耐震補強されているが、西校舎は耐震 診断の結果、補強不要と判断されている。



北側の周囲地盤で、20cm 程度の次下が見ら れた。損傷がほとんどない柱位置で傾斜を計 測したところ。傾斜はほとんどりであった。



建物自体には、目立った傾斜や沈下は確認さ れなかったが、床には多数のひび割れが見ら れ、1cm 程度の段差が生じている。また、こ れらのひび割れは、校庭に生じた亀製と同じ 位置に生じ、上階のスラブまでひび割れが生 じている。

文科省学校調查 写真原



西面南側 1 間の柱。短柱となったことでせん 断破壊し、損傷度V程度まで進行していた。 この他に損傷度Vの短柱が1本、損傷度IVの 短柱が5本、損傷度宜の短柱が5本確認され た。桁行は20スパンあり、北側の柱は同様に 短柱となっていたものの、南側に比べて被害 は小さかった (機傷度1~1程度)。また東面 の柱は、西面とは異なり短柱となっておらず、 概ね損傷度Ⅰ~Ⅱ程度であった。



西面南側 1 階の柱型付壁。関ロの部分でせん 断破壊が生じ、ひび割れが内部まで貫通して おり、地震力を負担できない状態であると思 われる (損傷度V)。

写真5



2階西面南側の柱 (損傷度Ⅱ)。短柱となって いる場所でも、損傷度は最大工程度であり、1 難と比較すると被害は軽微であった。3 階に ついても、ほぼ同程度の被害であった。




Database of RC school buildings

In addition to quick inspection

- Summary of the building
- Const. year
- ✓ Ground, base, pile
- Seismic intensity
- Damage to structure
- Damage class for all structural members
- ✓ Settlement, inclination

- ✓ Residual capacity ratio R
- Damage level (slight collapse)
- Damage by tsunami
- Comments
- Seismic capacity
- ✓ Is-indeces
- Strengthening & retrofit



Q6: What data were lost (not yet collected)?

- Damage to non-structural elements, impact to building function,
- Decision and procedure of rehabilitation
- Costs for repair and strengthening



Summary

Data Collection in Miyagi pref.

Collected (approx. 500 school buildings)

Configuration of structure, material ...

Seismic capacity (Is-index)

Damage class of structural members, residual capacity R Photo ...

Lost (or not yet collected)

Damage to non-structural elements, functionality, social impact ...

Decision making procedure for rehabilitation



Reconstruction almost completed











Report from Japan on Q2, Q3, and Q8

KOICHI KUSUNOKI FROM EARTHQUAKE RESEARCH INSTITUTE, THE UNIVERSITY OF TOKYO





Q2:Have any relationships between the different forms of data been explored?

Data Collection of damages to non-structural elements

- Fortunately, the number of the severely damaged building due to Tohoku E.Q. is not so much.
- ▶ The damage to non-structural elements are focused, since it is also harmful to the people around them.



Ceiling system



Concrete block wall

Data Collection of damages to non-structural elements

- Non-structural damage of the buildings administrated by MEXT are investigated.
- ▶ In order to get fund for the repairmen, reports on the level of the non-structural damages including photos, written estimates, and the building identification number were submitted to MEXT.
- There is a database in MEXT on building information such as structural type, design year, constructed year, number of stories, and etc.
- We got permission to see the reports and database.

Q3:What organizations were involved in collecting data and for what purpose?

Post earthquake survey organizations in Japan (Q3)

- Governments and national research institutes
 - Local governments
 - To grasp the damage of the area

Quick Inspection

To reduce additional damages due to aftershocks To reduce the number of refugees from seismically OK Buildings

To figure out what area and what type buildings were damaged.



Inspection is based on Visual Investigation.


Post earthquake survey organizations in Japan (Q3)

- Governments and national research institutes
 - Ministry of Land, Infrastructure, and transportation
 - ▶ To check the Building code and building administrations
 - Building Research Institute(BRI)
 - National Institute for Land and Infrastructure Management (NILIM)
 - Ministry of Education, Culture, Sports, Science and technology
 - From the scientific point of view
 - National Research Institute for Earth Science and Disaster Prevention (NIED)
 - ▶ Institutes and Laboratories of Universities
 - Earthquake Research Institute, the University of Tokyo
 - Disaster Prevention Research Institute, Kyoto University












- K-Net by NIED
- Strong motion observation network.
- Open to everybody
- Data is available soon after the earthquake



Post earthquake survey organizations in Japan (Q3)

- Academic associations and branches
 - To record the earthquake and damages
 - Disaster Management Committee, AlJ
 - Tohoku Branch of AlJ
 - Japan Association of Earthquake Engineering
 - Data Sharing between JAEE, JSCE, JGS, SSJ, and JSME
 - Societies decided to control the field investigation under the name of societies
 - Not to disturb the rescue activities and local government works
 - Due to nuclear power plant accident
- Research institutes and associations of construction, design, insurance, real estate, homebuilding companies such as BCS/JSCA, UR,
 - To check their buildings

Q8:How are data stored after collection and what are access policies for this data?

The data list format to the AIJ report (Q8)

The data of the damaged buildings were collected in a formatted list and shared within the research group. The data list is to be published as the appendices of the research report.

Data list of AIJ report

- Building name
- Location
- Structural type
- Number of stories
- Damage to the structure
- Damage to the ground
- Year of construction
- Seismic intensity
- Quick inspection result
- Seismic screening result(If available)
- Damage classification result
- Residual seismic capacity ratio(If available)
- Tsunami damage
- Memo
- Etc.

Collected and lost data, difficulties in the BRI survey on Tsunami damages(Japan Experience)

National Institute of Land and Infrastructure Management Toshikazu Kabeyasawa




What forms of data were collected?

- 1 Inundation depth of the building
- 2 Onsite investigation of damaged building
 - (1) State (Location, Damage)
 - (2) Dimension (Plan, Height, Openings)
 - (3) Detail (Member, Material)
- 3 Collecting drawings of Public buildings








How were the data collected?

- Water mark of forward and backward of survived building
- (2) Measure building and member dimension manually (focused on small-scale buildings)
- 3 Data usage permission for official purpose from local government







Difficulty in collecting data

- ① Water traces disappears one month after earthquake by rain Tsunami flow characteristic is affected by topography
- 2 Damage process or mechanism is not clarified Effect of Buoyancy, Debris Impact or Damming
- 3 Most of drawings and buildings are washed out

Tsunami Flow Characteristic





Overturning Mechanism



What data were missed?

- 1 Difference of water height disappears in valley type tsunami Minimum tsunami height for reconstruction decisions
- 2 Investigation concentrates on severely damaged area Survived buildings with direct foundation (effect of buoyancy)





How are data stored after collection?

Prompt Investigation Database (BRI/NILIM Report)

| 建物番号 | OG-11 | | | 調査 | 3 2011年 | 4月9日 | |
|--|--------------|----------|--------------------------|-------------|---------|-------|--|
| 名称 | | 2 | | | | | |
| 所在地 | 女川町女川浜女儿 | il - | | 建設 | 年不明 | F. | |
| 用途 | 商業施設・店舗 | | _ | 津波 | 壁難ビル | 指定なし | |
| 構造種別 | RC造 | (耐力壁付ラー。 | メン構造) | | | | |
| 建物規模 | 階数 | 2 階 | (地下 | 階) | 高さ | 7.2 m | |
| X差1/07/01天 | 平面寸法 | 11.3 m × | 9.4 m | | | | |
| 7 to 6 La / La 1974 | 海岸からの距離 | 約100 m | 標高 | | 15 m | (GPS) | |
| 建物位置 | 立地条件 | 女川街道沿い | -44 | | | | |
| 最大浸水深 | | 14 m | 周辺 | 生物側面 | 記痕跡 | | |
| ************************************** | 建物の状態 | 原位置に残存 | 1×2スパン、非構造部材のみ被害が られた | | オのみ被害が見 | | |
| 津波後の状況 | 躯体の被害 | 被害なし | -+ | | 1000 | | |
| | 非構造部材の被害被害あり | | 窓ガラ | 窓ガラス 天井材の脱落 | | | |
| 備考 | | | | | 11 | | |

- ・女川沿岸部に立地し残存していたRC2階建て
- ・津波の作用方向(梁間方向)に開口付き耐震壁を有し、桁行構面には大きな開口を有している
- ・内部には梁せい下まで浸水の痕跡が見られる
- ・柱断面は800×500mm、壁厚は180mmであった



写真 1 建物外額(1)



写真 2 建物外観(2)



写真3 建物 1階の浸水痕



Analysis of buildings based on drawings (BRI/NILIM Report)

6.2.6 建築物 E の被害

(1) 被災建築物の概要。


本建築物は1970年に建設された壁式ブレキャストRC造(リブ付中型コンクリートバネル造)2階建ての公営 集合住宅である。本団地は1棟あたり3~5戸からなる仕棟6棟から構成されており。海岸線に近い側の4戸1 住棟2棟について機がを行う。1階平面は図6.2.6・1に示す通り、長辺は4スパン(スパン長さ3.81㎡、短辺は1スパン(スパン長さ5.16㎡ で共通である。本建築物では屋上に悪流物が確認されたことから、浸水深は建築物高さ(5.85㎡以上と推定され。近隣のRC造3階建て集合住宅の前面における計態浸水深は7.5㎡であった。本建築物の被害状況としては、周辺地盤の洗掘による傾斜(写真6.2.6・1)や、漂流物の確実によるとみられる2階要壁の損傷(写真6.2.6・2)が見られたものの。1階には構造的な大きな損傷は確認されなかった。なお、海岸線から本建築物までの船離1数9800㎡であった。



写真 6.2.6-1 周辺地盤の洗掘による傾斜




写真 6.2.6-2 2階要壁の損傷




Statistical Damage Survey

| 区分 | 全壊 (流失) | 全 | 塘 | 全壊 (1階天井以上浸水) |
|-----------------|--------------------------|----------------------|----------------------|--------------------------------|
| 主な建物 状況 | 基礎だけ残して、建物が完全に 流されている | | 表しており補修に 使用することが困 | 1階天井以上浸水しており、 模修繕等による再使用も可能 |
| サンブル 写真 | | | RET | a li mina |
| 棟数 [※] | 約 78,000 | 約 34 | 1,000 | 約 8,000 |
| 区分 | 大規模半壊 | | 壊 浸水) | 建物被災状況(イメージ) |
| 主な建物 状況 | 床からおおむね1m以上(天井未満)浸水している | 床から概ね1m: (一部補修により | 未満の床上浸水 再利用可能) | W |
| サンプル 写真 | A MILE MAN | | | |
| 棟数※ | 約 36,000 | 約 40 | 0,000 | |
| 区分 | 一部損壊 (床下浸水) | 棟数 | 合計 | 314 |
| 主な建物 状況 | 床下の泥を取り除けば再利用可能 | | | |
| サンプル 写真 | 5 | 被災建物総計 | うち全壊 | |
| 棟数 [※] | 約 23,000 | 約 219,000 | 約 120,000 | -11 |
| | | 被災建物 棟数割 | 合 | |
| | 35% | 186 45 | 16% | 18N 11N |

Statistical Damage Survey



Statistical Damage Survey



Sharing data across different organization

Official study purpose is important for sharing data

IIS (University of Tokyo)

Collaborate Study on Tsunami Load on building (Damage survey of Plain structures)

BRI / NILIM

Development of new design guideline of tsunami shelter (Damage survey of Building)

PARI

Collaborate Study on Tsunami Load on building (Joint survey & Hydro dynamic test)

ASCE

Revising ASCE-07 Code (2016)
(Joint survey & Information exchange)

AIJ

3.11 Earthquake Damage Investigation Report Revising recommendation for design load (Provision of Information)

Report from Japan

Survey on the post-earthquake functional use of public buildings by BRI

Building Research Institute, Japan Tomohisa MUKAI



BackgroundDamage Examples of Government Buildings

Even damage level was minor, those government buildings had no functional use after EQ.

| No. | Area | Const. Year | Seismic Evaluation | Continuous Use | Seismic Intensity | Damage Level |
|-----|------------|----------------|-----------------------|-------------------|----------------------|-----------------|
| A | Tohok u | 1963 | (NG) | NG | 5 Upper | Severe |
| В | Kanto | 1961 | No | NG | 6 Lower | Minor |
| B' | Namo | 1961 | No | _ | 6 Lower | Moderate |
| С | | 1970 | (NG) | NG | 6 Upper | Severe |
| D | Kanto | 1968 | (NG) | NG | 6 Upper | Minor |
| E | Namo | 1967 | (NG) | NG | 5 Upper | Minor |
| F | | 1960 | (NG) | NG | 6 Lower | Severe |
| G | | 1958 | No | NG | 6 Upper | Moderate |
| Н | Konto | 1966 | No | NG | 6 Upper | Moderate |
| | Kanto | 1964 | No | NG | 6 Upper | Severe |
| J | | 1969 | (OK) | NG | 6 Upper | Moderate |

Objectives

Obtaining and analyzing data on situations of post-earthquake functional use for public buildings

Collect data on post-EQ situation



Analyze the situations on post-EQ functional use




Collecting post-EQ data

-> Factor Analysis of barriers on post-EQ functionality


- ①Collecting data of post-EQ situation for RC government buildings, RC gymnasia, RC public housings (Collected Number is 41 cases):
- →drawings, structural documents, information on situation of post-EQ continuous use
- <u>②Factor Analysis of situations on post-EQ</u> <u>functionality</u>:
- →Making the Flowchart which can explain the situation of post EQ continuous use for damaged buildings considering the collected data



Flowchart for post-EQ continuous use of damaged buildings



Flowchart for post EQ continuous use of damaged buildings



Conclusions

- ①Objectives · Methodology of data collection: In order to understand the post-EQ functional use for government buildings and evacuation facilities, **hearing surveys** were done by BRI.
- ② Analysis Result of collecting data:

We showed the flow-chart which explain how the administrators took **actions** and make **decisions on post-EQ functional use** for damaged public buildings.



Appendices;

Answers to Ken-san's 8 questions In the case of BRI



What forms of data were collected after the earthquake?

Data of interest to this workshop include building performance (physical damage), business interruptions, housing impacts, and post-earthquake decisions (repair vs demolish). We are interested in data at both the detailed building level as well as at the broader community level. What data were used to assess building residual capacity and how were these data used in reconstruction decisions? What should be implemented in data collection protocols to make the assessment of residual capacity more reliable?

Answer01;

BRI collected the data on post-earthquake functional use for public buildings to analyze the barrier of post-EQ functional use for public buildings.



Have any relationships between the different forms of data

been explored? For example, what is the relationship between the physical damage and business interruption? Are there other factors influencing the socioeconomic impacts, suggesting other forms of data that should be collected?

Answer02; No relevant items.



What organizations were involved in collecting data and for what purpose? Such organizations may include city government, insurance companies, university researchers, etc. Although the goal of data collection may be different for each organization, the data may be similar and synergistic efforts should be identified.

Answer03 (same as A01);

BRI collected the data on post-earthquake functional use for public buildings to analyze the barrier of post-EQ functional use for public buildings.



What barriers are there to sharing data across different organizations? What experience do you have in finding ways to share data across government and non-government entities?

Answer04;

Regarding public buildings, sharing data depends on the objectives. Basically we need permission to the administrator of public buildings in advance.



How were the data collected? Were any advanced technologies used to collect data or were all data collected manually? What training was provided for data surveyors?

Answer05; BRI collected all the data manually.



What data were lost? Were there specific data that were not collected, or not collected in a coordinated manner, such that the data may not be available for future research studies?

Answer06; Not at all.



Lessons from the data collection process. What aspects of the data collection process seemed to work well? What could be improved upon?

Answer07;

First of all, intimate personal and organizational relationships seems to be effective to collect the data after earthquake. Secondary, the system to judge the post-EQ functional use before earthquake occurs may enable us to collect the detail data of buildings.



How are data stored after collection and what are access policies for this data?

Answer08;

The data of the damaged buildings were collected in a formatted list and shared within the BRI.

Items in the formatted list:

- 1. Surveyed building information (usage, structural type, foundation system, geological formation)
- 2.Damage information (measured seismic intensity(JMA), information on judgments for post-EQ continuous use of the damaged building and on the components which became barrier for post-EQ continuous use, repair method & process, classification of building's importance after EQ)
- 3.Relevant data (structural documents, drawings, damage survey reports)

Suggestions for the development of consensus-based data collection protocols? One of the primary goals of the workshop is the initial development of consensus-based data collection protocols for application after future earthquakes around the world. What experiences from the events in your country could inform the development of these data collection protocols?

Answer09;

After big earthquake occurs, it is very difficult to collect he data immediately. The system to collect the building's data is needed before occurrence of earthquake.



Post Earthquake Date Collection by Local Government

Satoshi TANAKA

Tokoha University

Summary of the Inspection

- Local Gov. officials inspect the building damage
- Most of the victim support programs require the result of this inspection
- It covers all the disaster areas
- Collect the building damage data for both structural and non-structural components
- All the buildings (Wood, RC, and Steel) for all hazards (Earthquake, Flood, and Wind)
- Evaluate the damage from economical view point

What forms of data were collected after the earthquake?

Damage ratio = **Economic Damage /Entire Value Damage Assessment by Local Government** (1) Assessment by exterior inspection It is immediately obvious that the entire dwelling house has collapsed. 2 It is immediately obvious that one or more stories of the dwelling house has completely collapsed. One or 3 One or more of the sides of the foundation has been completely destroyed from ground. More liquefaction or other cause. applicable Completely destroyed Neither applied (2) Assessment by building tilt (damage ratio 50 percent Exterior wall or column is tilted at the rate of 1/20 or greater. or greater) **Applicable** Not applicable (3) Assessment by component Destruction rate of foundation is 75 percent or greater. Applicable Not applicable (As of 2012.3.8) Determine damage ratio of dwelling house from destruction Completely destroyed 50 percent or greater rates of individual components, 125,509 etc. (and tilt). 40 percent or greater, less than 50 percent Mostly destroyed Damage ratio of dwelling house 72,968 20 percent or greater, less than 40 percent Half destroyed 184,151 Less than 20 percent Less than half destroyed 766,748

Operational Guideline for Damage Assessment of Residential Houses in Disaster (Cabinet Office)

Untrained local government officials (not engineers) inspect and collect the data.

Visual inspection of the exterior and interior of building with check sheets.

Data is recorded on papers and stored them at the local government.

Access to the original data is very limited though the summary of the data is in GIS

Primary inspection is carried out by the visual inspection of the exterior 作章被害認定課委(地質: 木造・ブレハブ 第1次8) 議審朝合イメージ間 204程度の世上州が別等 **Exterior Wall** · 前面型格口等汇次 Totally Flow out destroye PARTOCIAL SEE **単位人が対象策している場合の数据い** CODERACE TVA Totally Inundation destroy up to celling 住家被容認定調査(地震:水道・ブレハブ(第1次B) 機容割合イメージ器 MEMO 1M MTHA 1% Inundation Mostly このかずかの数分にひび削れ destroy Im above floor level **Foundation** Roof Inundation destroy Inundation Minor under floor Damage Tsunami Earthquake

Secondary inspection is the visual inspection of both exterior and interior

Record damaged parts on building floor plan Evaluate the rank and extent of damage of each building component.



Inspection form

Floor plan with results of damage inspection noted

Damage Rank of Column for wooden house

木造・プレハブ [地震による被害]・部位による判定

第 2次調査

柱 (又は耐力壁)・・・ア.柱の損傷

= p1-26 2-2 ア.柱の損傷

•程度1



Eと果の仕口にむずかはずれが生じている。

柱面エングリートのひで倒れが見られる。

• 程度Ⅱ



E. 乗が着下たわんでいる。



アンカーボルトの体でが見られる。

• 程度Ⅲ



ちと梁の仕口においが生じる。後、



性、果に割れが見られる。

• 程度 IV







料、薬の付けに著ないすれが見られる。

• 程度 ∨



件、乗の制作、新重欠模が等した。



柱、飛に書は、明賞が至りており、交換が必要である。

• 損傷の判定 <表 柱 模式比20%)>

| | 観像の例示 | | | |
|-----|--|--|------|--|
| 特度 | 在来工法】 | 鉄骨系プレハブ1 | 操傷程度 | |
| I | 性と限の仕口にわずかなずれが生じている。 | 柱弾コンクリートのひび割れが見られる。 | 10% | |
| п | 一部の柱と原の仕口にか「込み等の損傷が見られる。 柱、梁が若干たわんでいる。 | アンカーボルトの体びが見られる。 他力ポルトのすべいが見られる。 | 25% | |
| ш | 作と家の仕口にずれが生じている。 社、家に割れが見られる。 | 特別施屋による小さな音形が柱に無じている。 保持合部の変形が見られる。 | 50% | |
| ĮV. | ・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・ | 標的単版による中ではの変形が特に生むでいる。 候補会部の複製、ボル1の一部映画が見られる。 | 75% | |
| v. | 様、梁の解れ、野国矢橋が著し、 ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ | 類解機器による大きな容別が特に生じている。 保持会部に強新が見られる。 | 100% | |

Damage Rank of Columns for Steel and RC

非木造 [地震・水害・風害による被害] ● 部位による判定

柱(又は耐力壁) A. 鉄骨造ア. 柱

○地震 p1-51 1-1 ア.柱(又は栗)の損傷 ○地震 p1-66 2-1 A. ア柱の損傷 ○水害 p2-47 1-1 A. ア柱の損傷 ○風害 p3-45 1-1 A. ア柱の損傷

●程度 I



柱振コンクリートのひび割れが見られる。

●程度Ⅳ



異態産業による中ぐらいの変形が柱に見られる。

●程度Ⅱ



アンカーボルトの伸びが見られる。

●程度V



報合部の破断が見られる。

●程度Ⅲ



局部運動による小さな変形が柱に見られる。

●損傷の判定

≺表 柱(地震1次調査):模成比60% /柱(地震2次調査·水害·風害):模成比50%>

| 程度 | 機構の倒示 | 接番程度 |
|----|--|------|
| 1 | ・柱間コンクリートのひび割れが見られる。 | 10% |
| n | アンカーボルトの伸びが見られる。高力ボルトのすべりが見られる。 | 25% |
| n | ・局部産品による小さな変形が核に見ら れる。 | 50% |
| w | ・局部展開による中ぐらいの変形が柱に 見られる。 | 75% |
| v | ・局部座頭による大きな変形が柱に見られる。 ・接合部の破断が見られる。 | 100% |

せ(又は耐力壁)B. 鉄筋コンクリート造 ア. 柱 ☆地震 pl-51 i-1 ア. 柱(又は巣)の損傷 柱(又は耐力壁)B. 鉄筋コンクリート造 ア. 柱 ☆地震 pl-59 2-1 B. ア柱の損傷 ☆風景 pl-59 2-1 B. ア柱の損傷 ☆風景 pl-59 2-1 B. ア柱の損傷 ☆風景 pl-51 i-1 ア・柱(又は巣)の損傷 ☆風景 pl-50 1-1 B. ア柱の損傷

●程度 I



返寄らないと見えにくい程度のひび割れ(輻的0.2mm以下)が生じ

●程度Ⅳ



大きなひび割れ(2mmを超える)が多数生じ、コンクリートの製造も 誰しい、飲飲が禁由しているが、飲筋の変形は見られない。

●程度Ⅱ



内眼ではっきりと見える程度のひび割れ(権約0.2mm~tmm)が 生じているが、コンクリートの製器は生じていない。

●程度V



数馬が大きく露出しており、数島の曲がり・後期が見られる。内部 のコンクリートも原れ着ち、柱の高さ方向の変形が生じている。

●程度Ⅲ



比較的大きなひび馴れ(転的)mm -- 2mm)が生じているが、コンクリートの製薬は様くわずかで、鉄筋は震型していない。

●損傷の判定

(表 柱(地震1次開表):構成比60%/は(地震2次開表・水害・薬害):接成比50%>

| 程度 | 機構の併示 | 损傷程度 |
|----|--|------|
| ı | ・近番らないと見えに(い程度のひび倒れ (編約03mm以下)が生じている。 | 10% |
| 1 | 内閣ではっきりと見える程度のひび割れ (福勢の2mm~ 1mm)が生じているが、コンク リートの製事は生じていない。 | 25% |
| ш | 比較的大きなひび観れ(報的:mm~2mm) が生じているが、コンクリートの剥落は様く わずかで、鉄筋は塞出していない。 | 50% |
| 17 | 大きなひび割れ(2mmを建える)が多数生じ、 コンクリートの刺馬も激しい。最低が露出しているが、最低の変形は見られない。 | 76% |
| ٧ | ・錬薬が大きく質出しており、終熱の曲がり・ 破断が見られる。内部のコンケリートも凝れ 落り、柱の高さ方向の変形が生じている。 | 100% |

Damage Rank of Non-Structural Components

非木造 [地震・水害・風害による被害] ● 部位による判定

外部仕上·雑壁·屋根

⇔地蔵 p1-58 1-2 雑壁・仕上等 ⇔地蔵 p1-76 2-3 外部仕上・雑壁・屋根 ⇔水害 p2-60 1-3 外部仕上・雑壁・屋根 ⇔風害 p3-59 1-3 外部仕上・雑壁・屋根

●程度1



【外部仕上】 仕上村のわずかな影響、日地のずれが見られる。



一部にひび割れ(権約0 2mm~1mm)やはがれが生じている。

●程度Ⅱ



【外部仕上】 仕上やパネルの目地にはっきりとしたひび離れが見られる。仕上 材が部分的に制難している。



【発音】 6004 各所にひび解れ(権約0.2mm~1mm)やはがれが生じている。

●程度Ⅲ



【外部仕上】 大きなひび割れ又は仕上の剝離が見られる。



全体にひび離れ(権約3.2mm~timm)やはがれが生じている。

●程度 IV



【外部仕上】 仕上村の破壊、应落が一部見られる。

(雑壁)



[編集] (402 全体にDST対れ(編約1mm~5mm) やはがれが生じている。

●程度 V



全国にわたる大きな電影が見られ、面外への大きなはらみ出し、大きな製薬が見られる。





(無壁) 9404 全体が変形し、仕上の大部分が製造している。

〈表 発療・仕上等(地震1次調査):構成比25% / 小紙料トト就等・原境(地震2次調査・大家・展開):議時於10%>

| 44 | 数条の例 | * | 基体积点 | |
|----|---|---|------|--|
| 程度 | 【外部性上】 | 【整理・雑型】 | 美操作品 | |
| 1 | 仕上や仕上昇の目地にわずかなひび割れ(幅約02mm)が見られる。 仕上昇の開角部にわずかな亀裂が生じている。 仕上昇のわずかな剣閣、目地のずれが見られる。 | - 一部にひび割れ(幅約0.2mm~/mm)やはがれが 生じている。 | 10% | |
| | ・仕上やパネルの日地にはっきりとしたひび割れが見られる。 ・仕上村の日地にずれが見られる。 ・仕上村が部分的に刺離している。 ・一部に飛来物による眼性な情突痕がある。 | 各所にひび離れ(幅約02mm~imm)やはがれが 生じている。 一部に最未物による軽雅な委奏儀がある。 | 25% | |
| | 大きなひび割れ又は仕上の制能が見られる。 仕上幹が部分的に刺聴・軽等している。 一部に無未物による突き繋ぎり、資道痕がある。 | 全体にひび割れ(幅約0.2mm~/mm)やはがれが 生じている。 一部に限未物による突を繋さり、賞遺館がある。 | 50% | |
| N | ・仕上の圏外へのはらみ出し、又は制売が見られる。 ・仕上材の破壊、商業が一部見られる。 ・大半にわたって飛来物による民突症、突き繋さり、貫達症がある。 | 全体にひび離れ(幅約1mm~>mm)やはがれが生じている。 大学にわたって飛来機による衝突症、突き繋ぎり、 貫通底がある。 | 75% | |
| ٧ | ・金良にわたる大きな集製が見られ、関格への大きなはらみ出し、大きな制等が見られる。・金酉にわたって発来物による衝突症、突き到さり、貫通症がある。 | ・全体が変形し、仕上の大部分が報用している。・金面にわたって発来物による衝突痕、突き繋ぎり、 貫通痕がある。 | 100% | |








Have any relationships between the different forms of data been explored?

Victim support programs are applied based on the inspection result



- Speed and fairness are essential to the inspection
- 1. Act on Support for Reconstructing Livelihoods of Disaster Victims
- 2. Donation Money by many organizations
- 3. Tax exemption
- 4. Low interest loan
- 5. Tuition exemption
- 6. Temporary housing

Ex. 3.11 Tohoku EQ, Miyagi Pref. case

A victim whose house was totally destroyed will receive about \$50,000 by 1 and 2 support programs.

Post-earthquake decisions (demolish or repair)

- Inspection result does not relate to the residual capacity
- Cost (repair vs new construction) is the key factor to the decision
- Supporting programs
 - Demolishing cost
 - Reconstruction cost (ex. \$20000 +)
- Changes in Family structure

Issues need to concern for data collection

- Since the inspectors are not well trained, they could record the damage but could not evaluate the damage properly.
- Difficult to know the structural component from the non-structural one.
- Just a visual inspection, which does not remove the covers of the structure.

What barriers are there to sharing data across different organizations?

- Act on the Protection of Personal Information
 - Damage data is regarded as personal information
- Original data is recorded on papers, not digitalized
- No standardized protocol for transferring and accumulating the data
- Data = damage description+ damage evaluation
 - Damage description, such as location, type and extent of damage, photos, can be sharing
 - Damage evaluation depends on objectives of inspection
 - Need to separate the damage description from damage evaluation

International Post-Earthquake Data Collection Workshop Anchorage Alaska, July 20-21, 2014,

Japanese Experience

1:00 pm - 2:30 pm

3:30 pm – 4:00 pm, July 20

Seven Participants

- 1. Toshimi Kabeyasawa, University of Tokyo (Q1, Q6)
- 2. Masaki Maeda, Tohoku University (Q1, Q5, Q6)
- 3. Koichi Kusunoki, University of Tokyo (Q2, Q3, Q8)
- 4. Toshikazu Kabeyasawa, MLIT (Q6)
- 5. Tomohisa Mukai, Building Research Institute (Q1)
- 6. Satoshi Tanaka, Fuji-Tokoha University (Q1, Q2, Q4)
- 7. Sam Kono, Tokyo Institute of Technology (Q7, Q9)

Reconnaissance report on Tohoku EQ (29 volumes)

- Summary
 - Seismology
 - **Tsunami**
 - 3. Soil failure
- JSCE
 - Damage and recovery 1
 - Damage and recovery 2
 - 3. Lifelines
 - Traffic facilities
 - 5. Nuclear
 - Immediate reactions
 - **Economic influence**
 - 8. Recovery

- - **RC**
 - PS/SRC/Wall/Masonry
 - 3. Steel
 - **Timber**
 - 5. **Foundations**
 - 6. Non-structural
 - 7. Fire
 - Equipment
 - Socio-economic
 - 10. Planning
 - 11. Standards and laws
- JGS (Geotech)
- JSME (Mechanical)
- City Planning Inst.
- JEES

東日本大震災合同調査報告 刊行予定一覧

| 刊行予定書 | 刊行予定 |
|--|-------------|
| ■共通編 (3編) | |
| 共通編1 地震・地震動 (幹事学会:日本地震工学会) | 2014年3月刊行 |
| 共通編2 津波の特性と被害 (幹事学会:土木学会) | 2014年春 |
| 共通編3 地盤災害 (幹事学会:地盤工学会) | 2014年春 |
| ■土木学会編(8編)(幹事学会: 土木学会) | 2014年~2016年 |
| 土木編1 土木構造物の地震被害と復旧 | |
| 土木羅2 土木構造物の津波被害と復旧 | |
| 土木編3 ライフライン施設の被害と復旧 | |
| 土木編4 交通施設の被害と復旧 | |
| 土木編5 原子力施設の被害とその影響 | |
| 土木編6 緊急・応急期の対応 | |
| 土木編7 社会経済的影響の分析 | |
| 土木編8 復興 | |
| ■日本建築学会編(11編)(幹事学会:日本建築学会) | 2014年~2016年 |
| 建築編1 鉄筋コンクリート造建築物 | |
| 建築編2 プレストレストコンクリート造建築物/鉄骨鉄筋コンクリート造建築物/壁式構造・組積造 | |
| 車築編3 鉄骨造建築物/シェル・空間構造 | |
| 建築編4 木造建築物/歴史的建造物の被害 | |
| 建築編5 建築基礎構造/津波の特性と被害 | |
| 建築編6 非構造部材/材料施工 | |
| 建築編7 火災/情報システム技術 | |
| 建築編8 建築設備・建築環境 | |
| 建築編9 建築社会システムと震災/集落計画 | |
| 建築編10 建築計画 | |
| 建築編11 建築法制/都市計画 | |
| ■地盤工学会編(3編)(幹事学会:地盤工学会) | 2014年 |
| 也盤編1 地盤構造物の被害,原因検討,復旧 | |
| 也盤編2 被災調査の記録 | |
| 也盤編3 地盤に関連する施設や地域の復興 | |
| ■日本機械学会編(1編)(幹事学会:日本機械学会) | |
| 技械編 | 2013年8月刊行 |
| ■日本都市計画学会編(1編)(幹事学会:日本都市計画学会) | 2014年 |
| 8市計画編 | |
| ■日本地震工学会編(1編)(幹事学会:日本地震工学会) | 2014年 |
| 原子力編 | |
| ■総集編 (1編) | 2017年 |
| 念集編・資料編 (幹事学会:日本建築学会) | |
| | |

Report from Japan on Q7 and Q9

+Heidi's question (online collection of case studies)

Sam KONO
Tokyo Institute of Technology

Q7:Lessons from the data collection process.

Good points

- EQ's are good wake-up calls. (People, engineers, government, researchers, ect.)
- EQ's keep proof-testing current codes/standards and education. (Lessons from previous EQ's are reflected in codes/ standards. The updates are tested repeatedly.)
- People prepare for EQ's in a good sense. (Market is aware of EQ's. People are aware of Tsunami after EQ's.)
- Large amount of knowledge can be obtained for professional engineers and young engineers.
- Reconnaissance report 29 volumes
 (Summary3+Civil8+Building11+Soil3+Mechanical1+CityPlanning1+NPP1+Appendix1)

Q7:Lessons from the data collection process.

Bad points

- Individuals, government, private companies, academic societies have different ways of collecting data and usage. (Market value may go down by sharing data. Private Information Protection Law)
- Hard to control inter-organization corporation/format for the first action. (Many organizations and individuals swarm to the damaged structures.)
- Interdisciplinary collaborations are far away. (except individual levels)
- Data collections are not easy task at all and there is not good momentum to share data with others. (Some collaboration system is required.)
- Data sharing policies are all different.

Q9:Consensus-based data collection protocols

- Specific goals are necessary to balance labor/time and outcome.
- Most data are voluntarily collected. It is not easy to pass them to unknown people since it is hard to tell how the database is used. (Commercial use will cause a problem.)

Heidi's question: Can Japan contribute to online collection of case studies?

- Each researcher is happy to contribute his/her data.
 - For very limited number of cases for public buildings (municipal building and schools).

• It is not easy to share data on private buildings.

Observatory for Community Resilience: Canterbury Case Study

National Science Foundation Award #1235573





EARTHQUAKE ENGINEERING RESEARCH INSTITUTE

Kenneth J. Elwood

- Building Officials Institute of New Zealand
- Canterbury Development Corporation
- Canterbury District Health Board quake Engineering Research Institute (EERI)
- Canterbury Earthquake Recovery Authority
- Canterbury Employers
 Chamber of Commerce

- Christchurch and Canterbury Tourism Board
- Christchurch City Council
- CORE Education Ltd
- GNS Science
- Healthy Christchurch
- Holmes Consulting Group
- Human Rights
 - Commission
- Lincoln University

measuring, monitoring, and acting upon data-driven indicators of recovery after the Canterbury earthquakes. A goal is to help EERI decide what type of role, assistance, and infrastructure it can provide or facilitate in future earthquakes with respect to measuring and monitoring recovery. The Canterbury earthquakes provide an excellent case study for this, being perhaps the most data-rich disaster in history.

The aim of the case study is to observe and understand how stakeholders in New Zealand are



EARTHQUAKE ENGINEERING RESEARCH IN

Board of Directors

Kenneth J. Elwood

Kathleen Tierney

- **Massey University**
- Ministry of Business, Innovation, and Employment
- Ministry of Education
- New Zealand Historical Places Trust


 University of Canterbury
- Pegasus Health University of Otago conducting this case study include the New Zealand Society NZSEE have a MOU that covers this type of collaborat • Victoria University

The aim of the case study is to observe and understand how stakeholders in New Zealand are measuring, monitoring, and acting upon data-driven indicators of recovery after the Canterbury earthquakes. A goal is to help EERI decide what type of role, assistance, and infrastructure it can provide or facilitate in future earthquakes with respect to measuring and monitoring recovery. The Canterbury earthquakes provide an excellent case study for this, being perhaps the most

- Reserve Bank of New Zealand
- ResOrgs
- **SCIRT**
- Statistics New Zealand



- 13 meetings = built environment
- 11 = social capital
- 8 = economic recovery
- 8 = human well-being
- Remaining = multiple roles



Themes

- Data Collection, Analysis, and Communication
- Use of Data in Decision Making
- Coordination and Sharing of Data
- Role of EERI and Outside Experts

Data Collection Tools

Heidi Tremayne
with Marjorie Greene and Maggie Ortiz
Earthquake Engineering Research Institute
with Sean Wilkinson, Newcastle University & EEFIT



Data collection and visualization tools for Eqk Reconnaissance

- Hardware
 - Phones, tablets, laptops, GPS, cameras, video
- Software
 - OS (fleeting), GIS, custom form or browser based solutions, databases
- Data
 - Taxonomy/metadata, GIS, before/after satellite data, imagery, notes, drawings, form data, etc.
- Visualization and Web Dissemination
 - Upload, Mapping, Photo Gallery, Search, archive



Post-Eq Data Collection History

- EERI has been conducting organized post-earthquake reconnaissance and data collection since the 1960s
- Traditional approach of EERI

 (as well as other organizations)
 has been hand written notes
 and photo documentation
- Since 2000 many organizations have tried to develop tools utilizing modern technologies









Challenges to Data Collection Tools



Challenge: Technology Outdated Quickly

- IT and technology advances quickly making tools obsolete, even middevelopment.
- Example: Rover with Windows Mobile




Note: Rover is still in use, but now uses web interface



Challenge: Level of Data Detail

Systematic data? What level of detail & quality?

- Limited time in field often leads to quick collection
- Slow, unwieldy tools can hamper use of detailed collection forms
 - Example: Accela (Palm & PC)
- Many researchers want to visit areas with most damage




- Few researchers want to document limited or no damage
- Many people with different levels or experience/expertise collect data. If data to be entered requires interpretation, the resulting data/interpretation may be inconsistent

Challenge: Data Ownership

- Many organizations, governments and government agencies involved in response and recovery hesitate to share data due to privacy, liability, etc. concerns.
- Each organization in the field wants to collect their own data, in their own way.
- Resistance to using other tools, when have developed in-house tools, would need training, or are comfortable with status-quo.

Challenge: Extended Timeline

- Reconnaissance Timeline:
 - Immediate Post-Eq
 - Intermediate Resilience
 - Long-term Recovery
- Data collection consistency?
- Identifying key data to collect?





Challenge: Large Number of Tools

- Many organizations have independently developed tools for data collection
- Data sharing can be difficult with different forms, metadata, and data frameworks
- Visualization of multiple data sets can be complicated
























Challenge: Connectivity


- Change to constant internet connectivity in modern life leads to expectations of nearimmediate data collection, sharing, and visualization
- With limited cellular or internet access many tools may not be operable
- Example: USGS html5 webapp tool has some functionality off line (but limited)



Challenge: Visualization

- Geo-located data is becoming easier to collect, thus map interfaces are becoming more common
- KMZ & KML map data layers exports are becoming easier and allow overlayment with other data
- With many levels of data and meta-data, other visualization may be needed beyond mapping
 - Search & Filter by metadata
 - Database
 - Image Galleries






Trends & Opportunities in Data Collection



Trend: Systematic Data Collection

- Researchers have an increasing need for detailed data to:
 - Measure resilience
 - Calibrate engineering models and analytical tools
 - Validate performance-based earthquake engineering approaches
 - Improve risk & loss modeling
- Will researchers be willing to gather this detailed data in the field?
- Example: GEM & PEER tools



Trend: Remote Sensing

- Data can be obtained remotely e.g. lidar, satellite imagery, Other satellite imagery e.g. DTMs, soil properties
- "Big data" can now be collected, stored and analysed relatively easily.
- This can feed directly into decision support



Trend: Data Visualization Framework

- California Clearinghouse approach utilizing UICDS
 - middleware developed by the U.S. Dept of Homeland Security to allow diverse datasets/organizations to share data without common platform or software



• Allows:

- data collection and ownership to remain with partner
- partner to set what data is visible to others
- Rapid sharing
- Approach = popular; implementation = challenging
- Requires metadata adaptor to the Incident Command Data Framework



Trend: Social Media & Remote Data

- Utilizing data from social media:
 - Paper by Mahalia Miller (at 10NCEE)
- Remote participation by experts or public:
 - Gleaning data from media reports, etc.
 - Example of crowdsourcing through GEOCAN after Haiti, NZ earthquakes
- This can feed directly into decision support





Trend: Increasing # of Field Teams

- As US reconnaissance funding models change, smaller and more numerous teams are participating in reconnaissance
 - EERI, TCLEE, GEER, PEER, ATC, ASCE, universities, professional societies, firms, etc.
- Broadening international collaboration and participation is also yielding additional researchers, data, tools, complexity, and opportunity.
- Reconnaissance teams for other disaster types are developing, can we learn from them?

Recommendations

- Data collection & visualization tools need to be:
 - Flexible and adaptable as IT functionality rapidly evolves
 - Platform and operating system independent
 - Functional with and without internet connectivity
 - Metadata and framework to facilitate sharing across disciplines, organizations and countries
- For systematic data collection to be possible, tools need to be flexible, able to accommodate detailed collection quickly, and widely adopted by the research community.

Damage/Loss data needed and collected by Insurance industry

- 1. What is damage/loss data?
- 2. For which perils do damage/loss data exist?
- 3. Who collects the damage/loss data?
- 4. Issues with DATA collected in the insurance industry
- 5. Accessibility of data
- **For which perils do damage/loss data exist?** In general data for weather related perils is much more plentiful than data from earthquakes.
- Who collects the damage/loss data? Data is collected by primary insurance companies and by risk modeling companies for different business reasons
 - o <u>Primary insurance companies</u>: claim settlement purposes (insurance companies) done by loss adjustors.
 - o Risk modeling companies:
 - for improving vulnerability functions for loss assessment
 - marketing purposes (risk modelers)
- Issues with DATA collected in the insurance industry are:
 - o DATA collected by insurance companies:
 - Usually good quality data, although the quality varies wildly from company to company.
 - sometimes biased by the strategy used for settling claims. Data usually not shared outside of the industry.
 - interest restricted to certain types of structures (insurable buildings in their books);
 - their interest is not holistic but often capped by the insurance limit (they might not care for losses beyond the limit they are responsible for);
 - Censored data: in many occasions, especially if claims are low, they might not conduct investigation but pay directly.
 - Detailed data about the damage that generate the loss is shared very rarely
 - o DATA collected by risk modeling companies:
 - Lack of time and support to conduct resource-intensive structured data collection
 - data is not standardized
 - Data is not collected in a systematic way. Biased towards more damaged buildings
 - Sometimes biased low because of lack of accessibility to structures

- Accessibility of data: In general data is held proprietary mostly for liability reasons (insurance companies) or to prevent accessibility by competitors (risk modelers). Circulation of insurance data within the industry does exist though:
 - From particular insurance companies TO consulting companies (for analysis and insight)
 - From (re)insurance companies TO (re)insurance companies (to gain trust, reinsurance)
 - From (re)insurance companies TO broking companies (reinsurance placement, consulting)
 - When data is shared externally it is only done at an aggregate level (minimal information about building type and no detailed information about exact location), which then loses significant potential for scientific and numerical analysis

Appendix III: Monday July 21 Discussion Summary Presentations & Notes

International Post-Earthquake Data Collection Workshop: Wrap-up

Agenda

- Breakout summaries (<45 min with discussion)
 - Five slides each breakout
 - Discussion after all three have been presented
- Next Steps (<1 hour)
 - Resolutions
 - Action items

Damage

PHYSICAL

WHY

- Identify Knowledge Gaps
- Conduct Forensic Studies
- Produce Damage Statistics
- Guide Response

WHAT

| CATEGORY | DATA | DEFINITION |
|----------|------|------------|
| | | |
| | | |
| | | |
| | | |

EARTHQUAKE

| CATEGORY | DATA | DEFINITION |
|------------|--------------------|------------|
| Earthquake | Name | |
| | Date | |
| | Ground Record(s) | |
| | Response Record(s) | |

STRUCTURE

| CATEGORY | DATA | DEFINITION |
|-----------|------------------------------|------------|
| Structure | ID | |
| | Coordinates | |
| | Address | |
| | Number of Stories | |
| | Occupancy | |
| | Number of Occupants | |
| | Number of Housing Units | |
| | Force-Resisting System(s) | |
| | Seismic Isolation | |
| | Mechanical Protection Device | |
| | Strengthening | |
| | Nonstructural Elements | |

STRUCTURE

| CATEGORY | DATA | DEFINITION |
|-----------|------------------------|------------|
| Structure | ID | |
| | Coordinates | |
| | Address | |
| | Number of Stories | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | Nonstructural Elements | |

23

CONSEQUENCES

| CATEGORY | DATA | DEFINITION |
|--------------|-----------------------|------------|
| Consequences | Survey Date | |
| | Tag | |
| | In Use or Not in Use | |
| | Damage Level | |
| | Damage Description | |
| | Cause of Damage | |
| | Tsunami Run-up Height | |
| | Crack / Damage Maps | |
| | Site / Soil Damage | |
| | Photos, Video, Media | |

18

HOW

- Representative samples
- Narratives with standard terms or keywords instead of or in addition to pull-down menus and check boxes?
- Explicit references to standards and ranking systems

Research Needs

- Define an index to quantify residual capacity
- Produce better simulation tools and models
- Identify factors contributing to resilience
- Develop better methods to estimate regional vulnerability

Summary of Impact Data Breakout Discussion

Mary Comerio, Moderator
With help from Judith Mitrani-Reiser

What are Critical Impact Sectors

- Housing
- Health
- Education
- Economy (Jobs)
- Environment
- Communication
- Lifeline operability
- Safety of Civil Society

All are interconnected

Holistic Overview:

Social

Economic

Natural Environment

What are Minimum Parameters for Baseline and Post-Event

Population impacted area (make up by census)

Urbanized vs non-urbanized

```
# Dwelling Units (+ types)
```

Hospitals/beds (+types)

Schools (+types)

Government buildings

Industrial/commercial buildings

Productivity

Ground Surface Changes

Lifeline Status

Non-Structural Damage

Data Collection Procedures and Use of International Protocols

- Data Protocols are critical
 - GEM consequence protocols, WHO reports, Sphere Standards, UNDAC other existing models
- Link Damage Survey to operational effectiveness —to define building functions by structure type and link loss/damage with disruption of service
- Engineering community needs to take ownership of functionality requirements to improve Performance Based Design

Value of Data Time Sensitivity of Data

- Overcome barriers to sharing by demonstrating community benefits
 - Examples NZ Geotech/ACC data, Hur. Sandy NYC hospitals shared beds avail daily
- Base Line (pre-event) AND Change in event
- Timeframe for data vary by sector
- Note what is perishable. Because of relation to functioning vs recovery

Recovery and Reconstruction

Participants David Johnston (NZ)

Mike Stannard (NZ)

Marco Di Ludovico (IT)

Juan Carlos de la Llera (CHILE)

Tomohisa Mukai (JP)

Scott Miles (US)

Vesna Terzic (US)

Ayhan Irfanoglu (US)

Ken Elwood (U. Auckland)

Moderator Stephanie Chang

Student/recorder Frederic Marquis

Why collect data? (value)

* "How is the recovery going?" (informing decision-makers)

Social Basic services Wellbeing, risk perception Data Physical Code What do you do Can the building be with the changes used? building? (demolition decision) Hard Reconstruction - Recovery Emergency

Time

What minimum types of data are required?

Categories

- 1. Damage
- 2. Rebuilding
- 3. Functionality
- 4. Decisions
- 5. Economics
- 6. Behavior
- 7. Population
- 8. Perceptions

2. Rebuilding

- % buildings... (by type, loc., T)
 - Assessed
 - Permitted
 - Repaired
 - Retrofitted
 - Demolished
 - Rebuilt
 - Occupied
- Trends (multiple/proxy/ simplified)
- Community changes

How to Collect and Share Data (principles, ideas)

- Balance data for informing decision-makers with data for research
- Interviews with staff (as well as population)
- Multiple sources, triangulation (e.g., rebuilding)
- Build in links (e.g., buildings with owners/tenants; business actions/time/impact)
- Data has to be made public and available

Breakout Session - Recovery and Reconstruction (Theme #3)

Post-Earthquake Data Collection Workshop Anchorage, Alaska July 20-21, 2014

Moderator: Stephanie Chang (UBC)
Student: Frederic Marquis (UBC)

Participants: David Johnston (NZ), Mike Stannard (NZ), Marco Di Ludovico(IT), Juan Carlos

de la Liera (CHILE), Scott Miles (US), Vesna Terzic (US), Tomohisa Mukai (JP),

Ayhan Irfanoglu (US), Ken Elwood (U. Auckland)

What minimum types of data are required?

Categories

1. Damage

- Detailed building geometry, materials, soils properties and damage data to fill gaps of building performance with the level of shaking experienced by the building.
- b. Amount of damage for members and damaged building by experimental tests
- c. Repair costs (structural members, non-structural members, damage location in the building) (individual building or community)
- d. Effectiveness of mitigation

2. Rebuilding

- a. % buildings
 - i. Assessed
 - ii. Permitted
 - iii. Repaired
 - iv. Retrofitted
 - v. Demolished
 - vi. Rebuilt
 - vii. Occupied
- b. Trends (multiple indicators, proxy indicators, simplified information)
- c. Community changes (e.g. spatial differences)

3. Functionality

- a. Post-EQ functionality not to shut down after EQ
- b. Occupancy of public buildings (e.g. hospitals)
- c. Lifelines recovery (different indices) and lifeline interdependencies. How the system works (lifelines, healthcare system, etc.)

4. Decisions

- a. Government (Policies, Legislation, Recovery Authority, Building Codes, Coding System, Communication to Population)
- b. Building Owners
- c. Impacts (including code changes and retrofits)

5. Economics

- a. Business database: type of business, downtime, timeline of inspection, type of data collected, time to initiate repair, time to repair, sequence of actions and their durations prior to repair of the buildings, tags, business interruption losses.
- b. Data to link types of businesses to dependency on their buildings to inform the need for relative reconstruction speed versus alternative work arrangements
- c. Data to link tenants to buildings to building owners and then track during recovery
- d. Businesses by place and time (number, open/close, % functional, \$/% output, jobs)
- e. Total jobs (new, lost)

6. Behavior

a. CCTV footage inside buildings during earthquakes and along sidewalks/streets

7. Population

- a. Population by place and time (and movements)
- b. School enrolment

8. Perceptions

- a. Detailed data on the response of people at different levels (individuals, communities, etc.) and their risk perception and how it has evolved in time.
- b. Psycho-social data of people's perception of loss and reconstruction of their built environment (e.g. "How much change is too much?")
- c. Comfort level, wellbeing, acceptable damage level and comprehension of risks at the community level.
- d. Effectiveness of mitigation

Value of the data

- How's the recovery going? (informing decision-makers)
- Matrix

| Type of Data | Social | Basic services | Wellbeing, risk perception | |
|--------------|----------|---------------------------------|--|-----------------|
| | Physical | Can the building be used? | What do you do with the building? (demolition decision) | Code changes |
| | Hard | | | |
| | | Emergency | Reconstruction - | Recovery |

Time

- Balance between research and decision-making needs
- Decision-making in future events

How to collect and share data

- Interviews with local staff, returnees, etc.
- Data has to be public and available
- Multiple sources, triangulation (e.g. rebuilding)

Summary Notes from Tuesday Comments & Participant Observations

- We need to start speaking to data analysis experts because approaches are now often more schema-less. Data searching through meta-data, searched and filtered by modern and novel tools at the cutting edge of data.
- All of the groups have different outcomes and thus the hard data commonalities seem to be the location and time of collection and occupancy type.
 - o Maybe that there are more commonalities but need to study further?
- The commonality may be the aim of having all teams on recon missions are collecting a matrix of data that has a similar framework. Is this the main outcome of this exercise?
 An agreement to a collaborative approach and procedure?
- Need to align each data to its purpose. Could this be the unifier that all data is linked by purpose for its use?
- Time is correlated to the purpose. Questions change over time. By segmenting in time, there may be a way to look at frameworks that change by time? (Many at workshop agreed with this statement.)
- Countries will act in their own ways, but it would be nice to validate this data in a common way. Protocols could ensure that data is valuable.
- Could we use Christchurch as an after the fact case study to better understand gaps in data when it was gathered by fragmented and various groups?
- What data is available before the event? This should be considered as the fundamental data in advance that we measure how it changes after the earthquake. A study of recent 2010 and 2011 earthquakes could be done in this regard???
- Its all about the deltas? Standards may help if we were working together and combining recon with the importance of data for local community response and recovery
- Self assigned quality score for data collection? Using cross checks? Duplicate data
 collection by multiple researchers for redundancy? A variety of solutions could be
 devised to validate field data and add error bar to damage ratings or values. Multiple
 teams should meet to calibrate and benchmark collection before they go into the field.
 This could help to achieve data consistency.
- Common themes could also be occupancy type. See above.
- Questions about how quick to gather data. Don't want to be in the way of responders but perhaps some quick observations can be made to make a quick assessment, then a later group can get more data if suitable. This does go against having quick teams add functionality questions to avoid needing to do interviews
- Consider use of GIS and geospatial data.
 - What is location? Need to be clear on these items. (coordinates of building or where recording data, etc) Also standards on other meta data to be clear on accurate location.
- Time and Purpose should be more important from perishable data.
- Structural damage is only tip of iceberg. More work is needed on nonstructural, networks, function, etc. Model calibration for risk, function, interconnection, network models, not just structural models.
- Need common tools that are easy to collect by many, not just a select few. This could also include crowd-sourced data from the public.
- Phases matter. The recovery phase is arguably more important than the first response phase. We need to add data from others, not just what we can gather. Must think

bigger beyond engineers. The focus of our efforts and discussion should be around standardizing process to get good data when others gather it, not what should be collected.

- Work needs to be done to come to consensus on damage levels (standardization).
- This group needs to focus on realistic resolutions on what we (internally) can do as a group, instead of beyond to major other stakeholders.
- It is important to move away from data as a currency, how it is used matters. Our creativity in its use should be the power, not the raw data. This can be seen in the life sciences arena where data sharing is commonplace and required. This needs to be a culture shift.
- Legal issues conflict in Japan and many other countries.
- Concepts of data collection and sharing is overwhelming and time consuming. A clearer, more definite outcome would help scale and clarify the scope of what we are doing.
 Countries and engineers in countries after earthquakes are so busy that it is hard to share, even several years after the event, while they are still trying to gather and understand data in their own country for their own purposes.
- How do we share the legacy of what we learned for researchers in the future? Can we create a document, activity or other items that can do this collectivity between our countries? Can we capture common best practices from all these countries who have recently been impacted?